



TRANSPORTATION CABINET

Frankfort, Kentucky 40622
www.transportation.ky.gov/

Steven L. Beshear
Governor

Michael W. Hancock, P.E.
Secretary

October 14, 2014

CALL NO. 106
CONTRACT ID NO. 141064
ADDENDUM # 1

Subject: Laurel County, HSIP 5292 (006)
Letting October 24, 2014

- (1) Revised - Plan Sheet - R2h
- (2) Deleted - Page 181 of 221

Proposal revisions are available at <http://transportation.ky.gov/Construction-Procurement/>.

Plan revisions are available at <http://www.lynnimaging.com/kytransportation/>.

If you have any questions, please contact us at 502-564-3500.

Sincerely,

A handwritten signature in blue ink that reads "Diana Castle Radcliffe".

Diana Castle Radcliffe
Director
Division of Construction Procurement

DR:ks
Enclosures



An Equal Opportunity Employer M/F/D

COUNTY OF	ITEM NO.	SHEET NO.
LAUREL	11-904.01	R2H

REVISED 10-14-2014

GENERAL NOTES

N.G.S. (U.S.G.S.) BENCH MARKS

DO NOT DISTURB N.G.S. (U.S.G.S.) BENCH MARKS IN ANY MANNER UNLESS DIRECTED BY THE ENGINEER.

DEPARTMENT OF THE ARMY PERMIT AND WATER QUALITY CERTIFICATION APPROVALS

A DEPARTMENT OF THE ARMY (DA) PERMIT, WHICH MAY REQUIRE APPROVAL OF A STATE WATER QUALITY CERTIFICATION FROM THE KENTUCKY DIVISION OF WATER, REGULATES THIS PROJECT AT ONE OR MORE LOCATIONS. PERFORM ALL APPLICABLE WORK IN COMPLIANCE WITH THE CONDITIONS STATED IN THE DA PERMIT AND THE APPROVED WATER QUALITY CERTIFICATION. POST A COPY OF THE DA PERMIT AND THE WATER QUALITY CERTIFICATION IN A CONSPICUOUS PLACE AT THE PROJECT SITE. IF A DA PERMIT OR WATER QUALITY CERTIFICATION APPROVAL IS PENDING, DO NOT WORK IN OR DISTURB THE DESIGNATED AREA(S) UNTIL OBTAINING THE APPROPRIATE APPROVAL(S). REFER TO NOTICE(S) CONTAINED IN THE CONTRACT BID PROPOSAL FOR DESIGNATED AREA(S) WHERE WORK IS PROHIBITED BY THE ABSENCE OF APPROVAL.

COMPACTION OF ASPHALT MIXTURES

WILL ACCEPT THE COMPACTION OF ASPHALT MIXTURES FURNISHED FOR DRIVING LANES AND RAMPS AT ONE INCH (25 MM) OR GREATER ON THIS PROJECT BY OPTION A ACCORDING TO SUBSECTIONS 402 AND 403 OF THE CURRENT STANDARD SPECIFICATIONS. USE JOINT CORES AS DESCRIBED IN SUBSECTION 402.03.02 FOR SURFACE MIXTURES ONLY. WILL ACCEPT THE COMPACTION OF ALL OTHER ASPHALT MIXTURES BY OPTION B.

STANDARD DRAWINGS

STANDARD DRAWINGS ARE NOT ATTACHED TO THESE PLANS, A STANDARD DRAWING BOOK AND THE HEADWALL SUPPLEMENTAL BOOK MAY BE OBTAINED FROM THE POLICY SUPPORT BRANCH OF THE DEPARTMENT OF ADMINISTRATIVE SERVICES IN FRANKFORT, KY. AT (502) 564-3670.

BEFORE YOU DIG

THE CONTRACTOR IS INSTRUCTED TO CALL 1-800-752-6007 TO REACH KY 811, THE ONE-CALL SYSTEM FOR INFORMATION ON THE LOCATION OF EXISTING UNDERGROUND UTILITIES. THE CALL IS TO BE PLACED A MINIMUM OF TWO (2) AND NO MORE THAN TEN (10) BUSINESS DAYS PRIOR TO EXCAVATION. THE CONTRACTOR SHOULD BE AWARE THAT OWNERS OF UNDERGROUND FACILITIES ARE NOT REQUIRED TO BE MEMBERS OF THE KY 811 ONE-CALL BEFORE-U-DIG (BUD) SERVICE. THE CONTRACTOR MUST COORDINATE EXCAVATION WITH THE UTILITY OWNERS, INCLUDING THOSE WHOM DO NOT SUBSCRIBE TO KY 811. IT MAY BE NECESSARY FOR THE CONTRACTOR TO CONTACT THE COUNTY COURT CLERK TO DETERMINE WHAT UTILITY COMPANIES HAVE FACILITIES IN THE AREA.

ROADBED NOTE, EMBANKMENT-IN-PLACE

USE EMBANKMENT-IN-PLACE WITH A MINIMUM C.B.R. VALUE OF 2 OR GREATER IN THE TOP 12 INCHES (300 MM) OF ROADBED IN CUT AND FILL SECTIONS.

SPECIAL NOTE FOR PERFORATED PIPE - 4 INCH FOR AGGREGATE BACKFILLED TRENCH

APPLY SECTION 704, UNDERDRAINS, OF THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS EXCEPT USE COARSE AGGREGATE FOR THE BACKFILL AND WRAP THE AGGREGATE WITH GEOTEXTILE FABRIC AS SHOWN IN THE EDGE DRAIN DETAILS. APPLY SECTION 214.03.04 OF THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS EXCEPT USE TYPE IV FABRIC. PLACE THE FABRIC AGAINST THE SIDES AND BOTTOM OF THE TRENCH WITH SUITABLE EQUIPMENT WITHOUT STRETCHING IT. THE FILTER AGGREGATE SHOULD BE PLACED IN THE TRENCH WITHOUT DAMAGING, DISPLACING, OR DISLODGING THE FABRIC. FOR NEW CONSTRUCTION THE FABRIC SHOULD BE PLACED UNDER THE DRAINAGE BLANKET, EXTEND THROUGH THE TRENCH AND WRAP BACK ON TOP OF THE DRAINAGE BLANKET AFTER IT IS PLACED. FOR RETROFIT SITUATIONS THE FABRIC SHOULD BE OVERLAPPED AT THE TOP OF THE BACK-FILLED TRENCH.

WINTER CLOSDOWN

ANY ASPHALT CONCRETE BASE AND/OR SURFACE COURSE USED AS A RIDING SURFACE EXPOSED TO TRAFFIC DURING WINTER CLOSDOWN PERIODS SHALL CONTAIN NATURAL, CONGLOMERATE, CRUSHED SLAG, CRUSHED GRANITE OR CRUSHED SANDSTONE SAND IN THE PROPORTION OF NO LESS THAN 25% OF THE TOTAL COMBINED COARSE AND FINE AGGREGATE.

TRAFFIC NOTE

SEE THE PLANS FOR MAINTENANCE OF TRAFFIC NOTES AND DETOUR SIGNING PLAN.

EROSION CONTROL

USE SEED MIXTURE TYPE III. QUANTITIES FOR TEMPORARY EROSION CONTROL BLANKET (TECB) ARE LISTED UNDER BID ITEM - EROSION CONTROL BLANKET.

EXISTING LANDSCAPE MATERIAL

DO NOT DISTURB LANDSCAPE PLANTS UNLESS ABSOLUTELY NECESSARY.

DO NOT TO DISTURB ANY PLANTS WITHOUT PRIOR APPROVAL OF THE PROJECT ENGINEER.

THE PROJECT ENGINEER SHALL NOTIFY THE DISTRICT AGRONOMIST FOR POSSIBLE DEPARTMENT SALVAGE OF ANY PLANTS NEEDING REMOVAL.

SPECIAL NOTES

Special Note 1I Portable Changeable Message Signs

Special Note 1ID Rock Blasting

Special Note 1IF For Turf Reinforcing Mat

Special Note for Barcode Label on Permanent Signs Effective 10.25.2013 Letting Revised Item Number

NOTES SPECIFIC TO PROJECT

SUBGRADE STABILIZATION

A ONE-FOOT WORKING PLATFORM WILL BE REQUIRED IN AREAS WHERE THE SUBGRADE IS SOFT AND/OR SATURATED. THE PLATFORM WILL CONSIST OF ONE FOOT OF KENTUCKY COARSE AGGREGATE # 2's, 3's OR 23's, IN ACCORDANCE WITH SECTION 805 OF THE CURRENT STANDARD SPECIFICATIONS, WRAPPED WITH GEOTEXTILE FABRIC, TYPE IV, IN ACCORDANCE WITH SECTION 214 & 843 OF THE CURRENT STANDARD SPECIFICATIONS. THE WORKING PLATFORM WILL BE REQUIRED DIRECTLY BENEATH THE ROADWAY TEMPLATE AND EXTENDING UNDER THE CURB AND GUTTER. THE WORKING PLATFORM MAY ALSO SERVE AS A DRAINAGE BLANKET BY PLACING SHORT SECTIONS OF PERFORATED DRAIN PIPE (4 FEET LONG) INTO THE BOTTOM OF THE GRANULAR MATERIAL. THE DRAINPIPE SHOULD BE LOCATED AT THE DROP INLETS. THE ACTUAL LOCATIONS AND THICKNESS SHALL BE DETERMINED BY THE ENGINEER DURING CONSTRUCTION AND MAY DEPEND ON SEASONAL FLUCTUATIONS IN THE WATER TABLE. FOR QUANTITY ESTIMATION PURPOSES, THIS TREATMENT SHALL BE INCLUDED FOR 800 LINEAR FEET OF STABILIZATION.

CORING HOLE THROUGH EX. BRICK RETAINING WALL

ALL WORK ASSOCIATED WITH CORING HOLE THROUGH RETAINING WALL SHALL BE CONSIDERED INCIDENTAL TO BID ITEM STORM SEWER PIPE - 12".

KY 1006 / KY 363

GENERAL & SPECIFIC NOTES

BURGESS & NIPLÉ

FILE NAME: G:\P\WORK\MWILEY\0148854\RO0202CHN_REVISED.DGN

USER: Mwiley
DATE PLOTTED: September 22, 2014

E-SHEET NAME:

MicroStation v8.11.7.180

COUNTY OF	ITEM NO.	SHEET NO.
LAUREL	11-904.01	R2H

REVISED 10-14-2014

GENERAL NOTES

N.G.S. (U.S.G.S.) BENCH MARKS

DO NOT DISTURB N.G.S. (U.S.G.S.) BENCH MARKS IN ANY MANNER UNLESS DIRECTED BY THE ENGINEER.

DEPARTMENT OF THE ARMY PERMIT AND WATER QUALITY CERTIFICATION APPROVALS

A DEPARTMENT OF THE ARMY (DA) PERMIT, WHICH MAY REQUIRE APPROVAL OF A STATE WATER QUALITY CERTIFICATION FROM THE KENTUCKY DIVISION OF WATER, REGULATES THIS PROJECT AT ONE OR MORE LOCATIONS. PERFORM ALL APPLICABLE WORK IN COMPLIANCE WITH THE CONDITIONS STATED IN THE DA PERMIT AND THE APPROVED WATER QUALITY CERTIFICATION. POST A COPY OF THE DA PERMIT AND THE WATER QUALITY CERTIFICATION IN A CONSPICUOUS PLACE AT THE PROJECT SITE. IF A DA PERMIT OR WATER QUALITY CERTIFICATION APPROVAL IS PENDING, DO NOT WORK IN OR DISTURB THE DESIGNATED AREA(S) UNTIL OBTAINING THE APPROPRIATE APPROVAL(S). REFER TO NOTICE(S) CONTAINED IN THE CONTRACT BID PROPOSAL FOR DESIGNATED AREA(S) WHERE WORK IS PROHIBITED BY THE ABSENCE OF APPROVAL.

COMPACTION OF ASPHALT MIXTURES

WILL ACCEPT THE COMPACTION OF ASPHALT MIXTURES FURNISHED FOR DRIVING LANES AND RAMPS AT ONE INCH (25 MM) OR GREATER ON THIS PROJECT BY OPTION A ACCORDING TO SUBSECTIONS 402 AND 403 OF THE CURRENT STANDARD SPECIFICATIONS. USE JOINT CORES AS DESCRIBED IN SUBSECTION 402.03.02 FOR SURFACE MIXTURES ONLY. WILL ACCEPT THE COMPACTION OF ALL OTHER ASPHALT MIXTURES BY OPTION B.

STANDARD DRAWINGS

STANDARD DRAWINGS ARE NOT ATTACHED TO THESE PLANS, A STANDARD DRAWING BOOK AND THE HEADWALL SUPPLEMENTAL BOOK MAY BE OBTAINED FROM THE POLICY SUPPORT BRANCH OF THE DEPARTMENT OF ADMINISTRATIVE SERVICES IN FRANKFORT, KY. AT (502) 564-3670.

BEFORE YOU DIG

THE CONTRACTOR IS INSTRUCTED TO CALL 1-800-752-6007 TO REACH KY 811, THE ONE-CALL SYSTEM FOR INFORMATION ON THE LOCATION OF EXISTING UNDERGROUND UTILITIES. THE CALL IS TO BE PLACED A MINIMUM OF TWO (2) AND NO MORE THAN TEN (10) BUSINESS DAYS PRIOR TO EXCAVATION. THE CONTRACTOR SHOULD BE AWARE THAT OWNERS OF UNDERGROUND FACILITIES ARE NOT REQUIRED TO BE MEMBERS OF THE KY 811 ONE-CALL BEFORE-U-DIG (BUD) SERVICE. THE CONTRACTOR MUST COORDINATE EXCAVATION WITH THE UTILITY OWNERS, INCLUDING THOSE WHOM DO NOT SUBSCRIBE TO KY 811. IT MAY BE NECESSARY FOR THE CONTRACTOR TO CONTACT THE COUNTY COURT CLERK TO DETERMINE WHAT UTILITY COMPANIES HAVE FACILITIES IN THE AREA.

ROADBED NOTE, EMBANKMENT-IN-PLACE

USE EMBANKMENT-IN-PLACE WITH A MINIMUM C.B.R. VALUE OF 2 OR GREATER IN THE TOP 12 INCHES (300 MM) OF ROADBED IN CUT AND FILL SECTIONS.

SPECIAL NOTE FOR PERFORATED PIPE - 4 INCH FOR AGGREGATE BACKFILLED TRENCH

APPLY SECTION 704, UNDERDRAINS, OF THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS EXCEPT USE COARSE AGGREGATE FOR THE BACKFILL AND WRAP THE AGGREGATE WITH GEOTEXTILE FABRIC AS SHOWN IN THE EDGE DRAIN DETAILS. APPLY SECTION 214.03.04 OF THE CURRENT EDITION OF THE STANDARD SPECIFICATIONS EXCEPT USE TYPE IV FABRIC. PLACE THE FABRIC AGAINST THE SIDES AND BOTTOM OF THE TRENCH WITH SUITABLE EQUIPMENT WITHOUT STRETCHING IT. THE FILTER AGGREGATE SHOULD BE PLACED IN THE TRENCH WITHOUT DAMAGING, DISPLACING, OR DISLODGING THE FABRIC. FOR NEW CONSTRUCTION THE FABRIC SHOULD BE PLACED UNDER THE DRAINAGE BLANKET, EXTEND THROUGH THE TRENCH AND WRAP BACK ON TOP OF THE DRAINAGE BLANKET AFTER IT IS PLACED. FOR RETROFIT SITUATIONS THE FABRIC SHOULD BE OVERLAPPED AT THE TOP OF THE BACK-FILLED TRENCH.

WINTER CLOSEDOWN

ANY ASPHALT CONCRETE BASE AND/OR SURFACE COURSE USED AS A RIDING SURFACE EXPOSED TO TRAFFIC DURING WINTER CLOSEDOWN PERIODS SHALL CONTAIN NATURAL, CONGLOMERATE, CRUSHED SLAG, CRUSHED GRANITE OR CRUSHED SANDSTONE SAND IN THE PROPORTION OF NO LESS THAN 25% OF THE TOTAL COMBINED COARSE AND FINE AGGREGATE.

TRAFFIC NOTE

SEE THE PLANS FOR MAINTENANCE OF TRAFFIC NOTES AND DETOUR SIGNING PLAN.

EROSION CONTROL

USE SEED MIXTURE TYPE III. QUANTITIES FOR TEMPORARY EROSION CONTROL BLANKET (TECB) ARE LISTED UNDER BID ITEM - EROSION CONTROL BLANKET.

EXISTING LANDSCAPE MATERIAL

DO NOT DISTURB LANDSCAPE PLANTS UNLESS ABSOLUTELY NECESSARY.

DO NOT TO DISTURB ANY PLANTS WITHOUT PRIOR APPROVAL OF THE PROJECT ENGINEER.

THE PROJECT ENGINEER SHALL NOTIFY THE DISTRICT AGRONOMIST FOR POSSIBLE DEPARTMENT SALVAGE OF ANY PLANTS NEEDING REMOVAL.

SPECIAL NOTES

Special Note 1I Portable Changeable Message Signs

Special Note 1ID Rock Blasting

Special Note 1IF For Turf Reinforcing Mat

NOTE DELETED.

Special Note for Barcode Label on Permanent Signs Effective 10.25.2013 Letting Revised Item Number

NOTES SPECIFIC TO PROJECT

SUBGRADE STABILIZATION

A ONE-FOOT WORKING PLATFORM WILL BE REQUIRED IN AREAS WHERE THE SUBGRADE IS SOFT AND/OR SATURATED. THE PLATFORM WILL CONSIST OF ONE FOOT OF KENTUCKY COARSE AGGREGATE # 2's, 3's OR 23's, IN ACCORDANCE WITH SECTION 805 OF THE CURRENT STANDARD SPECIFICATIONS, WRAPPED WITH GEOTEXTILE FABRIC, TYPE IV, IN ACCORDANCE WITH SECTION 214 & 843 OF THE CURRENT STANDARD SPECIFICATIONS. THE WORKING PLATFORM WILL BE REQUIRED DIRECTLY BENEATH THE ROADWAY TEMPLATE AND EXTENDING UNDER THE CURB AND GUTTER. THE WORKING PLATFORM MAY ALSO SERVE AS A DRAINAGE BLANKET BY PLACING SHORT SECTIONS OF PERFORATED DRAIN PIPE (4 FEET LONG) INTO THE BOTTOM OF THE GRANULAR MATERIAL. THE DRAINPIPE SHOULD BE LOCATED AT THE DROP INLETS. THE ACTUAL LOCATIONS AND THICKNESS SHALL BE DETERMINED BY THE ENGINEER DURING CONSTRUCTION AND MAY DEPEND ON SEASONAL FLUCTUATIONS IN THE WATER TABLE. FOR QUANTITY ESTIMATION PURPOSES, THIS TREATMENT SHALL BE INCLUDED FOR 800 LINEAR FEET OF STABILIZATION.

CORING HOLE THROUGH EX. BRICK RETAINING WALL

ALL WORK ASSOCIATED WITH CORING HOLE THROUGH RETAINING WALL SHALL BE CONSIDERED INCIDENTAL TO BID ITEM STORM SEWER PIPE - 12".

KY 1006 / KY 363

GENERAL & SPECIFIC NOTES

BURGESS & NIPLÉ

FILE NAME: G:\P\WORK\MWILEY\00148854\RO0202CHN_REVISED.DGN

USER: Mwiley
DATE PLOTTED: September 22, 2014

E-SHEET NAME:

MicroStation v8.1i.7.180