

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

SUBSECTION:	102.07.01 General.
REVISION:	Replace the first sentence with the following: Submit the Bid Proposal on forms furnished on the Department internet website (http://transportation.ky.gov/contract/), including the Bid Packet and disk created from the Expedite Bidding Program.
SUBSECTION:	102.07.02 Computer Bidding.
REVISION:	Replace the first paragraph with the following: Subsequent to ordering a Bid Proposal for a specific project, use the Department's Expedite Bidding Program on the internet website of the Department of Highways, Division of Construction Procurement (http://transportation.ky.gov/contract/). Download the bid file from the Department's website to prepare a Bid Proposal for submission to the Department. Include the completed Bid Packet produced by the Expedite Bidding Program in the Bid Proposal and submit it along with the disk created by said program. Replace the second paragraph with the following: In case of a dispute, the printed Bid Proposal and bid item sheets created by the Expedite Bidding Program take precedence over any bid submittal.
SUBSECTION:	102.08 IRREGULAR BID PROPOSALS.
REVISION:	Replace point four of the first paragraph with the following: 4) fails to submit a disk created from the Expedite Bidding Program. Replace point one of the second paragraph with the following: 1) when the Bid Proposal is on a form other than that furnished by the Department or printed from other than the Expedite Bidding Program, or when the form is altered or any part is detached; or
SUBSECTION:	103.02 AWARD OF CONTRACT.
REVISION:	Replace the first sentence of the third paragraph with the following: The Department will normally award the Contract within 10 working days after the date of receiving Bid Proposals unless the Department deems it best to hold the Bid Proposals of any or all bidders for a period not to exceed 60 calendar days for final disposition of award.
SUBSECTION:	106.10 FIELD WELDER CERTIFICATION REQUIREMENTS.
REVISION:	Insert the following sentence before the first sentence of the first paragraph: All field welding must be performed by a certified welder unless otherwise noted.
SUBSECTION:	112.03.12 Project Traffic Coordinator (PTC).
REVISION:	Add the following at the end of the subsection: After October 1, 2008 the Department will require the PTC to have successfully completed the applicable qualification courses. Personnel that have not successfully completed the applicable courses by that date will not be considered qualified. Prior to October 1, 2008, conform to Subsection 108.06 A) and ensure the designated PTC has sufficient skill and experience to properly perform the task.
SUBSECTION:	213.03.05 Temporary Control Measures.
PART:	F) Temporary Mulch.
REVISION:	Replace the last sentence with the following: Place temporary mulch to an approximate 2-inch loose depth (2 tons per acre) and anchor it into the soil by mechanically crimping it into the soil surface or applying tackifier to provide a protective cover. Regardless of the anchoring method used, ensure the protective cover holds until disturbance is required or permanent controls are in installed.

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

SUBSECTION: 402.05.02 Asphalt Mixtures and Mixtures With RAP.

PART: Lot Pay Adjustment Schedule, Compaction Option A, Base and Binder Mixtures

TABLES: VMA, AV, and LANE DENSITY

REVISION: Replace the VMA, AV, and LANE DENSITY tables with the following:

VMA	
Pay Value	Deviation From Minimum
1.00	≤ 0.5 below min.
0.95	0.6-1.0 below min.
0.90	1.1-1.5 below min.
⁽¹⁾	> 1.5 below min.

AV		
Pay Value	Test Result (%)	
	ESAL Class 2	ESAL Class 3 or 4
1.00	3.0-5.0	3.0-5.0
1.00 + 0.1 (AV-3.0)	1.5-2.9	2.0-2.9
1.00 + 0.1 (5.0-AV)	5.1-6.0	5.1-6.0
0.75	6.1-6.5	----
⁽¹⁾	< 1.5 or > 6.5	< 2.0 or > 6.0

LANE DENSITY		
Pay Value	Test Result (%)	
	ESAL Class 2	ESAL Class 3 or 4
1.00	92.0-96.5	92.0-96.5
0.95	91.0-91.9	91.0-91.9
0.90	90.0-90.9 or 96.6-97.0	90.0-90.9 or 96.6-97.0
0.85	97.1-98.5	----
0.75	89.0-89.9	----
⁽¹⁾	< 89.0 or > 98.5	< 90.0 or > 97.0

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

SUBSECTION:	402.05.02 Asphalt Mixtures and Mixtures With RAP.																																																															
PART:	Lot Pay Adjustment Schedule, Compaction Option A, Surface Mixtures																																																															
TABLES:	AV, LANE DENSITY, and JOINT DENSITY																																																															
REVISION:	Replace the AV, LANE DENSITY, and JOINT DENSITY tables with the following:																																																															
<table><tr><th colspan="3">AV</th></tr><tr><th rowspan="2">Pay Value</th><th colspan="2">Test Result (%)</th></tr><tr><th>ESAL Class 2</th><th>ESAL Class 3 or 4</th></tr><tr><td>1.00</td><td>3.0-5.0</td><td>3.0-5.0</td></tr><tr><td>1.00 + 0.1 (AV-3.0)</td><td>1.5-2.9</td><td>2.0-2.9</td></tr><tr><td>1.00 + 0.1 (5.0-AV)</td><td>5.1-6.0</td><td>5.1-6.0</td></tr><tr><td>0.75</td><td>6.1-6.5</td><td>----</td></tr><tr><td>⁽¹⁾</td><td>< 1.5 or > 6.5</td><td>< 2.0 or > 6.0</td></tr></table> <table><tr><th colspan="3">LANE DENSITY</th></tr><tr><th rowspan="2">Pay Value</th><th colspan="2">Test Result (%)</th></tr><tr><th>ESAL Class 2</th><th>ESAL Class 3 or 4</th></tr><tr><td>1.00</td><td>92.0-96.5</td><td>92.0-96.5</td></tr><tr><td>0.95</td><td>91.0-91.9</td><td>91.0-91.9</td></tr><tr><td>0.90</td><td>90.0-90.9 or 96.6-97.0</td><td>90.0-90.9 or 96.6-97.0</td></tr><tr><td>0.85</td><td>97.1-98.5</td><td>----</td></tr><tr><td>0.75</td><td>89.0-89.9</td><td>----</td></tr><tr><td>⁽¹⁾</td><td>< 89.0 or > 98.5</td><td>< 90.0 or > 97.0</td></tr></table> <table><tr><th colspan="2">JOINT DENSITY</th></tr><tr><th>Pay Value</th><th>Test Result (%)</th></tr><tr><td>1.00</td><td>89.0-96.5</td></tr><tr><td>0.95</td><td>88.0-88.9</td></tr><tr><td>0.90</td><td>87.0-87.9 or 96.6-97.0</td></tr><tr><td>0.75</td><td>< 87.0 or > 97.0</td></tr></table>				AV			Pay Value	Test Result (%)		ESAL Class 2	ESAL Class 3 or 4	1.00	3.0-5.0	3.0-5.0	1.00 + 0.1 (AV-3.0)	1.5-2.9	2.0-2.9	1.00 + 0.1 (5.0-AV)	5.1-6.0	5.1-6.0	0.75	6.1-6.5	----	⁽¹⁾	< 1.5 or > 6.5	< 2.0 or > 6.0	LANE DENSITY			Pay Value	Test Result (%)		ESAL Class 2	ESAL Class 3 or 4	1.00	92.0-96.5	92.0-96.5	0.95	91.0-91.9	91.0-91.9	0.90	90.0-90.9 or 96.6-97.0	90.0-90.9 or 96.6-97.0	0.85	97.1-98.5	----	0.75	89.0-89.9	----	⁽¹⁾	< 89.0 or > 98.5	< 90.0 or > 97.0	JOINT DENSITY		Pay Value	Test Result (%)	1.00	89.0-96.5	0.95	88.0-88.9	0.90	87.0-87.9 or 96.6-97.0	0.75	< 87.0 or > 97.0
AV																																																																
Pay Value	Test Result (%)																																																															
	ESAL Class 2	ESAL Class 3 or 4																																																														
1.00	3.0-5.0	3.0-5.0																																																														
1.00 + 0.1 (AV-3.0)	1.5-2.9	2.0-2.9																																																														
1.00 + 0.1 (5.0-AV)	5.1-6.0	5.1-6.0																																																														
0.75	6.1-6.5	----																																																														
⁽¹⁾	< 1.5 or > 6.5	< 2.0 or > 6.0																																																														
LANE DENSITY																																																																
Pay Value	Test Result (%)																																																															
	ESAL Class 2	ESAL Class 3 or 4																																																														
1.00	92.0-96.5	92.0-96.5																																																														
0.95	91.0-91.9	91.0-91.9																																																														
0.90	90.0-90.9 or 96.6-97.0	90.0-90.9 or 96.6-97.0																																																														
0.85	97.1-98.5	----																																																														
0.75	89.0-89.9	----																																																														
⁽¹⁾	< 89.0 or > 98.5	< 90.0 or > 97.0																																																														
JOINT DENSITY																																																																
Pay Value	Test Result (%)																																																															
1.00	89.0-96.5																																																															
0.95	88.0-88.9																																																															
0.90	87.0-87.9 or 96.6-97.0																																																															
0.75	< 87.0 or > 97.0																																																															
SUBSECTION:	402.05.02 Asphalt Mixtures and Mixtures With RAP.																																																															
PART:	Lot Pay Adjustment Schedule, Compaction Option B Mixtures																																																															
TABLE:	AV																																																															
REVISION:	Replace the AV table with the following:																																																															
<table><tr><th colspan="3">AV</th></tr><tr><th rowspan="2">Pay Value</th><th colspan="2">Test Result (%)</th></tr><tr><th>ESAL Class 2</th><th>ESAL Class 3 or 4</th></tr><tr><td>1.00</td><td>3.0-5.0</td><td>3.0-5.0</td></tr><tr><td>1.00 + 0.1 (AV-3.0)</td><td>1.5-2.9</td><td>2.0-2.9</td></tr><tr><td>1.00 + 0.1 (5.0-AV)</td><td>5.1-6.0</td><td>5.1-6.0</td></tr><tr><td>0.75</td><td>6.1-6.5</td><td>----</td></tr><tr><td>⁽²⁾</td><td>< 1.5 or > 6.5</td><td>< 2.0 or > 6.0</td></tr></table>				AV			Pay Value	Test Result (%)		ESAL Class 2	ESAL Class 3 or 4	1.00	3.0-5.0	3.0-5.0	1.00 + 0.1 (AV-3.0)	1.5-2.9	2.0-2.9	1.00 + 0.1 (5.0-AV)	5.1-6.0	5.1-6.0	0.75	6.1-6.5	----	⁽²⁾	< 1.5 or > 6.5	< 2.0 or > 6.0																																						
AV																																																																
Pay Value	Test Result (%)																																																															
	ESAL Class 2	ESAL Class 3 or 4																																																														
1.00	3.0-5.0	3.0-5.0																																																														
1.00 + 0.1 (AV-3.0)	1.5-2.9	2.0-2.9																																																														
1.00 + 0.1 (5.0-AV)	5.1-6.0	5.1-6.0																																																														
0.75	6.1-6.5	----																																																														
⁽²⁾	< 1.5 or > 6.5	< 2.0 or > 6.0																																																														
SUBSECTION:	410.01 DESCRIPTION.																																																															
REVISION:	Delete the second sentence of the paragraph.																																																															

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

SUBSECTION:	410.03.01 Corrective Work.																																																								
REVISION:	Replace the last sentence of the paragraph with the following: Provide a final surface comparable to the adjacent pavement that does not require corrective work in respect to texture, appearance, and skid resistance.																																																								
SUBSECTION:	410.03.02 Ride Quality.																																																								
PART:	B) Requirements.																																																								
NUMBER:	1) Category A.																																																								
REVISION:	Replace the last sentence of the first paragraph with the following: At the Department’s discretion, a pay deduction of \$1200 per 0.1-lane-mile section may be applied in lieu of corrective work.																																																								
SUBSECTION:	410.03.02 Ride Quality.																																																								
PART:	B) Requirements.																																																								
NUMBER:	2) Category B.																																																								
REVISION:	Replace the second and third sentence of the first paragraph with the following: When the IRI is greater than 90 for a 0.1-mile section, perform corrective work, or remove and replace the pavement to achieve the specified IRI. At the Department’s discretion, a pay deduction of \$750 per 0.1-lane-mile section may be applied in lieu of corrective work.																																																								
SUBSECTION:	410.05 PAYMENT.																																																								
REVISION:	Delete the last sentence of the first paragraph.																																																								
SUBSECTION:	410.05 PAYMENT.																																																								
TABLE:	RIDE QUALITY ADJUSTMENT SCHEDULES																																																								
REVISION:	Replace the adjustment tables with the following: RIDE QUALITY ADJUSTMENT SCHEDULES <table><tr><th colspan="2">CATEGORY “A” PROJECTS</th><th colspan="2">CATEGORY “B” PROJECTS</th></tr><tr><th><u>IRI</u></th><th><u>Pay Value Adjustment</u></th><th><u>IRI</u></th><th><u>Pay Value Adjustment</u></th></tr><tr><td>70 or less</td><td>0</td><td>80 or less</td><td>0</td></tr><tr><td>71</td><td>-\$30</td><td>81</td><td>-\$20</td></tr><tr><td>72</td><td>-\$70</td><td>82</td><td>-\$45</td></tr><tr><td>73</td><td>-\$120</td><td>83</td><td>-\$80</td></tr><tr><td>74</td><td>-\$180</td><td>84</td><td>-\$120</td></tr><tr><td>75</td><td>-\$250</td><td>85</td><td>-\$170</td></tr><tr><td>76</td><td>-\$330</td><td>86</td><td>-\$220</td></tr><tr><td>77</td><td>-\$420</td><td>87</td><td>-\$280</td></tr><tr><td>78</td><td>-\$520</td><td>88</td><td>-\$350</td></tr><tr><td>79</td><td>-\$630</td><td>89</td><td>-\$420</td></tr><tr><td>80</td><td>-\$750</td><td>90</td><td>-\$500</td></tr><tr><td>81 or higher</td><td>corrective work⁽¹⁾</td><td>91 or higher</td><td>corrective work⁽²⁾</td></tr></table> ⁽¹⁾When it is in the best interest of the Department, a minimum pay value deduction of \$1200 per 0.1-lane-mile section may be applied in lieu of corrective work. ⁽²⁾When it is in the best interest of the Department, a minimum pay value deduction of \$750 per 0.1-lane-mile section may be applied in lieu of corrective work.	CATEGORY “A” PROJECTS		CATEGORY “B” PROJECTS		<u>IRI</u>	<u>Pay Value Adjustment</u>	<u>IRI</u>	<u>Pay Value Adjustment</u>	70 or less	0	80 or less	0	71	-\$30	81	-\$20	72	-\$70	82	-\$45	73	-\$120	83	-\$80	74	-\$180	84	-\$120	75	-\$250	85	-\$170	76	-\$330	86	-\$220	77	-\$420	87	-\$280	78	-\$520	88	-\$350	79	-\$630	89	-\$420	80	-\$750	90	-\$500	81 or higher	corrective work ⁽¹⁾	91 or higher	corrective work ⁽²⁾
CATEGORY “A” PROJECTS		CATEGORY “B” PROJECTS																																																							
<u>IRI</u>	<u>Pay Value Adjustment</u>	<u>IRI</u>	<u>Pay Value Adjustment</u>																																																						
70 or less	0	80 or less	0																																																						
71	-\$30	81	-\$20																																																						
72	-\$70	82	-\$45																																																						
73	-\$120	83	-\$80																																																						
74	-\$180	84	-\$120																																																						
75	-\$250	85	-\$170																																																						
76	-\$330	86	-\$220																																																						
77	-\$420	87	-\$280																																																						
78	-\$520	88	-\$350																																																						
79	-\$630	89	-\$420																																																						
80	-\$750	90	-\$500																																																						
81 or higher	corrective work ⁽¹⁾	91 or higher	corrective work ⁽²⁾																																																						
SUBSECTION:	509.01 DESCRIPTION.																																																								
REVISION:	Replace the second paragraph with the following: The Department may allow the use of similar units that conform to the National Cooperative Highway Research Program (NCHRP) 350 Test Level 3 (TL-3) requirements and the typical features depicted by the Standard Drawings. Obtain the Engineers approval prior to use. Ensure the barrier wall shape, length, material, drain slot dimensions and locations typical features are met and the reported maximum deflection is 3 feet or less from the NCHRP 350 TL-3 for Test 3 – 11 (pickup truck																																																								

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

	impacting at 60 mph at a 25-degree angle.)		
SUBSECTION:	606.02.11 Coarse Aggregate.		
REVISION:	Replace with the following:		
	Conform to Section 805, size No. 8 or 9-M.		
SUBSECTION:	701.03.08 Testing of Pipe.		
REVISION:	Replace and rename the subsection with the following:		
	701.03.08 Inspection of Pipe. The engineer will visually inspect all pipe. The Department will require camera/video inspection on a minimum of 50 percent of the linear feet of all installed pipe structures. Conduct camera/video inspection according to KM 64-114. The pipe to be installed under pavement will be selected first. If the total linear feet of pipe under pavement is less than 50 percent of the linear feet of all pipe installed, the Engineer will randomly select installations from the remaining pipe structures on the project to provide for the minimum inspection requirement. The pipe will be selected in complete runs (junction-junction or headwall-headwall) until the total linear feet of pipe to be inspected is at least 50 percent of the total linear feet of all installed pipe on the project. Unless the Engineer directs otherwise, schedule the inspections no sooner than 30 days after completing the installation and completion of earthwork to within 1 foot of the finished subgrade. When final surfacing conflicts with the 30-day minimum, conduct the inspections prior to placement of the final surface. The contractor must ensure that all pipe are free and clear of any debris so that a complete inspection is possible. Notify the Engineer immediately if distresses or locations of improper installation are discovered. When camera testing shows distresses or improper installation in the installed pipe, the Engineer may require additional sections to be tested. Provide the video and report to the Engineer when testing is complete in accordance with KM 64-114. Pipes that exhibit distress or signs of improper installation may necessitate repair or removal as the Engineer directs. These signs include, but are not limited to: deflection, cracking, joint separation, sagging or other interior damage. If corrugated metal or thermoplastic pipes exceed the deflection and installation thresholds indicated in the table below, provide the Department with an evaluation of each location conducted by a Professional Engineer addressing the severity of the deflection, structural integrity, environmental conditions, design service life, and an evaluation of the factor of safety using Section 12, “Buried Structures and Tunnel Liners,” of the AASHTO LRFD Bridge Design Specifications. Based on the evaluation, the Department may allow the pipe to remain in place at a reduced unit price as shown in the table below. Provide 5 business days for the Department to review the evaluation. When the pipe shows deflection of 10 percent or greater, remove and replace the pipe. When the camera/video or laser inspection results are called into question, the Department may require direct measurements or mandrel testing. The Cabinet may elect to conduct Quality Assurance verifications of any pipe inspections.		
SUBSECTION:	701.04.07 Testing.		
REVISION:	Replace and rename the subsection with the following:		
	701.04.07 Pipeline Video Inspection. The Department will measure the quantity in linear feet along the pipe invert of the structure inspected. When inspection above the specified 50 percent is performed due to a disagreement or suspicion of additional distresses and the Department is found in error, the Department will measure the quantity as Extra Work according to Subsection 104.03. However, if additional distresses or non-conformance is found, the Department will not measure the additional inspection for payment.		
SUBSECTION:	701.05 PAYMENT.		
REVISION:	Add the following pay item to the list of pay items:		
	<u>Code</u> 23131ER701	<u>Pay Item</u> Pipeline Video Inspection	<u>Pay Unit</u> Linear Foot

**Supplemental Specifications to The Standard Specifications
for Road and Bridge Construction, 2008 Edition**
(Effective with the October 31, 2008 Letting)

SUBSECTION: 805.15 GRADATION ACCEPTANCE OF NON-SPECIFICATION COARSE AGGREGATE.

REVISION: Replace the “SIZES OF COARSE AGGREGATES” table in with the following:

SIZES OF COARSE AGGREGATES																	
Aggregate Size	Sieve	AMOUNTS FINER THAN EACH LABORATORY SIEVE (SQUARE OPENINGS) PERCENTAGE BY WEIGHT															
	Nominal ⁽³⁾ Maximum Aggregate Size	4 inch	3 1/2 inch	3 inch	2 1/2 inch	2 inch	1 1/2 inch	1 inch	3/4 inch	1/2 inch	3/8 inch	No. 4	No. 8	No. 16	No. 30	No. 100	No. 200
1	3 1/2 inch	100	90-100		25-60		0-15		0-5								
2	2 1/2 inch			100	90-100	35-70	0-15		0-5								
23	2 inch			100		40-90		0-15		0-5							
3	2 inch				100	90-100	35-70	0-15		0-5							
357	2 inch				100	95-100		35-70		10-30		0-5					
4	1 1/2 inch					100	90-100	20-55	0-15		0-5						
467	1 1/2 inch					100	95-100		35-70		10-30	0-5					
5	1 inch						100	90-100	20-55	0-10	0-5						
57	1 inch						100	95-100		25-60		0-10	0-5				
610	1 inch						100	85-100		40-75		15-40					
67	3/4 inch							100	90-100		20-55	0-10	0-5				
68	3/4 inch							100	90-100		30-65	5-25	0-10	0-5			
710	3/4 inch							100	80-100		30-75	0-30					
78	1/2 inch								100	90-100	40-75	5-25	0-10	0-5			
8	3/8 inch									100	85-100	10-30	0-10	0-5			
9-M	3/8 inch									100	75-100	0-25	0-5				
10 ⁽²⁾	No. 4										100	85-100				10-30	
11 ⁽²⁾	No. 4										100	40-90	10-40			0-5	
DENSE GRADED AGGREGATE ⁽¹⁾	3/4 inch							100	70-100		50-80	30-65			10-40		4-13
CRUSHED STONE BASE ⁽¹⁾	1 1/2 inch				100		90-100		60-95		30-70	15-55			5-20		0-8

⁽¹⁾ Gradation performed by wet sieve KM 64-620 or AASHTO T 11/T 27.

⁽²⁾ Sizes shown for convenience and are not to be considered as coarse aggregates.

⁽³⁾ Nominal Maximum Size is the largest sieve on the gradation table for an aggregate size on which any material may be retained.

Note: The Department will allow blending of same source/same type aggregate when precise procedures are used such as cold feed, belt, or equivalent and combining of sizes or types of aggregate using the weigh hopper at concrete plants or controlled feed belts at the pugmill to obtain designated sizes.