

AFFIDAVIT
J91 – Airfield Striping

I _____ hereby certify that the applicant's company
(_____) has under current employment at least two
(2) employees with the following experience and training:

- At least two (2) airfield marking projects completed within the last three (3) years.
 - o In order to be included as an airfield marking project, said project must include, at a minimum, surface prep, layout and application of runway and taxiway markings.
- Trained and Certified Personnel
 - o Personnel must have attended the training provided by the Kentucky Transportation Cabinet and successfully completed all testing requirements and able to show proof of certification as a "*Pavement Marking Inspection Technician*".
 - o Personnel must be fully knowledgeable and experienced with the requirements and guidelines contained in the most current editions of FAA's AC 150/5340-1 "Standards for Airport Markings", and AC 150/5370-2 "Operational Safety On Airports During Construction"

The following personnel meet the above requirements and are currently employed by the applicant's company. If more than two employed, please include and attach to this document:

- 1) _____
- 2) _____

In addition, the applicant's company certifies that they maintain ownership or lease agreements for equipment capable of providing:

- An ultrahigh pressure self-propelled water blaster with full vacuum recovery capable of operating pressures from 0 to 35,000psi
- Truck mounted marking equipment capable of heating the paint to provide uniform flow, and a minimum paint capacity of 200 gallons. This unit must be capable of painting 12" to 18" in a single pass with uniform bead coverage from a pressurized vessel.
- Self propelled and/or walk behind paint equipment with mechanical bead dispenser that can paint lines up to 12".
- Striper equipment must contain an agitator that will keep the paint thoroughly mixed and maintain proper application pressure for paint and beads at all times, and be equipped with a guide boom and/or optical pointer to attain consistent smooth and straight lines. The paint cutoff device must provide clean square lines.

I SWEAR OR AFFIRM THAT THE ABOVE AND FOREGOING REPRESENTATIONS ARE TRUE AND CORRECT TO THE BEST OF MY INFORMATION, KNOWLEDGE, AND BELIEF.

SIGNED (*Company Officer*)

DATE

PRINTED NAME

TITLE