

CALL NO. 308

CONTRACT ID. 192425

HARLAN COUNTY

FED/STATE PROJECT NUMBER FD05 048 0421 024-027

DESCRIPTION BLEDSOE ROAD (US 421)

WORK TYPE ASPHALT RESURFACING

PRIMARY COMPLETION DATE 6/30/2020

LETTING DATE: November 22,2019

Sealed Bids will be received electronically through the Bid Express bidding service until 10:00 AM EASTERN STANDARD TIME November 22,2019. Bids will be publicly announced at 10:00 AM EASTERN STANDARD TIME.

NO PLANS ASSOCIATED WITH THIS PROJECT.

REQUIRED BID PROPOSAL GUARANTY: Not less than 5% of the total bid.

TABLE OF CONTENTS

PART I SCOPE OF WORK

- PROJECT(S), COMPLETION DATE(S), & LIQUIDATED DAMAGES
- CONTRACT NOTES
- STATE CONTRACT NOTES
- SURFACING AREAS
- ASPHALT MIXTURE
- INCIDENTAL SURFACING
- FUEL AND ASPHALT PAY ADJUSTMENT
- COMPACTION OPTION B
- ASPHALT MIX PAVEMENT WEDGE MONOLITHIC OPERATION
- EDGE KEY (BY TON)
- ASPHALT MILLING AND TEXTURING
- BASE FAILURE REPAIR
- TYPICAL SECTION DIMENSIONS
- TRAFFIC CONTROL PLAN 2 LANE
- DURABLE PAVEMENT EDGE DETAILS
- SKETCH MAP(S)
- SUMMARY SHEET(S)
- TYPICAL SECTION(S)

PART II SPECIFICATIONS AND STANDARD DRAWINGS

- SPECIFICATIONS REFERENCE
- SUPPLEMENTAL SPECIFICATION
- 2016 STANDARD DRAWINGS THAT APPLY
- EDGE LINE RUMBLE STRIP DETAILS TWO LANE ROADWAYS

PART III EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

- LABOR AND WAGE REQUIREMENTS
- EXECUTIVE BRANCH CODE OF ETHICS
- KENTUCKY EQUAL EMPLOYMENT OPPORTUNITY ACT OF 1978 LOCALITY / STATE
- PROJECT WAGE RATES / STATE FUNDED

PART IV INSURANCE

PART V BID ITEMS

PART I SCOPE OF WORK

ADMINISTRATIVE DISTRICT - 11

CONTRACT ID - 192425 FD05 048 0421 024-027

COUNTY - HARLAN

PCN - MP04804211903 FD05 048 0421 024-027

BLEDSOE ROAD (US 421) (MP 24.150) BEGINNING AT A POINT 0.053 MILES SOUTH OF KY 221 EXTENDING NORTH TO THE HARLAN-LESLIE COUNTY LINE (MP 26.888), A DISTANCE OF 02.73 MILES.ASPHALT RESURFACING

GEOGRAPHIC COORDINATES LATITUDE 36:55:32.00 LONGITUDE 83:21:19.00

COMPLETION DATE(S):

COMPLETED BY 06/30/2020 APPLIES TO ENTIRE CONTRACT

CONTRACT NOTES

PROPOSAL ADDENDA

All addenda to this proposal must be applied when calculating bid and certified in the bid packet submitted to the Kentucky Department of Highways. Failure to use the correct and most recent addenda may result in the bid being rejected.

BID SUBMITTAL

Bidder must use the Department's electronic bidding software. The Bidder must download the bid file located on the Bid Express website (www.bidx.com) to prepare a bid packet for submission to the Department. The bidder must submit electronically using Bid Express.

JOINT VENTURE BIDDING

Joint venture bidding is permissible. All companies in the joint venture must be prequalified in one of the work types in the Qualifications for Bidders for the project. The bidders must get a vendor ID for the joint venture from the Division of Construction Procurement and register the joint venture as a bidder on the project. Also, the joint venture must obtain a digital ID from Bid Express to submit a bid. A joint bid bond of 5% may be submitted for both companies or each company may submit a separate bond of 5%.

UNDERGROUND FACILITY DAMAGE PROTECTION

The contractor shall make every effort to protect underground facilities from damage as prescribed in the Underground Facility Damage Protection Act of 1994, Kentucky Revised Statute KRS 367.4901 to 367.4917. It is the contractor's responsibility to determine and take steps necessary to be in compliance with federal and state damage prevention directives. When prescribed in said directives, the contractor shall submit Excavation Locate Requests to the Kentucky Contact Center (KY811) via web ticket entry. The submission of this request does not relieve the contractor from the responsibility of contacting non-member facility owners, whom shall be contacted through their individual Protection Notification Center. Non-compliance with these directives can result in the enforcement of penalties.

REGISTRATION WITH THE SECRETARY OF STATE BY A FOREIGN ENTITY

Pursuant to KRS 176.085(1)(b), an agency, department, office, or political subdivision of the Commonwealth of Kentucky shall not award a state contract to a person that is a foreign entity required by KRS 14A.9-010 to obtain a certificate of authority to transact business in the Commonwealth ("certificate") from the Secretary of State under KRS 14A.9-030 unless the person produces the certificate within fourteen (14) days of the bid or proposal opening. If the foreign entity is not required to obtain a certificate as provided in KRS 14A.9-010, the foreign entity should identify the applicable exception. Foreign entity is defined within KRS 14A.1-070.

For all foreign entities required to obtain a certificate of authority to transact business in the Commonwealth, if a copy of the certificate is not received by the contracting agency within the time frame identified above, the foreign entity's solicitation response shall be deemed non-responsive or the awarded contract shall be cancelled.

Businesses can register with the Secretary of State at https://secure.kentucky.gov/sos/ftbr/welcome.aspx .

SPECIAL NOTE FOR PROJECT QUESTIONS DURING ADVERTISEMENT

Questions about projects during the advertisement should be submitted in writing to the Division of Construction Procurement. This may be done by fax (502) 564-7299 or email to kytc.projectquestions@ky.gov. The Department will attempt to answer all submitted questions. The Department reserves the right not to answer if the question is not pertinent or does not aid in clarifying the project intent.

The deadline for posting answers will be 3:00 pm Eastern Daylight Time, the day preceding the Letting. Questions may be submitted until this deadline with the understanding that the later a question is submitted, the less likely an answer will be able to be provided.

The questions and answers will be posted for each Letting under the heading "Questions & Answers" on the Construction Procurement website (www.transportation.ky.gov/contract). The answers provided shall be considered part of this Special Note and, in case of a discrepancy, will govern over all other bidding documents.

HARDWOOD REMOVAL RESTRICTIONS

The US Department of Agriculture has imposed a quarantine in Kentucky and several surrounding states, to prevent the spread of an invasive insect, the emerald ash borer. Hardwood cut in conjunction with the project may not be removed from the state. Chipping or burning on site is the preferred method of disposal.

INSTRUCTIONS FOR EXCESS MATERIAL SITES AND BORROW SITES

Identification of excess material sites and borrow sites shall be the responsibility of the Contractor. The Contractor shall be responsible for compliance with all applicable state and federal laws and may wish to consult with the US Fish and Wildlife Service to seek protection under Section 10 of the Endangered Species Act for these activities.

ACCESS TO RECORDS

The contractor, as defined in KRS 45A.030 (9) agrees that the contracting agency, the Finance and Administration Cabinet, the Auditor of Public Accounts, and the Legislative Research Commission, or their duly authorized representatives, shall have access to any books, documents, papers, records, or other evidence, which are directly pertinent to this contract for the purpose of financial audit or program review. Records and other prequalification information confidentially

disclosed as part of the bid process shall not be deemed as directly pertinent to the contract and shall be exempt from disclosure as provided in KRS 61.878(1)(c). The contractor also recognizes that any books, documents, papers, records, or other evidence, received during a financial audit or program review shall be subject to the Kentucky Open Records Act, KRS 61.870 to 61.884.

In the event of a dispute between the contractor and the contracting agency, Attorney General, or the Auditor of Public Accounts over documents that are eligible for production and review, the Finance and Administration Cabinet shall review the dispute and issue a determination, in accordance with Secretary's Order 11-004.

April 30, 2018

SPECIAL NOTE FOR RECIPROCAL PREFERENCE

RECIPROCAL PREFERENCE TO BE GIVEN BY PUBLIC AGENCIES TO RESIDENT BIDDERS

By reference, KRS 45A.490 to 45A.494 are incorporated herein and in compliance regarding the bidders residency. Bidders who want to claim resident bidder status should complete the Affidavit for Claiming Resident Bidder Status along with their bid in the electronic bidding software. Submittal of the Affidavit should be done along the bid in Bid Express.

April 30, 2018

HARLAN COUNTY FD05 048 0421 024-027

Contract ID: 192425 Page 9 of 35

SURFACING AREAS

The Department estimates the mainline surfacing width to be 22 feet.

The Department estimates the total mainline area to be surfaced to be 40,639 square yards.

The Department estimates the shoulder width to be 1 foot on each side.

The Department estimates the total shoulder area to be surfaced to be 3,213 square yards.

ASPHALT MIXTURE

Unless otherwise noted, the Department estimates the rate of application for all asphalt mixtures to be 110 lbs/sy per inch of depth.

INCIDENTAL SURFACING

The Department has included in the quantities of asphalt mixtures established in the proposal estimated quantities required for resurfacing or surfacing mailbox turnouts, farm field entrances, residential and commercial entrances, curve widening, ramp gores and tapers, and road and street approaches, as applicable. Pave these areas to the limits as shown on Standard Drawing RPM-110-06 or as directed by the Engineer. In the event signal detectors are present in the intersecting streets or roads, pave the crossroads to the right of way limit or back of the signal detector, whichever is the farthest back of the mainline. Surface or resurface these areas as directed by the Engineer. The Department will not measure placing and compacting for separate payment but shall be incidental to the Contract unit price for the asphalt mixtures.

FUEL AND ASPHALT PAY ADJUSTMENT

The Department has included the Contract items Asphalt Adjustment and Fuel Adjustment for possible future payments at an established Contract unit price of \$1.00. The Department will calculate actual adjustment quantities after work is completed. If existing Contract amount is insufficient to pay all items on the contract with the adjustments, the Department will establish additional monies with a change order.

OPTION B

Be advised that the Department will control and accept compaction of asphalt mixtures furnished on this project under OPTION B in accordance with Sections 402 and 403.


SPECIAL NOTE FOR PAVEMENT WEDGE AND SHOULDER MONOLITHIC OPERATION

- **1.0 MATERIALS.** Provide an Asphalt Surface Mixture conforming to Section 403 of the Standard Specifications, as applicable to the project, for the pavement wedge.
- **2.0 CONSTRUCTION.** Place the specified Asphalt Surface Mixture on shoulders monolithically with the driving lane. Prime the existing shoulder with tack material as the Engineer directs before placing the wedge. Construct according to Section 403.03 of the Standard Specifications.

Equip the paver with a modified screed that extends the full width of the wedge being placed and is tapered to produce a wedge. Obtain the Engineer's approval of the modified screed before placing shoulder wedge monolithically with the driving lane.

The wedge may vary in thickness at the edge of the milled area in the shoulder. If the area to receive the shoulder wedge is milled prior to placement, during rolling operations pinch the outside edge of the new inlay wedge to match the existing shoulder elevation not being resurfaced. Unless required otherwise by the Contract, construct rolled or sawed rumble strips according to Section 403.03.08, as applicable.

The following sketch is primarily for the computation of quantities; however, the wedge will result in a similar cross-section where sufficient width exists. Do not construct a shoulder for placing the wedge unless specified elsewhere in the Contract.




- **3.0 MEASUREMENT.** The Department will measure Asphalt Surface Mixture placed as the pavement wedge according to Section 403.
- **4.0 PAYMENT.** The Department will make payment for the completed and accepted quantities of Asphalt Surface Mixtures on payement wedges according to Section 403.

SPECIAL NOTE FOR EDGE KEY

Construct Edge Keys at the beginning of project, end of project, at railroad crossings, and at ramps, as applicable. Unless specified in the Contract or directed by the Engineer, do not construct edge keys at intersecting streets, roads, alleys, or entrances. Cut out the existing asphalt surface to the required depth and width shown on the drawing and heel the new surface into the existing surface. The Department will make payment for this work at the Contract unit price per ton for Asphalt Pavement Milling and Texturing, which shall be full compensation for all labor, materials, equipment, and incidentals for removal and disposal of the existing asphalt surface required to construct the edge key.

EDGE KEY



Thickness = $\underline{1}$ Inch

L = 100 LF

L= Length of Edge Key

1-3309 Edge key by Ton 01/02//2012

SPECIAL NOTE FOR ASPHALT MILLING AND TEXTURING

Begin paving operations within <u>48 hours</u> of commencement of the milling operation. Continue paving operations continuously until completed. If paving operations are not begun within this time period, the Department will assess liquidated damages at the rate prescribed by Section 108.09 until such time as paving operations are begun.

Contrary to Section 408, the Department will retain possession of the material obtained from the milling operations. Deliver this material to the State Maintenance facility in Harlan County.

SPECIAL NOTE FOR BASE FAILURE REPAIR

Repair locations listed on the summary are approximate only. The Engineer will determine actual repair locations and dimensions at the time of construction. Prior to overall milling and/or leveling and wedging, excavate the designated base failure areas by milling to a depth 4 inches below the existing asphalt pavement surface level. Dispose of the excavated materials at waste sites off the Right-of-Way obtained by the Contractor at no additional cost to the Department. See Special Note for Waste and Borrow.

Backfill the excavated areas with Class 2 Asphalt Base 1.00D PG64-22. Compact the asphalt base to the compaction required in Section 403.03.10. Seal the asphalt base with leveling and wedging. Perform all base failure repairs in such a manner that removal and replacement are completed on the same day. Do this work as one of the Contractor's first operations in order to allow further compaction by traffic. Do not mill or place new asphalt surface over repaired base failure areas until a minimum of 7 calendar days have elapsed after placement of the asphalt base. After a minimum of 7 calendar days and when the Engineer determines the base failure repair areas have sufficiently stabilized, begin milling and/or resurfacing operations. Prior to milling and/or constructing the new asphalt surface, level and wedge any settlement of the repair areas.

The bidder must draw conclusions as to the conditions encountered. The Department does not give any guarantee as to the accuracy of the data and will not consider any claim for additional compensation if the materials encountered that are not in accord with the classification shown.

Accept payment at the Contract unit prices per ton for Asphalt Milling and Texturing, Asphalt Base, and Leveling and Wedging as full compensation for all labor, materials, equipment, and incidentals for removing pavement and disposing of the materials, furnishing and placing asphalt base, leveling and wedging, and all other items necessary to complete the work according to these notes to the satisfaction of the Engineer.

1-3605 basefailurerepairmillinlaypayton 01/02/2012

HARLAN COUNTY FD05 048 0421 024-027 Contract ID: 192425 Page 14 of 35

SPECIAL NOTE FOR TYPICAL SECTION DIMENSIONS

Consider the dimensions shown on the typical sections for pavement and shoulder widths and thickness' to be nominal or typical dimensions. The Engineer may direct or approve varying the actual dimensions to be constructed to fit existing conditions. Do not widen existing pavement or shoulders unless specified elsewhere in this proposal or directed by the engineer.

1-3725 Typical Section Dimensions 01/02/2012

TRAFFIC CONTROL PLAN

TRAFFIC CONTROL GENERAL

Except as provided herein, maintain and control traffic in accordance with the Standard and Supplemental Specifications and the Standard and Sepia Drawings, current editions. Except for the roadway and traffic control bid items listed, all items of work necessary to maintain and control traffic will be paid at the lump sum bid price to "Maintain and Control Traffic".

Contrary to Section 106.01, furnish new, or used in like new condition, traffic control devices at the beginning of the work and maintain in like new condition until completion of the work.

PROJECT PHASING & CONSTRUCTION PROCEDURES

The Engineer may specify days and hours when lane closures will not be allowed.

Maintain alternating one way traffic during construction. Provide a minimum clear lane width of 10 feet; however, provide for passage of vehicles of up to 16 feet in width. If traffic should be stopped due to construction operations, and a school bus on an official run arrives on the scene, make provisions for the passage of the bus as quickly as possible.

LANE CLOSURES

Do not leave lane closures in place during non-working hours.

SIGNS

Sign posts and splices shall be compliant with NCHRP 350 or MASH. Manufacturer's documentation validating this compliance shall be provided to the Engineer prior to installation. Signs, including any splices, shall be installed according to manufacturer's specifications and installation recommendations. Contrary to section 112.04.02, only long-term signs (signs intended to be continuously in place for more than 3 days) will be measured for payment. Short-term signs (signs intended to be left in place for 3 days or less) will not be measured for payment but will be incidental to Maintain and Control Traffic.

CHANGEABLE MESSAGE SIGNS

If deemed necessary by the Engineer, the Department will furnish, operate, and maintain Changeable Message Signs.

Traffic Control Plan Page 2 of 3

TEMPORARY ENTRANCES

The Engineer will not require the Contractor to provide continuous access to farms, single family, duplex, or triplex residential properties during working hours; however, provide reasonable egress and ingress to each such property when actual operations are not in progress at that location. Limit the time during which a farm or residential entrance is blocked to the minimum length of time required for actual operations, not extended for the Contractor's convenience, and in no case exceeding six (6) hours. Notify all residents twenty-four hours in advance of any driveway or entrance closings and make any accommodations necessary to meet the access needs of disabled residents.

Except as allowed by the Phasing as specified above, maintain direct access to all side streets and roads, schools, churches, commercial properties and apartments or apartment complexes of four or more units at all times.

The Department will measure asphalt materials required to construct and maintain any temporary entrances which may be necessary to provide temporary access; however, the Department will not measure aggregates, excavation, and/or embankment, but shall be incidental to Maintain and Control Traffic. The Engineer will determine the type of surfacing material, asphalt or aggregate, to be used at each entrance.

BARRICADES

The Department will not measure barricades used in lieu of barrels and cones for channelization or delineation, but shall be incidental to Maintain and Control Traffic according to Section 112.04.01.

The Department will measure barricades used to protect pavement removal areas in individual units Each. The Department will measure for payment the maximum number of barricades in concurrent use at the same time on a single day on all sections of the contract. The Department will measure individual barricades only once for payment, regardless of how many times they are set, reset, removed, and relocated during the duration of the project. The Department will not measure replacements for damaged barricades the Engineer directs to be replaced due to poor condition or reflectivity. Retain possession of the Barricades upon completion of construction.

PAVEMENT MARKINGS

If there is to be a deviation from the existing striping plan, the Engineer will furnish the Contractor a striping plan prior to placement of the final surface course.

Install Temporary Striping according to Section 112 with the following exception:

Traffic Control Plan Page 3 of 3

If the Contractor's operations or phasing requires temporary markings that must subsequently be removed from the final surface course, use an approved removable lane tape; however, the Department will not measure removable lane tape for separate payment, but will measure and pay for removable lane tape as temporary striping.

PAVEMENT EDGE DROP-OFFS

Do not allow a pavement edge between opposing directions of traffic or lanes that traffic is expected to cross in a lane change situation with an elevation difference greater than 1½". Place Warning signs (MUTCD W8-11 or W8-9A) in advance of and at 1500' intervals throughout the drop-off area. Dual post the signs on both sides of the traveled way. Wedge all transverse transitions between resurfaced and unresurfaced areas which traffic may cross with asphalt mixture for leveling and wedging. Remove the wedges prior to placement of the final surface course.

Protect pavement edges that traffic is not expected to cross, except accidentally, as follows:


Less than 2" - No protection required.


2" to 4" - Place plastic drums, vertical panels, or barricades every 50 feet. During daylight working hours only, the Engineer will allow the Contractor to use cones in lieu of plastic drums, panels, and barricades. Wedge the drop-off with DGA or asphalt mixture for leveling and wedging with a 1:1 or flatter slope in daylight hours, or 3:1 or flatter slope during nighttime hours, when work is not active in the drop-off area.

Greater than 4" - Protect drop-offs greater than 4 inches within 10 feet of traffic by placing drums, vertical panels, or barricades every 25 feet. The Engineer will not allow the use of cones in lieu of drums, vertical panels, or barricades for drop-offs greater than 4". Place Type III Barricades directly in front of the drop-off facing on coming traffic in both directions of travel. Provide warning signs as shown on the Standard Drawings or as directed by the Engineer

Pedestrians & Bicycles - Protect pedestrian and bicycle traffic as directed by the engineer.

1-3820 Traffic Control Plan 2 Lane 07/27/2017






Milling Summary FD05 048 0421 024-027

				Total	780
Milepoint	Comment	Length	Width	Avg Depth	Tons
24.150	Edge Key	100	24	0.5	7.33333333
26.888	Edge Key	100	24	0.5	7.33333333
VARIOUS	BASE FAILURES				765
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0
					0

Base Failure Repair Summary FD05 048 0421 024-027

Both 24.269 24.275 31.68 16 56.32 12.3904 12.31 NB 24.318 24.331 68.64 8 61.0133333 13.42293 13.42293 NB 24.367 24.391 126.72 8 112.64 24.7808 24.881 110.88 8 98.56 21.6832 21.6838 24.881 25.236 25.272 190.08 8 168.96 37.1712 37.1808 25.344 25.362 95.04 8 84.48 18.5856 18.588 25.236 25.272 190.08 8 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 25.868 25.955 26.012 300.96 8 267.52 58.8544 58.888 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 38.20373 38.80373					Total	2515	765	765
Both 24.269 24.275 31.68 16 56.32 12.3904 12.3 NB 24.318 24.331 68.64 8 61.0133333 13.42293 13.42293 NB 24.367 24.391 126.72 8 112.64 24.7808 24.7 SB 24.54 24.579 205.92 8 183.04 40.2688 40.2 SB 24.635 24.698 332.64 8 295.68 65.0496 65.0 SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5	D:	Danin MD	End MD	Longth	\A/; d4b	COVD	Milling	CL2 Asph Base 1.0D
NB 24.318 24.331 68.64 8 61.0133333 13.42293 13.42293 NB 24.367 24.391 126.72 8 112.64 24.7808 24.7 SB 24.54 24.579 205.92 8 183.04 40.2688 40.2 SB 24.635 24.698 332.64 8 295.68 65.0496 65.0 SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 <tr< th=""><th>Direction</th><th>Begin MP</th><th>End MP</th><th>Length</th><th>wiath</th><th>อนุาบ</th><th>(tons)</th><th>PG 64-22 (tons)</th></tr<>	Direction	Begin MP	End MP	Length	wiath	อนุาบ	(tons)	PG 64-22 (tons)
NB 24.367 24.391 126.72 8 112.64 24.7808 24.7 SB 24.54 24.579 205.92 8 183.04 40.2688 40.2 SB 24.635 24.698 332.64 8 295.68 65.0496 65.0 SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 <t< td=""><td>Both</td><td>24.269</td><td>24.275</td><td>31.68</td><td>16</td><td>56.32</td><td>12.3904</td><td>12.3904</td></t<>	Both	24.269	24.275	31.68	16	56.32	12.3904	12.3904
SB 24.54 24.579 205.92 8 183.04 40.2688 40.2 SB 24.635 24.698 332.64 8 295.68 65.0496 65.0 SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 <t< td=""><td>NB</td><td>24.318</td><td>24.331</td><td>68.64</td><td>8</td><td>61.0133333</td><td>13.42293</td><td>13.42293333</td></t<>	NB	24.318	24.331	68.64	8	61.0133333	13.42293	13.42293333
SB 24.635 24.698 332.64 8 295.68 65.0496 65.0 SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.15 195.36 8 173.653333 38.20373 38.20373	NB	24.367	24.391	126.72	8	112.64	24.7808	24.7808
SB 24.736 24.755 100.32 8 89.1733333 19.61813 19.61813 SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.344 25.362 95.04 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373	SB	24.54	24.579	205.92	8	183.04	40.2688	40.2688
SB 24.79 24.804 73.92 8 65.7066667 14.45547 14.45546 SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 32.00853 32.00853	SB	24.635	24.698	332.64	8	295.68	65.0496	65.0496
SB 24.86 24.881 110.88 8 98.56 21.6832 21.6 SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853	SB	24.736	24.755	100.32	8	89.1733333	19.61813	19.61813333
SB 25.236 25.272 190.08 8 168.96 37.1712 37.1 NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186 <td>SB</td> <td>24.79</td> <td>24.804</td> <td>73.92</td> <td>8</td> <td>65.7066667</td> <td>14.45547</td> <td>14.45546667</td>	SB	24.79	24.804	73.92	8	65.7066667	14.45547	14.45546667
NB 25.344 25.362 95.04 8 84.48 18.5856 18.5 NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	SB	24.86	24.881	110.88	8	98.56	21.6832	21.6832
NB 25.514 25.531 89.76 8 79.7866667 17.55307 17.55306 SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	SB	25.236	25.272	190.08	8	168.96	37.1712	37.1712
SB 25.866 25.918 274.56 8 244.053333 53.69173 53.69173 SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186		25.344	25.362	95.04	8		18.5856	18.5856
SB 25.955 26.012 300.96 8 267.52 58.8544 58.8 SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	NB	25.514	25.531	89.76	8	79.7866667	17.55307	17.55306667
SB 26.113 26.15 195.36 8 173.653333 38.20373 38.20373 SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	SB	25.866	25.918	274.56	8	244.053333	53.69173	53.69173333
SB 26.175 26.218 227.04 8 201.813333 44.39893 44.39893 SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186								
SB 26.36 26.4 211.2 8 187.733333 41.30133 41.30133 SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	SB	26.113	26.15	195.36	8	173.653333	38.20373	38.20373333
SB 26.456 26.487 163.68 8 145.493333 32.00853 32.00853 SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186		26.175	26.218	227.04	8		44.39893	44.39893333
SB 26.55 26.606 295.68 8 262.826667 57.82187 57.82186	SB	26.36	26.4		8		41.30133	41.30133333
			26.487					
SB 26.74 26.888 781.44 8 694.613333 152.8149 152.8149		26.55	26.606	295.68	8	262.826667	57.82187	57.82186667
	SB	26.74	26.888	781.44	8	694.613333	152.8149	152.8149333

FD05 048 0421 024-027 TYPICAL SECTION MILEPOINTS 24.150 to 26.888



*Where Existing Site Conditions Permit

PART II

SPECIFICATIONS AND STANDARD DRAWINGS

SPECIFICATIONS REFERENCE

Any reference in the plans or proposal to previous editions of the Standard Specifications for Road and Bridge Construction and Standard Drawings are superseded by Standard Specifications for Road and Bridge Construction, Edition of 2019 and Standard Drawings, Edition of 2016.


SUPPLEMENTAL SPECIFICATIONS

The contractor shall use the Supplemental Specifications that are effective at the time of letting. The Supplemental Specifications can be found at the following link:

http://transportation.ky.gov/Construction/Pages/Kentucky-Standard-Specifications.aspx

2016 KENTUCKY STANDARD DRAWINGS

CURVE WIDENING AND SUPERELEVATION TRANSITIONS	RGS-001-07
SUPERELEVATION FOR MULTILANE PAVEMENT	RGS-002-06
MISCELLANEOUS STANDARDS	RGX-001-06
APPROACHES, ENTRANCES, AND MAIL BOX TURNOUT	RPM-110-07
SHOULDER AND EDGE LINE RUMBLE STRIP DETAILS	TPM-165
LANE CLOSURE TWO-LANE HIGHWAY	TTC-100-04
SHOULDER CLOSURE	TTC-135-02
PAVEMENT CONDITION WARNING SIGNS	TTD-125-02
MOBILE OPERATION FOR PAINT STRIPING CASE I	TTS-100-02
MOBILE OPERATION FOR PAINT STRIPING CASE II	TTS-105-02



PART III

EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

Contract ID: 192425 Page 29 of 35

TRANSPORTATION CABINET DEPARTMENT OF HIGHWAYS

LABOR AND WAGE REQUIREMENTS APPLICABLE TO OTHER THAN FEDERAL-AID SYSTEM PROJECTS

- I. Application
- II. Nondiscrimination of Employees (KRS 344)

I. APPLICATION

- 1. These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to all work performed on the contract by piecework, station work or by subcontract. The contractor's organization shall be construed to include only workmen employed and paid directly by the contractor and equipment owned or rented by him, with or without operators.
- 2. The contractor shall insert in each of his subcontracts all of the stipulations contained in these Required Provisions and such other stipulations as may be required.
- 3. A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

II. NONDISCRIMINATION OF EMPLOYEES

AN ACT OF THE KENTUCKY GENERAL ASSEMBLY TO PREVENT DISCRIMINATION IN EMPLOYMENT KRS CHAPTER 344 EFFECTIVE JUNE 16, 1972

The contract on this project, in accordance with KRS Chapter 344, provides that during the performance of this contract, the contractor agrees as follows:

- 1. The contractor shall not fail or refuse to hire, or shall not discharge any individual, or otherwise discriminate against an individual with respect to his compensation, terms, conditions, or privileges of employment, because of such individual's race, color, religion, national origin, sex, disability or age (forty and above); or limit, segregate, or classify his employees in any way which would deprive or tend to deprive an individual of employment opportunities or otherwise adversely affect his status as an employee, because of such individual's race, color, religion, national origin, sex, disability or age forty (40) and over. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.
- 2. The contractor shall not print or publish or cause to be printed or published a notice or advertisement relating to employment by such an employer or membership in or any classification or referral for employment by the employment agency, indicating any preference, limitation, specification, or discrimination, based on race, color, religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, except that such a notice or advertisement may indicate a preference, limitation, or specification based on religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, when religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, is a bona fide occupational qualification for employment.

- 3. If the contractor is in control of apprenticeship or other training or retraining, including on-the-job training programs, he shall not discriminate against an individual because of his race, color, religion, national origin, sex, disability or age forty (40) and over, in admission to, or employment in any program established to provide apprenticeship or other training.
- 4. The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representative of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment. The contractor will take such action with respect to any subcontract or purchase order as the administrating agency may direct as a means of enforcing such provisions, including sanctions for non-compliance.

Revised: January 25, 2017

EXECUTIVE BRANCH CODE OF ETHICS

In the 1992 regular legislative session, the General Assembly passed and Governor Brereton Jones signed Senate Bill 63 (codified as KRS 11A), the Executive Branch Code of Ethics, which states, in part:

KRS 11A.040 (7) provides:

No present or former public servant shall, within six (6) months following termination of his office or employment, accept employment, compensation, or other economic benefit from any person or business that contracts or does business with, or is regulated by, the state in matters in which he was directly involved during the last thirty-six (36) months of his tenure. This provision shall not prohibit an individual from returning to the same business, firm, occupation, or profession in which he was involved prior to taking office or beginning his term of employment, or for which he received, prior to his state employment, a professional degree or license, provided that, for a period of six (6) months, he personally refrains from working on any matter in which he was directly involved during the last thirty-six (36) months of his tenure in state government. This subsection shall not prohibit the performance of ministerial functions, including but not limited to filing tax returns, filing applications for permits or licenses, or filing incorporation papers, nor shall it prohibit the former officer or public servant from receiving public funds disbursed through entitlement programs.

KRS 11A.040 (9) states:

A former public servant shall not represent a person or business before a state agency in a matter in which the former public servant was directly involved during the last thirty-six (36) months of his tenure, for a period of one (1) year after the latter of:

- a) The date of leaving office or termination of employment; or
- b) The date the term of office expires to which the public servant was elected.

This law is intended to promote public confidence in the integrity of state government and to declare as public policy the idea that state employees should view their work as a public trust and not as a way to obtain private benefits.

If you have worked for the executive branch of state government within the past six months, you may be subject to the law's prohibitions. The law's applicability may be different if you hold elected office or are contemplating representation of another before a state agency.

Also, if you are affiliated with a firm which does business with the state and which employs former state executive-branch employees, you should be aware that the law may apply to them.

In case of doubt, the law permits you to request an advisory opinion from the Executive Branch Ethics Commission, 3 Fountain Place, Frankfort, Kentucky 40601; telephone (502) 564-7954.

Revised: January 27, 2017

Kentucky Equal Employment Opportunity Act of 1978

The requirements of the Kentucky Equal Employment Opportunity Act of 1978 (KRS 45.560-45.640) shall apply to this Contract. The apparent low Bidder will be required to submit EEO forms to the Division of Construction Procurement, which will then forward to the Finance and Administration Cabinet for review and approval. No award will become effective until all forms are submitted and EEO/CC has certified compliance. The required EEO forms are as follows:

- EEO-1: Employer Information Report
- Affidavit of Intent to Comply
- Employee Data Sheet
- Subcontractor Report

These forms are available on the Finance and Administration's web page under *Vendor Information*, *Standard Attachments and General Terms* at the following address: https://www.eProcurement.ky.gov.

Bidders currently certified as being in compliance by the Finance and Administration Cabinet may submit a copy of their approval letter in lieu of the referenced EEO forms.

For questions or assistance please contact the Finance and Administration Cabinet by email at **finance.contractcompliance@ky.gov** or by phone at 502-564-2874.

EMPLOYEE RIGHTS
UNDER THE FAIR LABOR STANDARDS ACT

THE UNITED STATES DEPARTMENT OF LABOR WAGE AND HOUR DIVISION

FEDERAL MINIMUM WAGE

\$7.25

PEN HUUN

BEGINNING JULY 24, 2009

OVERTIME PAY

At least $1\frac{1}{2}$ times your regular rate of pay for all hours worked over 40 in a workweek.

CHILD LABOR

An employee must be at least **16** years old to work in most non-farm jobs and at least **18** to work in non-farm jobs declared hazardous by the Secretary of Labor.

Youths **14** and **15** years old may work outside school hours in various non-manufacturing, non-mining, non-hazardous jobs under the following conditions:

No more than

- 3 hours on a school day or 18 hours in a school week;
- 8 hours on a non-school day or 40 hours in a non-school week.

Also, work may not begin before **7 a.m.** or end after **7 p.m.**, except from June 1 through Labor Day, when evening hours are extended to **9 p.m.** Different rules apply in agricultural employment.

TIP CREDIT

Employers of "tipped employees" must pay a cash wage of at least \$2.13 per hour if they claim a tip credit against their minimum wage obligation. If an employee's tips combined with the employer's cash wage of at least \$2.13 per hour do not equal the minimum hourly wage, the employer must make up the difference. Certain other conditions must also be met.

ENFORCEMENT

The Department of Labor may recover back wages either administratively or through court action, for the employees that have been underpaid in violation of the law. Violations may result in civil or criminal action.

Employers may be assessed civil money penalties of up to \$1,100 for each willful or repeated violation of the minimum wage or overtime pay provisions of the law and up to \$11,000 for each employee who is the subject of a violation of the Act's child labor provisions. In addition, a civil money penalty of up to \$50,000 may be assessed for each child labor violation that causes the death or serious injury of any minor employee, and such assessments may be doubled, up to \$100,000, when the violations are determined to be willful or repeated. The law also prohibits discriminating against or discharging workers who file a complaint or participate in any proceeding under the Act.

ADDITIONAL INFORMATION

- Certain occupations and establishments are exempt from the minimum wage and/or overtime pay provisions.
- Special provisions apply to workers in American Samoa and the Commonwealth of the Northern Mariana Islands.
- \bullet Some state laws provide greater employee protections; employers must comply with both.
- \bullet The law requires employers to display this poster where employees can readily see it.
- Employees under 20 years of age may be paid \$4.25 per hour during their first 90 consecutive calendar days of employment with an employer.
- Certain full-time students, student learners, apprentices, and workers with disabilities may be paid less than the minimum wage under special certificates issued by the Department of Labor.



Contract ID: 192425

Page 32 of 35

PART IV

INSURANCE

Refer to *Kentucky Standard Specifications for Road and Bridge Construction*,

current edition

PART V

BID ITEMS

Contract ID: 192425 Page 35 of 35

192425

PROPOSAL BID ITEMS

Report Date 10/25/19

Page 1 of 1

Section: 0001 - PAVING

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0010	00190		LEVELING & WEDGING PG64-22	587.00	TON		\$	
0020	00212		CL2 ASPH BASE 1.00D PG64-22	765.00	TON		\$	
0030	00301		CL2 ASPH SURF 0.38D PG64-22	2,525.00	TON		\$	
0040	00356		ASPHALT MATERIAL FOR TACK	23.00	TON		\$	
0050	02562		TEMPORARY SIGNS	210.00	SQFT		\$	
0060	02650		MAINTAIN & CONTROL TRAFFIC	1.00	LS		\$	
0070	02676		MOBILIZATION FOR MILL & TEXT	1.00	LS		\$	
0800	02677		ASPHALT PAVE MILLING & TEXTURING	780.00	TON		\$	
0090	02697		EDGELINE RUMBLE STRIPS	28,914.00	LF		\$	
0100	06510		PAVE STRIPING-TEMP PAINT-4 IN	23,132.00	LF		\$	
0110	06514		PAVE STRIPING-PERM PAINT-4 IN	57,828.00	LF		\$	
0120	06600		REMOVE PAVEMENT MARKER TYPE V	180.00	EACH		\$	
0130	10020NS		FUEL ADJUSTMENT	6,035.00	DOLL	\$1.00	\$	\$6,035.00
0140	10030NS		ASPHALT ADJUSTMENT	15,158.00	DOLL	\$1.00	\$	\$15,158.00

Section: 0002 - DEMOBILIZATION

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY		UNIT	UNIT PRIC	FP	AMOUNT
0150	02569		DEMOBILIZATION	1.	00	LS		\$	