



CALL NO. 335

CONTRACT ID. 172118

OHIO COUNTY

FED/STATE PROJECT NUMBER FE06 092 0069 011-014

DESCRIPTION HARTFORD-CENTERTOWN ROAD (KY 69)

WORK TYPE GUARDRAIL

PRIMARY COMPLETION DATE 8/1/2017

LETTING DATE: April 28,2017

Sealed Bids will be received electronically through the Bid Express bidding service until 10:00 AM EASTERN DAYLIGHT TIME April 28,2017. Bids will be publicly announced at 10:00 AM EASTERN DAYLIGHT TIME.

NO PLANS ASSOCIATED WITH THIS PROJECT.

REQUIRED BID PROPOSAL GUARANTY: Not less than 5% of the total bid.

TABLE OF CONTENTS

PART I	SCOPE OF WORK • PROJECT(S), COMPLETION DATE(S), & LIQUIDATED DAMAGES • CONTRACT NOTES • STATE CONTRACT NOTES • DGA BASE FOR SHOULDERS • WASTE AND BORROW SITES • SHOULDER PREPARATION • GUARDRAIL • TYPICAL SECTION DIMENSIONS • TRAFFIC CONTROL PLAN • EROSION CONTROL PLAN FOR MAINTENANCE PROJECTS • SKETCH MAP(S) • SUMMARY SHEET(S) • TYPICAL SECTION(S) • DETAIL SHEET(S) • GUARDRAIL DELIVERY VERIFICATION SHEET • GUARDRAIL ON BRIDGE CASE I
PART II	SPECIFICATIONS AND STANDARD DRAWINGS • SPECIFICATIONS REFERENCE • SUPPLEMENTAL SPECIFICATION • 2016 STANDARD DRAWINGS THAT APPLY
PART III	EMPLOYMENT, WAGE AND RECORD REQUIREMENTS • LABOR AND WAGE REQUIREMENTS • EXECUTIVE BRANCH CODE OF ETHICS • KENTUCKY EQUAL EMPLOYMENT OPPORTUNITY ACT OF 1978 LOCALITY / STATE • PROJECT WAGE RATES / STATE
PART IV	INSURANCE
PART V	BID ITEMS

PART I
SCOPE OF WORK

ADMINISTRATIVE DISTRICT - 02

CONTRACT ID - 172118
FE06 092 0069 011-014
COUNTY - OHIO
PCN - MP09200691701
FE06 092 0069 011-014

HARTFORD-CENTERTOWN ROAD (KY 69) (MP 11.594) FROM 0.293 MILES NORTH OF KY 273 EXTENDING NORTH TO 0.662 MILES SOUTH OF US 231. (MP 13.010), A DISTANCE OF 01.42 MILES.GUARDRAIL
GEOGRAPHIC COORDINATES LATITUDE 37:26:24.00 LONGITUDE 86:55:40.00

COMPLETION DATE(S):

COMPLETED BY 08/01/2017	SPECIFIED COMPLETION DATE - ALL ITEMS IN CONTRACT
-------------------------	--

CONTRACT NOTES

PROPOSAL ADDENDA

All addenda to this proposal must be applied when calculating bid and certified in the bid packet submitted to the Kentucky Department of Highways. Failure to use the correct and most recent addenda may result in the bid being rejected.

BID SUBMITTAL

Bidder must use the Department's Expedite Bidding Program available on the Internet web site of the Department of Highways, Division of Construction Procurement. (www.transportation.ky.gov/construction-procurement)

The Bidder must download the bid file located on the Bid Express website (www.bidx.com) to prepare a bid packet for submission to the Department. The bidder must submit electronically using Bid Express.

JOINT VENTURE BIDDING

Joint venture bidding is permissible. All companies in the joint venture must be prequalified in one of the work types in the Qualifications for Bidders for the project. The bidders must get a vendor ID for the joint venture from the Division of Construction Procurement and register the joint venture as a bidder on the project. Also, the joint venture must obtain a digital ID from Bid Express to submit a bid. A joint bid bond of 5% may be submitted for both companies or each company may submit a separate bond of 5%.

UNDERGROUND FACILITY DAMAGE PROTECTION

The contractor shall make every effort to protect underground facilities from damage as prescribed in the Underground Facility Damage Protection Act of 1994, Kentucky Revised Statute KRS 367.4901 to 367.4917. It is the contractor's responsibility to determine and take steps necessary to be in compliance with federal and state damage prevention directives. When prescribed in said directives, the contractor shall submit Excavation Locate Requests to the Kentucky Contact Center (KY811) via web ticket entry. The submission of this request does not relieve the contractor from the responsibility of contacting non-member facility owners, whom shall be contacted through their individual Protection Notification Center. Non-compliance with these directives can result in the enforcement of penalties.

SPECIAL NOTE FOR COMPOSITE OFFSET BLOCKS

Contrary to the Standard Drawings (2016 edition) the Cabinet will allow 6" composite offset blocks in lieu of wooden offset blocks, except as specified on proprietary end treatments and crash cushions. The composite blocks shall be selected from the Cabinet's List of Approved Materials.

REGISTRATION WITH THE SECRETARY OF STATE BY A FOREIGN ENTITY

Pursuant to KRS 176.085(1)(b), an agency, department, office, or political subdivision of the Commonwealth of Kentucky shall not award a state contract to a person that is a foreign entity required by [KRS 14A.9-010](#) to obtain a certificate of authority to transact business in the Commonwealth (“certificate”) from the Secretary of State under [KRS 14A.9-030](#) unless the person produces the certificate within fourteen (14) days of the bid or proposal opening. If the foreign entity is not required to obtain a certificate as provided in [KRS 14A.9-010](#), the foreign entity should identify the applicable exception. Foreign entity is defined within [KRS 14A.1-070](#).

For all foreign entities required to obtain a certificate of authority to transact business in the Commonwealth, if a copy of the certificate is not received by the contracting agency within the time frame identified above, the foreign entity’s solicitation response shall be deemed non-responsive or the awarded contract shall be cancelled.

Businesses can register with the Secretary of State at <https://secure.kentucky.gov/sos/ftbr/welcome.aspx>.

SPECIAL NOTE FOR PROJECT QUESTIONS DURING ADVERTISEMENT

Questions about projects during the advertisement should be submitted in writing to the Division of Construction Procurement. This may be done by fax (502) 564-7299 or email to kytc.projectquestions@ky.gov. The Department will attempt to answer all submitted questions. The Department reserves the right not to answer if the question is not pertinent or does not aid in clarifying the project intent.

The deadline for posting answers will be 3:00 pm Eastern Daylight Time, the day preceding the Letting. Questions may be submitted until this deadline with the understanding that the later a question is submitted, the less likely an answer will be able to be provided.

The questions and answers will be posted for each Letting under the heading “Questions & Answers” on the Construction Procurement website (www.transportation.ky.gov/contract). The answers provided shall be considered part of this Special Note and, in case of a discrepancy, will govern over all other bidding documents.

HARDWOOD REMOVAL RESTRICTIONS

The US Department of Agriculture has imposed a quarantine in Kentucky and several surrounding states, to prevent the spread of an invasive insect, the emerald ash borer. Hardwood cut in conjunction with the project may not be removed from the state. Chipping or burning on site is the preferred method of disposal.

INSTRUCTIONS FOR EXCESS MATERIAL SITES AND BORROW SITES

Identification of excess material sites and borrow sites shall be the responsibility of the Contractor. The Contractor shall be responsible for compliance with all applicable state and federal laws and may wish to consult with the US Fish and Wildlife Service to seek protection under Section 10 of the Endangered Species Act for these activities.

ACCESS TO RECORDS

The contractor, as defined in KRS 45A.030 (9) agrees that the contracting agency, the Finance and Administration Cabinet, the Auditor of Public Accounts, and the Legislative Research Commission, or their duly authorized representatives, shall have access to any books, documents, papers, records, or other evidence, which are directly pertinent to this contract for the purpose of financial audit or program review. Records and other prequalification information confidentially disclosed as part of the bid process shall not be deemed as directly pertinent to the contract and shall be exempt from disclosure as provided in KRS 61.878(1)(c). The contractor also recognizes that any books, documents, papers, records, or other evidence, received during a financial audit or program review shall be subject to the Kentucky Open Records Act, KRS 61.870 to 61.884.

In the event of a dispute between the contractor and the contracting agency, Attorney General, or the Auditor of Public Accounts over documents that are eligible for production and review, the Finance and Administration Cabinet shall review the dispute and issue a determination, in accordance with Secretary's Order 11-004.

06/01/16

SPECIAL NOTE FOR RECIPROCAL PREFERENCE

Reciprocal preference to be given by public agencies to resident bidders

By reference, KRS 45A.490 to 45A.494 are incorporated herein and in compliance regarding the bidders residency. Bidders who want to claim resident bidder status should complete the Affidavit for Claiming Resident Bidder Status along with their bid in the Expedite Bidding Program. Submittal of the Affidavit should be done along with the bid in Bid Express.

03/01/2011

DGA BASE FOR SHOULDERS

Unless otherwise noted, the Department estimates the rate of application for DGA Base for Shoulders to be 115 lbs/sy per inch of depth. The Department will not measure necessary grading and/or shaping of existing shoulders prior to placing of DGA Base, but shall be incidental to the Contract unit price per ton for DGA Base.

Accept payment at the Contract unit price per ton as full compensation for all labor, materials, equipment, and incidentals for grading and/or shaping of existing shoulders and furnishing, placing, and compacting the DGA Base.

SPECIAL PROVISION FOR WASTE AND BORROW SITES

Obtain U.S. Army Corps of Engineer's approval before utilizing a waste or borrow site that involves "Waters of the United States". The Corps of Engineers defines "Waters of the United States" as perennial or intermittent streams, ponds or wetlands. The Corps of Engineers also considers ephemeral streams, typically dry except during rainfall but having a defined drainage channel, to be jurisdictional waters. Direct questions concerning any potential impacts to "Waters of the United States" to the attention of the appropriate District Office for the Corps of Engineers for a determination prior to disturbance. Be responsible for any fees associated with obtaining approval for waste and borrow sites from the U.S. Army Corps of Engineer or other appropriate regulatory agencies.

1-296 Waste & Borrow Sites
01/02/2012

SPECIAL NOTE FOR SHOULDER PREPARATION
FE06 092 0060 011-014

Grade, shape, and compact shoulder as shown on the typical section and as directed by the Engineer to provide proper template and foundation for the guardrail. The Department will not measure grading, shaping, and compacting shoulders for separate payment, but shall be incidental to the DGA placed on the shoulder.

SPECIAL NOTES FOR GUARDRAIL FE06 092 0069 011-014

I. DESCRIPTION

Except as specified herein, perform all work in accordance with the 2012 Department's Standard and Supplemental Specifications, Special Provisions and Special Notes, and Standard and Sepia Drawings, current editions. Article references are to the Standard Specifications.

Furnish all equipment, labor, materials, and incidentals for the following work items:

(1) Site preparation, shoulder preparation, and erosion control; (2) Remove End Treatments and Terminal Sections; (3) Install Guardrail, Extra Length Posts, Bridge Guardrail Reinforcement, and cribbing furnished by the Department; (4) Furnish and install End Treatments and Terminal Sections, posts for Bridge Guardrail Case I, Delineators for Guardrail, and Precast Concrete Bridge Rail Blocks, as applicable; (5) Maintain and control traffic; and (6) all other work specified as part of this contract.

II. MATERIALS

Except as specified herein, provide for all materials to be sampled and tested in accordance with the Department's Sampling Manual and make the materials available for sampling a sufficient time in advance of the use of the materials to allow for the necessary time for testing.

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Erosion Control. See Special Note for Erosion Control.

C. Shoulder Preparation and Cribbing Backfill. Furnish Dense Graded Aggregate (DGA) according to Section 302, no alternate. Do not furnish Crushed Stone Base in lieu of DGA.

D. Materials Furnished by the Department. Unless otherwise specified herein, the Department will make the materials available to the Contractor at the Bailey Bridge Lot in Frankfort, Kentucky between the hours of 8:00 a.m. and 3:30 p.m. Monday through Friday. Determine curvature of radius rail for entrances and terminal sections, number of 9 foot posts, length of rail and cribbing, and other requirements and provide the Engineer a list of requirements fourteen (14) calendar days prior to beginning work.

E. Guardrail and Guardrail Single Face-A. The Department will furnish recycled guardrail elements and radius rail, steel posts, extra length (9 foot) steel posts, and timber

Guardrail
FE06 092 0069 011-014
Page 2 of 6

off set blocks in general conformance to Section 814 and the Standard Drawings, but may vary in some respects, such as gage, pre-punched hole patterns, etc. The Contractor shall furnish guardrail hardware (nuts, bolts, and washers), End Treatments and Terminal Sections, and Bridge Guardrail Posts in accordance with Section 814, Standard Drawings, and Detail Drawings.

F. Bridge Guardrail Case I. Furnish posts and hardware according to the detail drawing. The Department will furnish recycled guardrail elements.

G. Bridge Guardrail Reinforcement. The Department will furnish recycled guardrail elements for Bridge Guardrail Reinforcement.

H. Cribbing. The Department will furnish used or recycled guardrail elements for Cribbing.

I. Delineators for Guardrail. Furnish Bi-Directional White Delineators for Guardrail according to Standard Drawing RBR-055.

J. Precast Concrete Bridge Rail Block. Use Class A Concrete meeting requirements of Section 601.02 and Steel Reinforcement Grade 40, 50, or 60 deformed bars meeting the requirements 811.02.02.

III. CONSTRUCTION METHODS

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Site and Shoulder Preparation. Be responsible for all site preparation, including but not limited to, clearing and grubbing, excavation, embankment, and removal of all obstructions or any other items; regrading, reshaping, adding and compacting of suitable materials on the existing shoulders to provide proper template or foundation for the guardrail; temporary pollution and erosion control; disposal, of excess and waste materials and debris; and final dressing, cleanup, and seeding and protection. Perform all site preparation as approved or directed by the Engineer.

C. Erosion Control. See Special Note for Erosion Control.

D. Install Guardrail. Remove existing end treatments and terminal sections as directed by the Engineer and install materials furnished by the Department to construct guardrail. Except as specified herein, construct guardrail system according to Section 719 and the Standard Drawings. Consider locations listed on the summary and/or shown on the drawings to be approximate only. The Engineer will determine the exact termini for

Guardrail
FE06 092 0069 011-014
Page 3 of 6

individual guardrail installations and locations for extra length posts at the time of construction. Unless directed otherwise by the Engineer, provide a minimum two (2) foot shoulder width. Construct radii at entrances and road intersections as directed by the Engineer.

Erect guardrail to the lines and grades shown on current Standard Drawings or as directed by the Engineer by any method approved by the Engineer which allows construction of the guardrail to the true grade without apparent sags.

When installing guardrail, do not leave blunt ends exposed where they would be hazardous to the public. When it is not practical to complete the construction of the guardrail and the permanent end treatments and terminal sections first, provide a temporary end by connecting at least 25 feet of rail to the last post, and by slightly flaring, and burying the end of the rail completely into the existing shoulder. If left overnight, place a drum with bridge panel in advance of the guardrail end and maintain during use.

E. End Treatments and Terminal Sections. See Section 719.

F. Install Guardrail Single Face-A. Install materials furnished by the Department and construct Guardrail – Steel W Beam (Single Face-A) according to Standard Drawing BHS-007-07.

G. Bridge Guardrail Case 1. Construct Bridge Guardrail Posts as shown on the detail drawings. Install materials furnished by the Department on the posts to complete the Bridge Guardrail Case I.

H. Reinforce Bridge Guardrail. Install materials furnished by the Department over existing rail and posts to form a 2 ply system as shown on the detail drawings.

I. Precast Concrete Bridge Rail Block. Install under guardrail on all 4 corners of bridges with curbs as shown on the detail drawing.

J. Delineators for Guardrail. Construct delineators for guardrail according to Standard Drawing RBR-055 and RBR-060, as applicable, except space at 50 feet on centers

K. Cribbing. Install materials furnished by the Department to construct cribbing at locations determined by the Engineer at the time of construction and backfill with DGA as shown on the detail drawing.

L. Property Damage. Be responsible for all damage to public and/or private property resulting from the work. Restore damaged roadway features and private property at no additional cost to the Department.

Guardrail
FE06 092 0069 011-014
Page 4 of 6

M. Coordination with Utility Companies. Locate all underground, above ground and overhead utilities prior to beginning construction. Be responsible for contacting and maintaining liaison with all utility companies that have utilities located within the project limits. Do not disturb existing overhead or underground utilities. It is not anticipated that any utility facilities will need to be relocated and/or adjusted; however, in the event that it is discovered that the work does require that utilities be relocated and/or adjusted, the utility companies will work concurrently with the Contractor while relocating their facilities. Be responsible for repairing all utility damage that occurs as a result of guardrail operations at no additional cost to the Department.

N. Right of Way Limits. The Department has not established exact limits of the Right-of-Way. Limit work activities to obvious Right-of-Way, permanent or temporary easements, and work areas secured by the Department through consent and release of the adjacent property owners. Be responsible for all encroachments onto private lands.

O. Disposal of Waste. Dispose of all removed concrete, debris, and other waste and debris off the Right-of-Way at sites obtained by the Contractor at no additional cost to the Department. See Special Note for Waste and Borrow.

P. Final Dressing, Clean Up, and Seeding and Protection. Apply Class A Final Dressing to all disturbed areas, both on and off the Right-of-Way. Sow all disturbed earthen areas according to the Special Note for Erosion Control.

Q. Erosion Control. See Special Note for Erosion Control.

IV. METHOD OF MEASUREMENT

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Erosion Control. See Special Note for Erosion Control.

C. Site preparation. Other than the bid items listed, the Department will not measure Site Preparation for separate payment but shall be incidental to Install Guardrail Steel W Beam Single Face and Single Face-A, Install; End Treatments and Terminal Sections; cribbing, and DGA, as applicable.

D. Dense Graded Aggregate. See Section 302.04.

E. Remove End Treatments and Remove Terminal Sections. The Department will measure removed End Treatments and Terminal Sections of each type in individual units, Each.

Guardrail
FE06 092 0069 011-014
Page 5 of 6

F. Guardrail, Steel W Beam Single Face, Install. The Department will measure the actual length of guardrail furnished by the Department and installed by the Contractor. Contrary to section 719.04.01, the Department will measure the actual length of shop curved guardrail in linear feet and will not multiply the actual length by a factor of 1.3 to determine the pay quantity.

G. Guardrail, Steel W Beam Single Face-A, Install. See Standard Drawing BHS-07-07.

H. Reinforce Bridge Guardrail. The Depart will measure installation of materials furnished by the Department over existing rail and posts in Linear Feet.

I. Guardrail Hardware. The Department will not measure guardrail hardware for separate payment but shall be incidental to Guardrail, Steel W Beam Single Face, Install.

J. Extra Length Posts. Contrary to Section 719.04.03, the Department will not measure installation of Extra Length Posts furnished by the Department for separate payment but shall be incidental to Guardrail, Steel W Beam Single Face, Install and Guardrail, Steel W Beam Single Face-A, Install.

K. End Treatments and Terminal Sections. See Section 719.04.

L. Delineators for Guardrail. See Standard Drawing RBR-055.

M. Precast Concrete Bridge Rail Block. The Department will measure Precast Concrete Bridge Rail Blocks in individual units, Each.

N. Cribbing. The Department will measure Cribbing in Square Feet of finished in place area. The Department will not measure laps, cut-offs, excess, and waste.

V. BASIS OF PAYMENT

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Dense Graded Aggregate. See Section 302.05.

C. Remove End Treatments and Remove Terminal Sections. Accept payment at the Contract unit price Each as full compensation for all labor, materials, equipment, and incidentals for removing and salvaging End treatments and Terminal Sections.

D. Guardrail, Steel W Beam Single Face, Install. See Section 719.05.

Guardrail
FE06 092 0069 011-014
Page 6 of 6

E. Guardrail, Steel W Beam Single Face-A, Install. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals installing materials furnished by the Department.

F. End Treatments and Terminal Sections. See Section 719.05.

G. Reinforce Bridge Guardrail. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals installing materials furnished by the Department.

H. Delineators for Guardrail. See Standard Drawing RBR-055.

I. Precast Concrete Bridge Rail Block. Accept payment at the Contract unit price Each as full compensation for all labor, materials, equipment, and for incidentals for furnishing and installing the Precast Concrete Bridge Rail Blocks.

J. Cribbing. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals for installing the materials furnished by the Department.

SPECIAL NOTE FOR TYPICAL SECTION DIMENSIONS

Consider the dimensions shown on the typical sections for pavement and shoulder widths and thickness' to be nominal or typical dimensions. The Engineer may direct or approve varying the actual dimensions to be constructed to fit existing conditions. Do not widen existing pavement or shoulders unless specified elsewhere in this proposal or directed by the engineer.

1-3725 Typical Section Dimensions
01/02/2012

SPECIAL NOTES FOR GUARDRAIL FE06 092 0069 011-014

I. DESCRIPTION

Except as specified herein, perform all work in accordance with the 2012 Department's Standard and Supplemental Specifications, Special Provisions and Special Notes, and Standard and Sepia Drawings, current editions. Article references are to the Standard Specifications.

Furnish all equipment, labor, materials, and incidentals for the following work items:

(1) Site preparation, shoulder preparation, and erosion control; (2) Remove End Treatments and Terminal Sections; (3) Install Guardrail, Extra Length Posts, Bridge Guardrail Reinforcement, and cribbing furnished by the Department; (4) Furnish and install End Treatments and Terminal Sections, posts for Bridge Guardrail Case I, Delineators for Guardrail, and Precast Concrete Bridge Rail Blocks, as applicable; (5) Maintain and control traffic; and (6) all other work specified as part of this contract.

II. MATERIALS

Except as specified herein, provide for all materials to be sampled and tested in accordance with the Department's Sampling Manual and make the materials available for sampling a sufficient time in advance of the use of the materials to allow for the necessary time for testing.

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Erosion Control. See Special Note for Erosion Control.

C. Shoulder Preparation and Cribbing Backfill. Furnish Dense Graded Aggregate (DGA) according to Section 302, no alternate. Do not furnish Crushed Stone Base in lieu of DGA.

D. Materials Furnished by the Department. Unless otherwise specified herein, the Department will make the materials available to the Contractor at the Bailey Bridge Lot in Frankfort, Kentucky between the hours of 8:00 a.m. and 3:30 p.m. Monday through Friday. Determine curvature of radius rail for entrances and terminal sections, number of 9 foot posts, length of rail and cribbing, and other requirements and provide the Engineer a list of requirements fourteen (14) calendar days prior to beginning work.

E. Guardrail and Guardrail Single Face-A. The Department will furnish recycled guardrail elements and radius rail, steel posts, extra length (9 foot) steel posts, and timber

Guardrail
FE06 092 0069 011-014
Page 2 of 6

off set blocks in general conformance to Section 814 and the Standard Drawings, but may vary in some respects, such as gage, pre-punched hole patterns, etc. The Contractor shall furnish guardrail hardware (nuts, bolts, and washers), End Treatments and Terminal Sections, and Bridge Guardrail Posts in accordance with Section 814, Standard Drawings, and Detail Drawings.

F. Bridge Guardrail Case I. Furnish posts and hardware according to the detail drawing. The Department will furnish recycled guardrail elements.

G. Bridge Guardrail Reinforcement. The Department will furnish recycled guardrail elements for Bridge Guardrail Reinforcement.

H. Cribbing. The Department will furnish used or recycled guardrail elements for Cribbing.

I. Delineators for Guardrail. Furnish Bi-Directional White Delineators for Guardrail according to Standard Drawing RBR-055.

J. Precast Concrete Bridge Rail Block. Use Class A Concrete meeting requirements of Section 601.02 and Steel Reinforcement Grade 40, 50, or 60 deformed bars meeting the requirements 811.02.02.

III. CONSTRUCTION METHODS

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Site and Shoulder Preparation. Be responsible for all site preparation, including but not limited to, clearing and grubbing, excavation, embankment, and removal of all obstructions or any other items; regrading, reshaping, adding and compacting of suitable materials on the existing shoulders to provide proper template or foundation for the guardrail; temporary pollution and erosion control; disposal, of excess and waste materials and debris; and final dressing, cleanup, and seeding and protection. Perform all site preparation as approved or directed by the Engineer.

C. Erosion Control. See Special Note for Erosion Control.

D. Install Guardrail. Remove existing end treatments and terminal sections as directed by the Engineer and install materials furnished by the Department to construct guardrail. Except as specified herein, construct guardrail system according to Section 719 and the Standard Drawings. Consider locations listed on the summary and/or shown on the drawings to be approximate only. The Engineer will determine the exact termini for

Guardrail
FE06 092 0069 011-014
Page 3 of 6

individual guardrail installations and locations for extra length posts at the time of construction. Unless directed otherwise by the Engineer, provide a minimum two (2) foot shoulder width. Construct radii at entrances and road intersections as directed by the Engineer.

Erect guardrail to the lines and grades shown on current Standard Drawings or as directed by the Engineer by any method approved by the Engineer which allows construction of the guardrail to the true grade without apparent sags.

When installing guardrail, do not leave blunt ends exposed where they would be hazardous to the public. When it is not practical to complete the construction of the guardrail and the permanent end treatments and terminal sections first, provide a temporary end by connecting at least 25 feet of rail to the last post, and by slightly flaring, and burying the end of the rail completely into the existing shoulder. If left overnight, place a drum with bridge panel in advance of the guardrail end and maintain during use.

E. End Treatments and Terminal Sections. See Section 719.

F. Install Guardrail Single Face-A. Install materials furnished by the Department and construct Guardrail – Steel W Beam (Single Face-A) according to Standard Drawing BHS-007-07.

G. Bridge Guardrail Case 1. Construct Bridge Guardrail Posts as shown on the detail drawings. Install materials furnished by the Department on the posts to complete the Bridge Guardrail Case I.

H. Reinforce Bridge Guardrail. Install materials furnished by the Department over existing rail and posts to form a 2 ply system as shown on the detail drawings.

I. Precast Concrete Bridge Rail Block. Install under guardrail on all 4 corners of bridges with curbs as shown on the detail drawing.

J. Delineators for Guardrail. Construct delineators for guardrail according to Standard Drawing RBR-055 and RBR-060, as applicable, except space at 50 feet on centers

K. Cribbing. Install materials furnished by the Department to construct cribbing at locations determined by the Engineer at the time of construction and backfill with DGA as shown on the detail drawing.

L. Property Damage. Be responsible for all damage to public and/or private property resulting from the work. Restore damaged roadway features and private property at no additional cost to the Department.

Guardrail
FE06 092 0069 011-014
Page 4 of 6

M. Coordination with Utility Companies. Locate all underground, above ground and overhead utilities prior to beginning construction. Be responsible for contacting and maintaining liaison with all utility companies that have utilities located within the project limits. Do not disturb existing overhead or underground utilities. It is not anticipated that any utility facilities will need to be relocated and/or adjusted; however, in the event that it is discovered that the work does require that utilities be relocated and/or adjusted, the utility companies will work concurrently with the Contractor while relocating their facilities. Be responsible for repairing all utility damage that occurs as a result of guardrail operations at no additional cost to the Department.

N. Right of Way Limits. The Department has not established exact limits of the Right-of-Way. Limit work activities to obvious Right-of-Way, permanent or temporary easements, and work areas secured by the Department through consent and release of the adjacent property owners. Be responsible for all encroachments onto private lands.

O. Disposal of Waste. Dispose of all removed concrete, debris, and other waste and debris off the Right-of-Way at sites obtained by the Contractor at no additional cost to the Department. See Special Note for Waste and Borrow.

P. Final Dressing, Clean Up, and Seeding and Protection. Apply Class A Final Dressing to all disturbed areas, both on and off the Right-of-Way. Sow all disturbed earthen areas according to the Special Note for Erosion Control.

Q. Erosion Control. See Special Note for Erosion Control.

IV. METHOD OF MEASUREMENT

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Erosion Control. See Special Note for Erosion Control.

C. Site preparation. Other than the bid items listed, the Department will not measure Site Preparation for separate payment but shall be incidental to Install Guardrail Steel W Beam Single Face and Single Face-A, Install; End Treatments and Terminal Sections; cribbing, and DGA, as applicable.

D. Dense Graded Aggregate. See Section 302.04.

E. Remove End Treatments and Remove Terminal Sections. The Department will measure removed End Treatments and Terminal Sections of each type in individual units, Each.

Guardrail
FE06 092 0069 011-014
Page 5 of 6

F. Guardrail, Steel W Beam Single Face, Install. The Department will measure the actual length of guardrail furnished by the Department and installed by the Contractor. Contrary to section 719.04.01, the Department will measure the actual length of shop curved guardrail in linear feet and will not multiply the actual length by a factor of 1.3 to determine the pay quantity.

G. Guardrail, Steel W Beam Single Face-A, Install. See Standard Drawing BHS-07-07.

H. Reinforce Bridge Guardrail. The Depart will measure installation of materials furnished by the Department over existing rail and posts in Linear Feet.

I. Guardrail Hardware. The Department will not measure guardrail hardware for separate payment but shall be incidental to Guardrail, Steel W Beam Single Face, Install.

J. Extra Length Posts. Contrary to Section 719.04.03, the Department will not measure installation of Extra Length Posts furnished by the Department for separate payment but shall be incidental to Guardrail, Steel W Beam Single Face, Install and Guardrail, Steel W Beam Single Face-A, Install.

K. End Treatments and Terminal Sections. See Section 719.04.

L. Delineators for Guardrail. See Standard Drawing RBR-055.

M. Precast Concrete Bridge Rail Block. The Department will measure Precast Concrete Bridge Rail Blocks in individual units, Each.

N. Cribbing. The Department will measure Cribbing in Square Feet of finished in place area. The Department will not measure laps, cut-offs, excess, and waste.

V. BASIS OF PAYMENT

A. Maintain and Control Traffic. See Traffic Control Plan.

B. Dense Graded Aggregate. See Section 302.05.

C. Remove End Treatments and Remove Terminal Sections. Accept payment at the Contract unit price Each as full compensation for all labor, materials, equipment, and incidentals for removing and salvaging End treatments and Terminal Sections.

D. Guardrail, Steel W Beam Single Face, Install. See Section 719.05.

Guardrail
FE06 092 0069 011-014
Page 6 of 6

E. Guardrail, Steel W Beam Single Face-A, Install. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals installing materials furnished by the Department.

F. End Treatments and Terminal Sections. See Section 719.05.

G. Reinforce Bridge Guardrail. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals installing materials furnished by the Department.

H. Delineators for Guardrail. See Standard Drawing RBR-055.

I. Precast Concrete Bridge Rail Block. Accept payment at the Contract unit price Each as full compensation for all labor, materials, equipment, and for incidentals for furnishing and installing the Precast Concrete Bridge Rail Blocks.

J. Cribbing. Accept payment at the Contract unit price per Linear Foot as full compensation for all labor, materials, equipment, and for incidentals for installing the materials furnished by the Department.

SPECIAL NOTE FOR EROSION CONTROL

FE06 092 0069 011-014

I. DESCRIPTION

Perform all erosion and water pollution control work in accordance with the Department's 2012 Standard and Interim Supplemental Specifications, Special Provisions and Special Notes, and Standard and Sepia Drawings, current editions, and as directed by the Engineer. Section references are to the Standard Specifications. This work shall consist of:

(1) Developing and preparing a Best Management Practices Plan (BMP) tailored to suit the specific construction phasing for each site within the project; (2) Preparing the project site for construction, including locating, furnishing, installing, and maintaining temporary and/or permanent erosion and water pollution control measures as required by the BMP prior to beginning any earth disturbing activity on the project site; (3) Clearing and grubbing and removal of all obstructions as required for construction; (4) Removing all erosion control devices when no longer needed; (5) Restoring all disturbed areas as nearly as possible to their original condition; (6) Preparing seedbeds and permanently seeding all disturbed areas; (7) Providing a Kentucky Erosion Prevention and Sediment Control Program (KEPSC-RI) qualified inspector; and (8) Performing any other work to prevent erosion and/or water pollution as specified by this contract, required by the BMP, or as directed by the Engineer.

II. MATERIALS

Furnish materials in accordance with these notes, the Standard Specifications and Interim Supplemental Specifications, and applicable Special Provisions and Special Notes, and Standard and Sepia Drawings, current editions. Provide for all materials to be sampled and tested in accordance with the Department's Sampling Manual. Unless directed otherwise by the Engineer, make the materials available for sampling a sufficient time in advance of the use of the materials to allow for the necessary time for testing.

III. CONSTRUCTION

Be advised, these Erosion Control Plan Notes do not constitute a BMP plan for the project. Jointly with the Engineer, prepare a site specific BMP plan for each drainage area within the project in accordance with Section 213. Provide a unique BMP at each project site using good engineering practices taking into account existing site conditions, the type of work to be performed, and the construction phasing, methods and techniques to be utilized to complete the work. Be responsible for all erosion prevention, sediment control, and water pollution prevention measures required by

Erosion Control
FE06 092 0069 011-014
Page 2 of 3

the BMP for each site. Represent and warrant compliance with the Clean Water Act (33 USC Section 1251 et seq.), the 404 Permit, the 401 Water Quality Certification, and applicable state and local government agency laws, regulations, rules, specifications, and permits. Contrary to Section 105.05, in case of discrepancy between these notes, the Standard Specifications, Interim Supplemental Specifications, Special and Special Notes, Standard and Sepia Drawings, and such state and local government agency requirements, adhere to the most restrictive requirement.

Conduct operations in such a manner as to minimize the amount of disturbed ground during each phase of the construction and limit the haul roads to the minimum required to perform the work. Preserve existing vegetation not required to be removed by the work or the contract. Seed and/or mulch disturbed areas at the earliest opportunity. Use silt fence, silt traps, temporary ditches, brush barriers, erosion control blankets, sodding, channel lining, and other erosion control measures in a timely manner as required by the BMP and as directed or approved by the Engineer. Prevent sediment laden water from leaving the project, entering an existing drainage structure, or entering a stream.

Provide for erosion control measures to be in place and functioning prior to any earth disturbance within a drainage area. Compute the volume and size of silt control devices necessary to control sediment during each phase of construction. Remove sediment from silt traps before they become a maximum of $\frac{1}{2}$ full. Maintain silt fence by removing accumulated trappings and/or replacing the geotextile fabric when it becomes clogged, damaged, or deteriorated, or when directed by the Engineer. Properly dispose of all materials trapped by erosion control devices at approved sites off the right of way obtained by the Contractor at no additional cost to the Department (See Special Note for Waste and Borrow).

As work progresses, add or remove erosion control measures as required by the BMP applicable to the Contractor's project phasing and construction methods and techniques. Update the volume calculations and modify the BMP as necessary throughout the duration of the project. Ensure that an updated BMP is kept on site and available for public inspection throughout the life of the project.

After all construction is complete, restore all disturbed areas in accordance with Section 212. Completely remove all temporary erosion control devices not required as part of the permanent erosion control from the construction site. Prior to removal, obtain the Engineer's concurrence of items to be removed. Grade the remaining exposed earth (both on and off the Right of-Way) as nearly as possible to its original condition, or as directed by the Engineer. Prepare the seed bed areas and sow all exposed earthen areas with the applicable seed mixture(s) according to Section 212.03.03.

Erosion Control
FE06 092 0069 011-014
Page 3 of 3

IV. MEASUREMENT

Erosion Control Blanket. If required by the BMP, the Department will measure Erosion Control Blanket according to Section 212.04.07.

Sodding. If required by the BMP, the Department will measure Sodding according to Section 212.04.08.

Channel Lining. If required by the BMP, the Department will measure Channel Lining according to Sections 703.04.04-703.04.07.

Erosion Control. Contrary to Sections 212.04, 213.04, and 703.04 other than Erosion Control Blankets, Sodding, and Channel Lining, the Department will not measure Erosion Control, including but not limited to, developing, updating, and maintaining a BMP plan for each site; providing a KEPSC-RI qualified inspector; locating, furnishing, installing, inspecting, maintaining, and removing erosion and water pollution control items; Roadway Excavation, Borrow Excavation, Embankment In Place, Topsoil Furnished and Placed, and Spreading Stockpiled Topsoil; Topdressing Fertilizer, Temporary and Permanent Seeding and Protection, Special Seeding Crown Vetch, and Temporary Mulch; Sedimentation Basin and Clean Sedimentation Basin, Silt Trap Type "A" and Clean Silt Trap Type "A"; Silt Trap Type "B" and Clean Silt Trap Type "B"; Silt Trap Type "C" and Clean Silt Trap Type "C"; Temporary Silt Fence and Clean Temporary Silt Fence; Plants, Vines, Shrubs, and Trees; Gabion and Dumped Stone Deflectors and Riffle Structures; Boulders; Temporary Ditches and clean Temporary Ditches; Geotextile Fabric, and all other erosion and water pollution control items required by the BMP or the Engineer, but shall be incidental to applicable items of work.


V. Basis of Payment

Erosion Control Blanket. If not listed as a bid item, but required by the BMP, the Department will pay for Erosion Control Blankets as Extra Work according to Sections 104.03 and 109.04.

Sodding. If not listed as a bid item, but required by the BMP, the Department will pay for Sodding as Extra Work according to Sections 104.03 and 109.04.

Channel Lining. If not listed as a bid item, but required by the BMP, the Department will pay for Channel Lining as Extra Work according to Sections 104.03 and 109.04.


OHIO COUNTY




GUARDRAIL SUMMARY
FE06 092 0069 011-014


SOUTHBOUND		NORTH BOUND	
11.594	End Treatment Type 1 375' Install Guardrail	11.595	End Treatment Type 1 1225' Install Guardrail
11.665	Radius & Terminal Section No. 1	11.826	Radius & Terminal Section No. 1 Entrance
11.665-11.710	2 Entrances/Guardrail Not Warranted	11.836	Radius & Terminal Section No. 1 550' Install Guardrail
11.710	Radius & Terminal Section No. 1 1187.5' Install Guardrail	11.940	Radius & Terminal Section No. 1 Entrance
11.936	Radius & Terminal Section No. 1 Entrance	11.945	Radius & Terminal Section No. 1 25' Single Face-A
11.941	Radius & Terminal Section No. 1 25' Single Face-A		31.5 ' Bridge Rail Case 1
	31.5' Bridge Rail Case 1		25' Single Face-A
	25' Single Face-A		450' Install Guardrail
	750' Install Guardrail	12.045	Radius & Terminal Section No. 1
12.083	Radius & Terminal Section No. 1	12.045-12.123	Entrance/Guardrail Not Warranted
12.083-12.123	Entrance/Guardrail Not Warranted	12.123	Remove End Treatment Type 6 & Construct End Treatment Type 4A Bridge Rail - Leave in Place
12.123	Remove End Treatment Type 6 & Install End Treatment Type 1 Bridge Rail - Leave in Place	12.235	Remove End Treatment Type 6 & Install End Treatment Type 4A Guardrail Not Warranted
12.235	Remove End Treatment Type 6 & connect to Existing 1225' Install Guardrail	12.235-12.710	Guardrail Not Warranted
12.468	Radius & Terminal Section No. 1	12.710	End Treatment Type 1
12.468-12.802	Entrance/Guardrail Not Warranted		550' Install Guardrail
12.802	Existing Type 7 - Leave in Place	12.813	25' Single Face-A
	Existing Bridge Rail - Leave in Place		Remove Terminal Section No. 1
12.830	Existing Type 7 - Leave in Place		42' Bridge Guardrail Reinforcement
12.835-12.970	Guardrail Not Warranted	12.822	Remove Terminal Section No. 1
12.970	End Treatment Type 1		25' Single Face-A
	75' Install Guardrail		825' Install Guardrail1
	25' Single Face-A	12.980	25' Single Face-A
12.985	Remove Terminal Section No. 1	12.985	Remove Terminal Section No. 1
	42' Bridge Guardrail Reinforcement		42' Bridge Guardrail Reinforcement
12.993	Remove Terminal Section No. 1	12.993	Remove Terminal Section No. 1
	25' Single Face-A		25' Single Face-A
	100' Install Guardrail		100' Install Guardrail
13.010	End treatment Type 1	13.010	End Treatment Type 1

TYPICAL SECTION
FE06 092 0069 011-014





REINFORCE BRIDGE GUARDRAIL
FE06 092 0069 011-014





Bridge MP	L=	D=	No. Posts	On the Bridge
				LF of 2 PLY Rail
12.822	N/A	8	N/A	42
12.993	N/A	8	N/A	84


D = Curb Height

- NOTES:**
- 1. Bridge rail @ Milepoint 12.822 is for northbound side only; however install precast bridge rail blocks on both sides. Bridge rail @ Milepoint 12.993 is for both directions.
 - 2. Use existing posts and rail. Add a second new rail element to form a 2 ply system.
 - 3. Use a Precast Concrete Bridge Block at all 4 corners of the bridge ends facing oncoming traffic in both directions. See detail drawing for Precast Concrete Bridge Block.


PRECAST CONCRETE BRIDGE RAIL BLOCK



NOTE: Excavate as needed to set block in place.



NOTE: ALL EXPOSED EDGES SHALL BE BEVELED 3/4"



Contract Id: _____ Contractor: _____

Section Engineer: _____ District & County: _____

DESCRIPTION	UNIT	QTY LEAVING PROJECT	QTY RECEIVED@BB YARD
GUARDRAIL (Includes End treatments & crash cushions)	LF	_____	_____
STEEL POSTS	EACH	_____	_____
STEEL BLOCKS	EACH	_____	_____
WOOD OFFSET BLOCKS	EACH	_____	_____
BACK UP PLATES	EACH	_____	_____
CRASH CUSHION	EACH	_____	_____
NUTS, BOLTS, WASHERS	BAG/BCKT	_____	_____
DAMAGED RAIL TO MAINT. FACILITY	LF	_____	_____
DAMAGED POSTS TO MAINT. FACILITY	EACH	_____	_____

***Required Signatures before Leaving Project Site**

Printed Section Engineer’s Representative_____ & Date_____

Signature Section Engineer’s Representative_____ & Date_____

Printed Contractor’s Representative_____ & Date_____

Signature Contractor’s Representative_____ & Date_____

***Required Signatures after Arrival at Bailey Bridge Yard (All material on truck must be counted & the quantity received column completed before signatures)**

Printed Bailey Bridge Yard Representative_____ & Date_____


Signature Bailey Bridge Yard Representative_____ & Date_____

Printed Contractor’s Representative_____ & Date_____

Signature Contractor’s Representative_____ & Date_____

**Payment for the bid item remove guardrail will be based upon the quantities shown in the Bailey Bridge Yard received column. Payment will not be made for guardrail removal until the guardrail verification sheets are electronically submitted to the Section Engineer by the Bailey Bridge Yard Representative.

GUARDRAIL ON BRIDGE, CASE I
BLACKTOP FLUSH WITH CURB OR ABOVE
FE06 092 0069 011-014



Bridge MP	D =	W=	L=	No. Posts	LF of 2 PLY Rail
11.950	0	14"	4'	11	63'

L = Length of Guardrail Post D = Curb Height W = Width of Bridge Curb

WARRANTS: When guardrail can be bolted to the back of the bridge curb, and where the bridge surface is flush with the curb top, and where the clear distance between the faces of the guardrail is less than 20 Feet, remove existing concrete and/or guardrail bridge rail and use Case I Bridge Guardrail.

- NOTES:**
- 1. If asphalt paving is included in the Contract and the dimension from the top of the existing riding surface to the top of the curb is 2 inches or less, pave the surface flush to the top of the curb, and use Case I Bridge Guardrail.
 - 2. Do not use Case I Bridge Guardrail if existing pavement is not flush with the pavement and asphalt pavement is not included in the Contract or if the dimension from top of the existing riding surface to the top of the curb is greater than 2 inches.

PART II

SPECIFICATIONS AND STANDARD DRAWINGS

SPECIFICATIONS REFERENCE

Any reference in the plans or proposal to previous editions of the *Standard Specifications for Road and Bridge Construction* and *Standard Drawings* are superseded by *Standard Specifications for Road and Bridge Construction, Edition of 2012* and *Standard Drawings, Edition of 2016*.

SUPPLEMENTAL SPECIFICATIONS

The contractor shall use the Supplemental Specifications that are effective at the time of letting.
The Supplemental Specifications can be found at the following link:

<http://transportation.ky.gov/Construction/Pages/Kentucky-Standard-Specifications.aspx>

2016 APPLICABLE KENTUCKY STANDARD DRAWINGS

FE06 092 0069 011-014

RAILING SYSTEM TY II GUARDRAIL TREATMENT.....	BHS-007-07
TYPICAL GUARDRAIL INSTALLATIONS.....	RBI-001-11
TYPICAL GUARDRAIL INSTALLATIONS.....	RBI-002-07
INSTALLATION OF GUARDRAIL END TREATMENT TYPE 1	RBI-004-05
STEEL BEAM GUARDRAIL (“W”-BEAM).....	RBR-001-12
GUARDRAIL COMPONENTS.....	RBR-005-11
GUARDRAIL TERMINAL SECTIONS	RBR-010-06
STEEL GUARDRAIL POSTS.....	RBR-015-05
GUARDRAIL END TREATMENT TYPE 1	RBR-020-06
GUARDRAIL END TREATMENT TYPE 4A	RBR-035-11
DELINEATORS FOR GUARDRAIL.....	RBR-055
CURVE WIDENING AND SUPERELEVATION TRANSITIONS.....	RGS-001-07
MISCELLANEOUS STANDARDS	RGX-001-06
LANE CLOSURE TWO-LANE HIGHWAY	TTC-100-04
SHOULDER CLOSURE.....	TTC-135-02
PAVEMENT CONDITION WARNING SIGNS	TTD-125-02

PART III

EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

**TRANSPORTATION CABINET
DEPARTMENT OF HIGHWAYS**

**LABOR AND WAGE REQUIREMENTS
APPLICABLE TO OTHER THAN FEDERAL-AID SYSTEM PROJECTS**

- I. Application
- II. Nondiscrimination of Employees (KRS 344)

I. APPLICATION

1. These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to all work performed on the contract by piecework, station work or by subcontract. The contractor's organization shall be construed to include only workmen employed and paid directly by the contractor and equipment owned or rented by him, with or without operators.

2. The contractor shall insert in each of his subcontracts all of the stipulations contained in these Required Provisions and such other stipulations as may be required.

3. A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

3. If the contractor is in control of apprenticeship or other training or retraining, including on-the-job training programs, he shall not discriminate against an individual because of his race, color, religion, national origin, sex, disability or age forty (40) and over, in admission to, or employment in any program established to provide apprenticeship or other training.

4. The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representative of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment. The contractor will take such action with respect to any subcontract or purchase order as the administering agency may direct as a means of enforcing such provisions, including sanctions for non-compliance.

Revised: January 25, 2017

II. NONDISCRIMINATION OF EMPLOYEES

**AN ACT OF THE KENTUCKY
GENERAL ASSEMBLY TO PREVENT
DISCRIMINATION IN EMPLOYMENT
KRS CHAPTER 344
EFFECTIVE JUNE 16, 1972**

The contract on this project, in accordance with KRS Chapter 344, provides that during the performance of this contract, the contractor agrees as follows:

1. The contractor shall not fail or refuse to hire, or shall not discharge any individual, or otherwise discriminate against an individual with respect to his compensation, terms, conditions, or privileges of employment, because of such individual's race, color, religion, national origin, sex, disability or age (forty and above); or limit, segregate, or classify his employees in any way which would deprive or tend to deprive an individual of employment opportunities or otherwise adversely affect his status as an employee, because of such individual's race, color, religion, national origin, sex, disability or age forty (40) and over. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.

2. The contractor shall not print or publish or cause to be printed or published a notice or advertisement relating to employment by such an employer or membership in or any classification or referral for employment by the employment agency, indicating any preference, limitation, specification, or discrimination, based on race, color, religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, except that such a notice or advertisement may indicate a preference, limitation, or specification based on religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, when religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, is a bona fide occupational qualification for employment.

EXECUTIVE BRANCH CODE OF ETHICS

In the 1992 regular legislative session, the General Assembly passed and Governor Brereton Jones signed Senate Bill 63 (codified as KRS 11A), the Executive Branch Code of Ethics, which states, in part:

KRS 11A.040 (7) provides:

No present or former public servant shall, within six (6) months following termination of his office or employment, accept employment, compensation, or other economic benefit from any person or business that contracts or does business with, or is regulated by, the state in matters in which he was directly involved during the last thirty-six (36) months of his tenure. This provision shall not prohibit an individual from returning to the same business, firm, occupation, or profession in which he was involved prior to taking office or beginning his term of employment, or for which he received, prior to his state employment, a professional degree or license, provided that, for a period of six (6) months, he personally refrains from working on any matter in which he was directly involved during the last thirty-six (36) months of his tenure in state government. This subsection shall not prohibit the performance of ministerial functions, including but not limited to filing tax returns, filing applications for permits or licenses, or filing incorporation papers, nor shall it prohibit the former officer or public servant from receiving public funds disbursed through entitlement programs.

KRS 11A.040 (9) states:

A former public servant shall not represent a person or business before a state agency in a matter in which the former public servant was directly involved during the last thirty-six (36) months of his tenure, for a period of one (1) year after the latter of:

- a) The date of leaving office or termination of employment; or
- b) The date the term of office expires to which the public servant was elected.

This law is intended to promote public confidence in the integrity of state government and to declare as public policy the idea that state employees should view their work as a public trust and not as a way to obtain private benefits.

If you have worked for the executive branch of state government within the past six months, you may be subject to the law's prohibitions. The law's applicability may be different if you hold elected office or are contemplating representation of another before a state agency.

Also, if you are affiliated with a firm which does business with the state and which employs former state executive-branch employees, you should be aware that the law may apply to them.

In case of doubt, the law permits you to request an advisory opinion from the Executive Branch Ethics Commission, 3 Fountain Place, Frankfort, Kentucky 40601; telephone (502) 564-7954.

Revised: January 27, 2017

Kentucky Equal Employment Opportunity Act of 1978

The requirements of the Kentucky Equal Employment Opportunity Act of 1978 (KRS 45.560-45.640) shall apply to this Contract. The apparent low Bidder will be required to submit EEO forms to the Division of Construction Procurement, which will then forward to the Finance and Administration Cabinet for review and approval. No award will become effective until all forms are submitted and EEO/CC has certified compliance. The required EEO forms are as follows:

- EEO-1: Employer Information Report
- Affidavit of Intent to Comply
- Employee Data Sheet
- Subcontractor Report

These forms are available on the Finance and Administration's web page under ***Vendor Information, Standard Attachments and General Terms*** at the following address:
<https://www.eProcurement.ky.gov>.

Bidders currently certified as being in compliance by the Finance and Administration Cabinet may submit a copy of their approval letter in lieu of the referenced EEO forms.

For questions or assistance please contact the Finance and Administration Cabinet by email at **finance.contractcompliance@ky.gov** or by phone at 502-564-2874.

EMPLOYEE RIGHTS

UNDER THE FAIR LABOR STANDARDS ACT

THE UNITED STATES DEPARTMENT OF LABOR WAGE AND HOUR DIVISION

FEDERAL MINIMUM WAGE

\$7.25 PER HOUR

BEGINNING JULY 24, 2009

OVERTIME PAY

At least 1½ times your regular rate of pay for all hours worked over 40 in a workweek.

CHILD LABOR

An employee must be at least **16** years old to work in most non-farm jobs and at least **18** to work in non-farm jobs declared hazardous by the Secretary of Labor.

Youths **14** and **15** years old may work outside school hours in various non-manufacturing, non-mining, non-hazardous jobs under the following conditions:

No more than

- **3** hours on a school day or **18** hours in a school week;
- **8** hours on a non-school day or **40** hours in a non-school week.

Also, work may not begin before **7 a.m.** or end after **7 p.m.**, except from June 1 through Labor Day, when evening hours are extended to **9 p.m.** Different rules apply in agricultural employment.

TIP CREDIT

Employers of “tipped employees” must pay a cash wage of at least \$2.13 per hour if they claim a tip credit against their minimum wage obligation. If an employee's tips combined with the employer's cash wage of at least \$2.13 per hour do not equal the minimum hourly wage, the employer must make up the difference. Certain other conditions must also be met.

ENFORCEMENT

The Department of Labor may recover back wages either administratively or through court action, for the employees that have been underpaid in violation of the law. Violations may result in civil or criminal action.

Employers may be assessed civil money penalties of up to \$1,100 for each willful or repeated violation of the minimum wage or overtime pay provisions of the law and up to \$11,000 for each employee who is the subject of a violation of the Act's child labor provisions. In addition, a civil money penalty of up to \$50,000 may be assessed for each child labor violation that causes the death or serious injury of any minor employee, and such assessments may be doubled, up to \$100,000, when the violations are determined to be willful or repeated. The law also prohibits discriminating against or discharging workers who file a complaint or participate in any proceeding under the Act.

ADDITIONAL INFORMATION

- Certain occupations and establishments are exempt from the minimum wage and/or overtime pay provisions.
- Special provisions apply to workers in American Samoa and the Commonwealth of the Northern Mariana Islands.
- Some state laws provide greater employee protections; employers must comply with both.
- The law requires employers to display this poster where employees can readily see it.
- Employees under 20 years of age may be paid \$4.25 per hour during their first 90 consecutive calendar days of employment with an employer.
- Certain full-time students, student learners, apprentices, and workers with disabilities may be paid less than the minimum wage under special certificates issued by the Department of Labor.

For additional information:



1-866-4-USWAGE

(1-866-487-9243)

TTY: 1-877-889-5627



WWW.WAGEHOUR.DOL.GOV

PART IV

INSURANCE

INSURANCE

The Contractor shall procure and maintain the following insurance in addition to the insurance required by law:

- 1) Commercial General Liability-Occurrence form – not less than \$2,000,000 General aggregate, \$2,000,000 Products & Completed Aggregate, \$1,000,000 Personal & Advertising, \$1,000,000 each occurrence.
- 2) Automobile Liability- \$1,000,000 per accident
- 3) Employers Liability:
 - a) \$100,000 Each Accident Bodily Injury
 - b) \$500,000 Policy limit Bodily Injury by Disease
 - c) \$100,000 Each Employee Bodily Injury by Disease
- 4) The insurance required above must be evidenced by a Certificate of Insurance and this Certificate of Insurance must contain one of the following statements:
 - a) "policy contains no deductible clauses."
 - b) "policy contains _____ (amount) deductible property damage clause but company will pay claim and collect the deductible from the insured."
- 5) KENTUCKY WORKMEN'S COMPENSATION INSURANCE. The contractor shall furnish evidence of coverage of all his employees or give evidence of self-insurance by submitting a copy of a certificate issued by the Workmen's Compensation Board.

The cost of insurance is incidental to all contract items. All subcontractors must meet the same minimum insurance requirements.

PART V

BID ITEMS

Section: 0001 - GUARDAIL

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0010	00001		DGA BASE	1,140.00	TON		\$	
0020	01987		DELINEATOR FOR GUARDRAIL BI DIRECTIONAL WHITE	160.00	EACH		\$	
0030	02353		INSTALL GUARDRAIL-STEEL W BM-S FACE	7,412.50	LF		\$	
0040	02355		GUARDRAIL-STEEL W BEAM-S FACE A INSTALL	250.00	LF		\$	
0050	02360		GUARDRAIL TERMINAL SECTION NO 1	11.00	EACH		\$	
0060	02367		GUARDRAIL END TREATMENT TYPE 1	7.00	EACH		\$	
0070	02391		GUARDRAIL END TREATMENT TYPE 4A	2.00	EACH		\$	
0080	02395		REMOVE GUARDRAIL TERMINAL SECT NO 1	6.00	EACH		\$	
0090	02396		REMOVE GUARDRAIL END TREATMENT TYPE 6	4.00	EACH		\$	
0100	02562		TEMPORARY SIGNS	150.00	SQFT		\$	
0110	02650		MAINTAIN & CONTROL TRAFFIC	1.00	LS		\$	
0120	03236		CRIBBING	6,975.00	SQFT		\$	
0130	08805		GUARDRAIL-BRIDGE CASE I	63.00	LF		\$	
0140	08810		PRECAST CONC BRIDGE RAIL BLOCK	8.00	EACH		\$	
0150	23300EC		REINFORCE BRIDGE GUARDRAIL INSTALL 2ND PLY TO EXIST POSTS AND RAIL	126.00	LF		\$	

Section: 0002 - DEMOBILIZATION

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0160	02569		DEMOBILIZATION	1.00	LS		\$	