

CALL NO. <u>401</u> CONTRACT ID. <u>222096</u> <u>GRANT COUNTY</u> FED/STATE PROJECT NUMBER <u>041GR22P005 - FD05</u> DESCRIPTION <u>KY 3025, US 25, AND US 25X IN GRANT COUNTY</u> WORK TYPE <u>ASPHALT RESURFACING</u> PRIMARY COMPLETION DATE <u>11/15/2022</u>

#### **LETTING DATE:** <u>May</u> <u>26,2022</u>

Sealed Bids will be received electronically through the Bid Express bidding service until 10:00 AM EASTERN DAYLIGHT TIME May 26,2022. Bids will be publicly announced at 10:00 AM EASTERN DAYLIGHT TIME.

#### NO PLANS ASSOCIATED WITH THIS PROJECT.

**DEFERRED PAYMENT** 

**REQUIRED BID PROPOSAL GUARANTY:** Not less than 5% of the total bid.

# TABLE OF CONTENTS

#### PART I SCOPE OF WORK

- PROJECT(S), COMPLETION DATE(S), & LIQUIDATED DAMAGES
- CONTRACT NOTES
- STATE CONTRACT NOTES
- DEFERRED PAYMENT
- SURFACING AREAS
- ASPHALT MIXTURE
- DGA BASE FOR SHOULDERS
- INCIDENTAL SURFACING
- FUEL AND ASPHALT PAY ADJUSTMENT
- COMPACTION OPTION A
- COMPACTION OPTION B
- WASTE AND BORROW SITES
- ASPHALT MIX PAVEMENT WEDGE MONOLITHIC OPERATION
- ASPHALT MILLING AND TEXTURING
- ASPHALT MILLING AND TEXTURING
- BASE FAILURE REPAIR
- TYPICAL SECTION DIMENSIONS
- TRAFFIC CONTROL PLAN 2 LANE
- DURABLE PAVEMENT EDGE DETAILS
- TRAFFIC SIGNAL LOOP DETECTORS
- SKETCH MAP(S)
- MATERIAL SUMMARY
- SUMMARY SHEET(S)
- TYPICAL SECTION(S)
- BRIDGE DETAIL FOR PAVING PROJECT

#### PART II SPECIFICATIONS AND STANDARD DRAWINGS

- SPECIFICATIONS REFERENCE
- SUPPLEMENTAL SPECIFICATION
- 2020 STANDARD DRAWINGS THAT APPLY

#### PART III EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

- LABOR AND WAGE REQUIREMENTS
- EXECUTIVE BRANCH CODE OF ETHICS
- KENTUCKY EQUAL EMPLOYMENT OPPORTUNITY ACT OF 1978 LOCALITY / STATE
- PROJECT WAGE RATES / STATE FUNDED
- PART IV INSURANCE
- PART V BID ITEMS

# PART I

# **SCOPE OF WORK**

#### **ADMINISTRATIVE DISTRICT - 06**

#### CONTRACT ID - 222096

041GR22P005 - FD05

#### **COUNTY - GRANT**

#### PCN - MP04100252201 FD05 041 0025 012-014

DIXIE HIGHWAY (US 25) (MP 12.680) BEGINNING AT RIDGELEA DRIVE/KY 1560 EXTENDING NORTH TO THE PAVEMENT JOINT 0.114 MILES SOUTH OF HOGAN'S PARKWAY. (MP 14.000), A DISTANCE OF 01.32 MILES.ASPHALT RESURFACING

GEOGRAPHIC COORDINATES LATITUDE 38:39:37.00 LONGITUDE 84:34:38.00 ADT 5,736

#### PCN - MP041025X2201 FD05 041 025X 000-003

DIXIE HIGHWAY (US 25X) (MP 0.000) BEGINNING AT US 25 EXTENDING NORTH TO US 25. (MP 2.239), A DISTANCE OF 02.23 MILES.ASPHALT RESURFACING

GEOGRAPHIC COORDINATES LATITUDE 38:40:15.00 LONGITUDE 84:34:49.00

ADT 7,897

#### PCN - MP04130252201 FD05 041 3025 001-002

ARNIE RISEN BLVD. (KY 3025) (MP 1.072) BEGIN AT KY 1560 EXTENDING NORTH TO US 25X (MP 1.757), A DISTANCE OF 0.68 MILES.ASPHALT RESURFACING GEOGRAPHIC COORDINATES LATITUDE 38:39:22.45 LONGITUDE 84:34:36.59 ADT 2,822

#### COMPLETION DATE(S):

COMPLETED BY 11/15/2022

APPLIES TO ENTIRE CONTRACT

## **CONTRACT NOTES**

#### PROPOSAL ADDENDA

All addenda to this proposal must be applied when calculating bid and certified in the bid packet submitted to the Kentucky Department of Highways. Failure to use the correct and most recent addenda may result in the bid being rejected.

#### **BID SUBMITTAL**

Bidder must use the Department's electronic bidding software. The Bidder must download the bid file located on the Bid Express website (www.bidx.com) to prepare a bid packet for submission to the Department. The bidder must submit electronically using Bid Express.

#### JOINT VENTURE BIDDING

Joint venture bidding is permissible. All companies in the joint venture must be prequalified in one of the work types in the Qualifications for Bidders for the project. The bidders must get a vendor ID for the joint venture from the Division of Construction Procurement and register the joint venture as a bidder on the project. Also, the joint venture must obtain a digital ID from Bid Express to submit a bid. A joint bid bond of 5% may be submitted for both companies or each company may submit a separate bond of 5%.

#### **UNDERGROUND FACILITY DAMAGE PROTECTION**

The contractor shall make every effort to protect underground facilities from damage as prescribed in the Underground Facility Damage Protection Act of 1994, Kentucky Revised Statute KRS 367.4901 to 367.4917. It is the contractor's responsibility to determine and take steps necessary to be in compliance with federal and state damage prevention directives. When prescribed in said directives, the contractor shall submit Excavation Locate Requests to the Kentucky Contact Center (KY811) via web ticket entry. The submission of this request does not relieve the contractor from the responsibility of contacting non-member facility owners, whom shall be contacted through their individual Protection Notification Center. Non-compliance with these directives can result in the enforcement of penalties.

#### **REGISTRATION WITH THE SECRETARY OF STATE BY A FOREIGN ENTITY**

Pursuant to KRS 176.085(1)(b), an agency, department, office, or political subdivision of the Commonwealth of Kentucky shall not award a state contract to a person that is a foreign entity required by <u>KRS 14A.9-010</u> to obtain a certificate of authority to transact business in the Commonwealth ("certificate") from the Secretary of State under <u>KRS 14A.9-030</u> unless the person produces the certificate within fourteen (14) days of the bid or proposal opening. If the foreign entity is not required to obtain a certificate as provided in <u>KRS 14A.9-010</u>, the foreign entity should identify the applicable exception. Foreign entity is defined within <u>KRS 14A.1-070</u>.

For all foreign entities required to obtain a certificate of authority to transact business in the Commonwealth, if a copy of the certificate is not received by the contracting agency within the time frame identified above, the foreign entity's solicitation response shall be deemed non-responsive or the awarded contract shall be cancelled.

Businesses can register with the Secretary of State at <u>https://secure.kentucky.gov/sos/ftbr/welcome.aspx</u>.

#### SPECIAL NOTE FOR PROJECT QUESTIONS DURING ADVERTISEMENT

Questions about projects during the advertisement should be submitted in writing to the Division of Construction Procurement. This may be done by fax (502) 564-7299 or email to <u>kytc.projectquestions@ky.gov</u>. The Department will attempt to answer all submitted questions. The Department reserves the right not to answer if the question is not pertinent or does not aid in clarifying the project intent.

The deadline for posting answers will be 3:00 pm Eastern Daylight Time, the day preceding the Letting. Questions may be submitted until this deadline with the understanding that the later a question is submitted, the less likely an answer will be able to be provided.

The questions and answers will be posted for each Letting under the heading "Questions & Answers" on the Construction Procurement website (<u>www.transportation.ky.gov/contract</u>). The answers provided shall be considered part of this Special Note and, in case of a discrepancy, will govern over all other bidding documents.

#### HARDWOOD REMOVAL RESTRICTIONS

The US Department of Agriculture has imposed a quarantine in Kentucky and several surrounding states, to prevent the spread of an invasive insect, the emerald ash borer. Hardwood cut in conjunction with the project may not be removed from the state. Chipping or burning on site is the preferred method of disposal.

#### INSTRUCTIONS FOR EXCESS MATERIAL SITES AND BORROW SITES

Identification of excess material sites and borrow sites shall be the responsibility of the Contractor. The Contractor shall be responsible for compliance with all applicable state and federal laws and may wish to consult with the US Fish and Wildlife Service to seek protection under Section 10 of the Endangered Species Act for these activities.

#### ACCESS TO RECORDS

The contractor, as defined in KRS 45A.030 (9) agrees that the contracting agency, the Finance and Administration Cabinet, the Auditor of Public Accounts, and the Legislative Research Commission, or their duly authorized representatives, shall have access to any books, documents, papers, records, or other evidence, which are directly pertinent to this contract for the purpose of financial audit or program review. Records and other prequalification information confidentially

disclosed as part of the bid process shall not be deemed as directly pertinent to the contract and shall be exempt from disclosure as provided in KRS 61.878(1)(c). The contractor also recognizes that any books, documents, papers, records, or other evidence, received during a financial audit or program review shall be subject to the Kentucky Open Records Act, KRS 61.870 to 61.884.

In the event of a dispute between the contractor and the contracting agency, Attorney General, or the Auditor of Public Accounts over documents that are eligible for production and review, the Finance and Administration Cabinet shall review the dispute and issue a determination, in accordance with Secretary's Order 11-004.

April 30, 2018

#### SPECIAL NOTE FOR RECIPROCAL PREFERENCE

#### **RECIPROCAL PREFERENCE TO BE GIVEN BY PUBLIC AGENCIES TO RESIDENT** BIDDERS

By reference, KRS 45A.490 to 45A.494 are incorporated herein and in compliance regarding the bidders residency. Bidders who want to claim resident bidder status should complete the Affidavit for Claiming Resident Bidder Status along with their bid in the electronic bidding software. Submittal of the Affidavit should be done along the bid in Bid Express.

April 30, 2018

## DEFERRED PAYMENT

The successful bidder on this project may request a work order with an effective date prior to June 15, 2022. The successful bidder must make the request in writing to the Department. The Department will issue a work order at the request of the contractor with the distinct understanding that payment for any Work Performed Estimates may be delayed until July 15, 2022. Unless the successful bidder requests an earlier work order date, the Department will issue a work order on June 15, 2022 for this project.

#### SURFACING AREAS KY 3025

The Department estimates the mainline surfacing width to be 24 feet. The Department estimates the total mainline area to be surfaced to be 10,610 square yards. The Department estimates the asphalt shoulder width to be varied 0 to 1.5 foot on each side. The Department estimates the total shoulder area to be surfaced to be 1,145 square yards. SURFACING AREAS US 25 The Department estimates the mainline surfacing width to be varied 24-36 feet. The Department estimates the total mainline area to be surfaced to be 24,892 square yards. The Department estimates the asphalt shoulder width to be 1 foot on each side. The Department estimates the total shoulder area to be surfaced to be 1,549 square yards. The Department estimates the DGA shoulder width to be 1.5 feet on each side. The Department estimates the total shoulder area to receive DGA to be 2,323 square yards. SURFACING AREAS US 25X The Department estimates the mainline surfacing width to be varied 24-38 feet. The Department estimates the total mainline area to be surfaced to be 50,879 square yards. The Department estimates the asphalt shoulder width to be varied 0-8 feet on each side. The Department estimates the total shoulder area to be surfaced to be 3,445 square yards.

The Department estimates the DGA shoulder width to be 1 foot on each side.

The Department estimates the total shoulder area to receive DGA to be 2,627 square yards.

#### ASPHALT MIXTURE

Unless otherwise noted, the Department estimates the rate of application for all asphalt mixtures to be 110 lbs/sy per inch of depth.

#### DGA BASE FOR SHOULDERS (US 25 AND US 25X)

Unless otherwise noted, the Department estimates the rate of application for DGA Base for Shoulders to be 115 lbs/sy per inch of depth. The Department will not measure necessary grading and/or shaping of existing shoulders prior to placing of DGA Base, but shall be incidental to the Contract unit price per ton for DGA Base.

Accept payment at the Contract unit price per ton as full compensation for all labor, materials, equipment, and incidentals for grading and/or shaping of existing shoulders and furnishing, placing, and compacting the DGA Base.

#### **INCIDENTAL SURFACING**

The Department has included in the quantities of asphalt mixtures established in the proposal estimated quantities required for resurfacing or surfacing mailbox turnouts, farm field entrances, residential and commercial entrances, curve widening, ramp gores and tapers, and road and street approaches, as applicable. Pave these areas to the limits as shown on Standard Drawing RPM-110-06 or as directed by the Engineer. In the event signal detectors are present in the intersecting streets or roads, pave the crossroads to the right of way limit or back of the signal detector, whichever is the farthest back of the mainline. Surface or resurface these areas as directed by the Engineer. The Department will not measure placing and compacting for separate payment but shall be incidental to the Contract unit price for the asphalt mixtures.

#### FUEL AND ASPHALT PAY ADJUSTMENT

The Department has included the Contract items Asphalt Adjustment and Fuel Adjustment for possible future payments at an established Contract unit price of \$1.00. The Department will calculate actual adjustment quantities after work is completed. If existing Contract amount is insufficient to pay all items on the contract with the adjustments, the Department will establish additional monies with a change order.

#### OPTION A (US 25 AND US 25X)

Be advised that the Department will accept compaction of asphalt mixtures furnished for driving lanes and ramps, at 1 inch (25mm) or greater, on this project according to OPTION A in accordance with Section 402 and Section 403 of the current Standard Specifications. The Department will require joint cores as described in Section 402.03.02 for surface mixtures only. The Department will accept compaction of all other asphalt mixtures according to OPTION B.

#### **OPTION B KY 3025**

Be advised that the Department will control and accept compaction of asphalt mixtures furnished on this project under OPTION B in accordance with Sections 402 and 403.

#### SPECIAL PROVISION FOR WASTE AND BORROW SITES (US 25)

Obtain U.S. Army Corps of Engineer's approval before utilizing a waste or borrow site that involves "Waters of the United States". The Corps of Engineers defines "Waters of the United States" as perennial or intermittent streams, ponds or wetlands. The Corps of Engineers also considers ephemeral streams, typically dry except during rainfall but having a defined drainage channel, to be jurisdictional waters. Direct questions concerning any potential impacts to "Waters of the United States" to the attention of the appropriate District Office for the Corps of Engineers for a determination prior to disturbance. Be responsible for any fees associated with obtaining approval for waste and borrow sites from the U.S. Army Corps of Engineer or other appropriate regulatory agencies.

1-296 Waste & Borrow Sites 01/02/2012

#### SPECIAL NOTE FOR PAVEMENT WEDGE AND SHOULDER MONOLITHIC OPERATION

**1.0 MATERIALS.** Provide an Asphalt Surface Mixture conforming to Section 403 of the Standard Specifications, as applicable to the project, for the pavement wedge.

**2.0 CONSTRUCTION.** Place the specified Asphalt Surface Mixture on shoulders monolithically with the driving lane. Prime the existing shoulder with tack material as the Engineer directs before placing the wedge. Construct according to Section 403.03 of the Standard Specifications.

Equip the paver with a modified screed that extends the full width of the wedge being placed and is tapered to produce a wedge. Obtain the Engineer's approval of the modified screed before placing shoulder wedge monolithically with the driving lane.

The wedge may vary in thickness at the edge of the milled area in the shoulder. If the area to receive the shoulder wedge is milled prior to placement, during rolling operations pinch the outside edge of the new inlay wedge to match the existing shoulder elevation not being resurfaced. Unless required otherwise by the Contract, construct rolled or sawed rumble strips according to Section 403.03.08, as applicable.

The following sketch is primarily for the computation of quantities; however, the wedge will result in a similar cross-section where sufficient width exists. Do not construct a shoulder for placing the wedge unless specified elsewhere in the Contract.



**3.0 MEASUREMENT.** The Department will measure Asphalt Surface Mixture placed as the pavement wedge according to Section 403.

**4.0 PAYMENT.** The Department will make payment for the completed and accepted quantities of Asphalt Surface Mixtures on pavement wedges according to Section 403.

1-3232-DS Pavement Wedge Monolithic 01/02/2012

#### SPECIAL NOTE FOR ASPHALT MILLING AND TEXTURING (KY 3025 AND US 25X)

Begin paving operations within <u>48 hours</u> of commencement of the milling operation. Continue paving operations continuously until completed. If paving operations are not begun within this time period, the Department will assess liquidated damages at the rate prescribed by Section 108.09 until such time as paving operations are begun.

Take possession of the millings and recycle the millings or dispose of the millings off the Rightof-Way at sites obtained by the Contractor at no additional cost to the Department.

### SPECIAL NOTE FOR ASPHALT MILLING AND TEXTURING (US 25)

Begin paving operations within <u>48 hours</u> of commencement of the milling operation. Continue paving operations continuously until completed. If paving operations are not begun within this time period, the Department will assess liquidated damages at the rate prescribed by Section 108.09 until such time as paving operations are begun.

Contrary to Section 408, the Department will retain possession of the material obtained from the milling operations. Deliver this material to the State Maintenance facility in <u>Grant</u> County.

**NOTICE TO CONTRACTOR:** The Department considers transfer of millings to the state maintenance facility to be a part of the construction project.

#### **SPECIAL NOTE FOR BASE FAILURE REPAIR (US 25)**

Repair locations listed on the summary are approximate only. The Engineer will determine actual repair locations and dimensions at the time of construction. Prior to overall milling and/or leveling and wedging, excavate the designated base failure areas to a depth  $\underline{6}$  inches below the existing asphalt pavement surface level. Dispose of the excavated materials at waste sites off the Right-of-Way obtained by the Contractor at no additional cost to the Department. See Special Note for Waste and Borrow.

Backfill the excavated areas with Class 2 Asphalt Base 1.00D PG64-22. Compact the asphalt base to the compaction required in Section 403.03.10. Seal the asphalt base with leveling and wedging. Perform all base failure repairs in such a manner that removal and replacement are completed on the same day. Do this work as one of the Contractor's first operations in order to allow further compaction by traffic. Do not mill or place new asphalt surface over repaired base failure areas until a minimum of 7 calendar days have elapsed after placement of the asphalt base. After a minimum of 7 calendar days and when the Engineer determines the base failure repair areas have sufficiently stabilized, begin milling and/or resurfacing operations. Prior to milling and/or constructing the new asphalt surface, level and wedge any settlement of the repair areas.

The bidder must draw conclusions as to the conditions encountered. The Department does not give any guarantee as to the accuracy of the data and will not consider any claim for additional compensation if the materials encountered that are not in accord with the classification shown.

Accept payment at the Contract unit prices per square yard for Base Failure repair and per ton for Leveling and Wedging as full compensation for all labor, materials, equipment, and incidentals for removing pavement and disposing of the materials, furnishing and placing asphalt base, leveling and wedging, and all other items necessary to complete the work according to these notes to the satisfaction of the Engineer.

#### SPECIAL NOTE FOR TYPICAL SECTION DIMENSIONS

Consider the dimensions shown on the typical sections for pavement and shoulder widths and thickness' to be nominal or typical dimensions. The Engineer may direct or approve varying the actual dimensions to be constructed to fit existing conditions. Do not widen existing pavement or shoulders unless specified elsewhere in this proposal or directed by the engineer.

1-3725 Typical Section Dimensions 01/02/2012

## TRAFFIC CONTROL PLAN

### TRAFFIC CONTROL GENERAL

Except as provided herein, maintain and control traffic in accordance with the Standard and Supplemental Specifications and the Standard and Sepia Drawings, current editions. Except for the roadway and traffic control bid items listed, all items of work necessary to maintain and control traffic will be paid at the lump sum bid price to "Maintain and Control Traffic".

Contrary to Section 106.01, furnish new, or used in like new condition, traffic control devices at the beginning of the work and maintain in like new condition until completion of the work.

#### **PROJECT PHASING & CONSTRUCTION PROCEDURES**

The Engineer may specify days and hours when lane closures will not be allowed.

Maintain alternating one way traffic during construction. Provide a minimum clear lane width of 11 feet for KY 3025, US 25, and US 25X; however, provide for passage of vehicles of up to 16 feet in width. If traffic should be stopped due to construction operations, and a school bus on an official run arrives on the scene, make provisions for the passage of the bus as quickly as possible.

#### LANE CLOSURES

Do not leave lane closures in place during non-working hours.

#### SIGNS

Sign posts and splices shall be compliant with NCHRP 350 or MASH. Manufacturer's documentation validating this compliance shall be provided to the Engineer prior to installation. Signs, including any splices, shall be installed according to manufacturer's specifications and installation recommendations. Contrary to section 112.04.02, only long-term signs (signs intended to be continuously in place for more than 3 days) will be measured for payment. Short-term signs (signs intended to be left in place for 3 days or less) will not be measured for payment but will be incidental to Maintain and Control Traffic.

#### CHANGEABLE MESSAGE SIGNS

If deemed necessary by the Engineer, the Department will furnish, operate, and maintain Changeable Message Signs.

#### **TEMPORARY ENTRANCES**

The Engineer will not require the Contractor to provide continuous access to farms, single family, duplex, or triplex residential properties during working hours; however, provide reasonable egress

Traffic Control Plan Page 2 of 3

and ingress to each such property when actual operations are not in progress at that location. Limit the time during which a farm or residential entrance is blocked to the minimum length of time required for actual operations, not extended for the Contractor's convenience, and in no case exceeding six (6) hours. Notify all residents twenty-four hours in advance of any driveway or entrance closings and make any accommodations necessary to meet the access needs of disabled residents.

Except as allowed by the Phasing as specified above, maintain direct access to all side streets and roads, schools, churches, commercial properties and apartments or apartment complexes of four or more units at all times.

The Department will measure asphalt materials required to construct and maintain any temporary entrances which may be necessary to provide temporary access; however, the Department will not measure aggregates, excavation, and/or embankment, but shall be incidental to Maintain and Control Traffic. The Engineer will determine the type of surfacing material, asphalt or aggregate, to be used at each entrance.

## TRAFFIC SIGNAL LOOPS

Install traffic signal loops according to the Special Notes for Traffic Signal Loop Replacement. Coordinate the placement of the loops with the Engineer.

#### THERMOPLASTIC INTERSECTION MARKINGS

Consider the locations listed on the summary as approximate only. Prior to milling and/or resurfacing, locate and document the locations of the existing markings. After resurfacing, replace the markings at their approximate existing locations or as directed by Engineer. Place markings not existing prior to resurfacing as directed by the Engineer.

#### BARRICADES

The Department will not measure barricades used in lieu of barrels and cones for channelization or delineation, but shall be incidental to Maintain and Control Traffic according to Section 112.04.01.

The Department will measure barricades used to protect pavement removal areas in individual units Each. The Department will measure for payment the maximum number of barricades in concurrent use at the same time on a single day on all sections of the contract. The Department will measure individual barricades only once for payment, regardless of how many times they are set, reset, removed, and relocated during the duration of the project. The Department will not measure replacements for damaged barricades the Engineer directs to be replaced due to poor condition or reflectivity. Retain possession of the Barricades upon completion of construction.

Traffic Control Plan Page 3 of 3

# **PAVEMENT MARKINGS**

If there is to be a deviation from the existing striping plan, the Engineer will furnish the Contractor a striping plan prior to placement of the final surface course.

Install Temporary Striping according to Section 112 with the following exception:

If the Contractor's operations or phasing requires temporary markings that must subsequently be removed from the final surface course, use an approved removable lane tape; however, the Department will not measure removable lane tape for separate payment, but will measure and pay for removable lane tape as temporary striping.

# PAVEMENT EDGE DROP-OFFS

Do not allow a pavement edge between opposing directions of traffic or lanes that traffic is expected to cross in a lane change situation with an elevation difference greater than 1½". Place Warning signs (MUTCD W8-11 or W8-9A) in advance of and at 1500' intervals throughout the drop-off area. Dual post the signs on both sides of the traveled way. Wedge all transverse transitions between resurfaced and unresurfaced areas which traffic may cross with asphalt mixture for leveling and wedging. Remove the wedges prior to placement of the final surface course.


Protect pavement edges that traffic is not expected to cross, except accidentally, as follows:

Less than 2" - No protection required.

2" to 4" - Place plastic drums, vertical panels, or barricades every 50 feet. During daylight working hours only, the Engineer will allow the Contractor to use cones in lieu of plastic drums, panels, and barricades. Wedge the drop-off with DGA or asphalt mixture for leveling and wedging with a 1:1 or flatter slope in daylight hours, or 3:1 or flatter slope during nighttime hours, when work is not active in the drop-off area.

Greater than 4" - Protect drop-offs greater than 4 inches within 10 feet of traffic by placing drums, vertical panels, or barricades every 25 feet. The Engineer will not allow the use of cones in lieu of drums, vertical panels, or barricades for drop-offs greater than 4". Place Type III Barricades directly in front of the drop-off facing on coming traffic in both directions of travel. Provide warning signs as shown on the Standard Drawings or as directed by the Engineer

Pedestrians & Bicycles - Protect pedestrian and bicycle traffic as directed by the engineer.



## SPECIAL NOTE FOR TRAFFIC SIGNAL LOOP DETECTORS (US 25X)

**1.0 DESCRIPTION.** Be advised that there are existing traffic signal loop detectors within the construction limits of this project. Except as specified herein, perform traffic signal loop replacement in accordance with the Department's Standard/Supplemental Specifications, Special Provisions, Special Notes, and Standard/Sepia Drawings, current editions and as directed by the Engineer. Article references are to the Standard Specifications. Furnish all materials, labor, equipment, and incidentals for replacement of traffic signal loop installation(s) and all other work specified as part of this contract.

**1.1 Pre-bid Requirements.** Conform to Subsection 723.03.17

**2.0 MATERIALS.** Except as specified herein, furnish materials in accordance with Subsection 732.02 and Section 835. Provide for materials to be sampled and tested in accordance with the Department's Sampling Manual. Make materials available for sampling a sufficient time in advance of the use of the materials to allow for the necessary time for testing, unless otherwise specified in this Special Note.

2.1 Maintain and Control Traffic. See Traffic Control Plan.

**2.2** Sand. Furnish natural sand meeting the requirements of Subsection 804.04.01.

**2.3** Seeding. Furnish Seed Mix Type I.

**2.4** Loop Saw Slot and Fill. Furnish loop sealant, backer rod, and non-shrink grout according to the Saw Slot Detail.

**2.5** Junction Boxes. Furnish junction box type B, #57 aggregate, and geotextile filter type IV according to junction box detail.

**2.6** Cable No. 14/1 Pair (Lead-in). Furnish cable that is specified in Section 835. Cable shall be ran splice free. This shall include splice kits to connect to the loop wire.

**2.7** Conduit. Furnish and install appropriate conduit from transitions to the roadway, junction boxes and poles. See details below.

**3.0 CONSTRUCTION.** Except as specified herein, install and test Traffic Signal Loop Detectors in accordance with Section 723 and the drawings.

**3.1 Testing.** Conform to Subsection 723.03.17 (A)

**3.2** Coordination. Conform to Subsection723.03.17 (B)

**3.3 Connection.** Conform to Subsection 723.03.17 (C)

3.4 Maintain and Control Traffic. See Traffic Control Plan.

**3.5 Milling.** Conform to Subsection 723.03.17 (F)

**3.6 Loop Saw Slot and Fill.** Conform to Subsection 723.03.13 (A).

Traffic Signal Loop Detectors Page 2 of 8

- **3.7** Backfilling and Disturbed Areas. Conform to Subsection 723.03.11.
- **3.8 Removal.** Conform to Subsection 723.03.16.
- 3.9 Property/Roadway Damage. Conform to Subsection 723.03.17 (J).

3.10 Right-of-Way Limits. Conform to Subsection 723.03.17 (K).

**3.11 Utility Clearance.** Conform to Subsection 716.03.01.

**3.12 Control.** Obtain the Engineer's approval of all designs required to be furnished by the Contractor prior to incorporation into the work. The Department reserves the right to permit other contractors, state forces, public utility companies, and others to do work during the construction within the limits of, or adjacent to, the project. Conduct operations and cooperate with such other parties so that interference with each other's work will be reduced to a minimum. The Contractor agrees to make no claims against the Department for additional compensation due to delays or other conditions created by the operations of such other parties. Should a difference of opinion arise as to the rights of the Contractor and others working within the limits of, or adjacent to, the project, the Engineer will decide as to the respective rights of the various parties involved in order to ensure the completion of the work in general harmony and in a satisfactory manner, and the Engineer's decision shall be final and binding upon the Contractor.

**3.13 Bore and Jack**. Conform to Subsection 723.03.06 (I).

**3.14 Open Cut Roadway.** Conform to Subsection 723.03.06 (I).

**4.0 MEASUREMENT.** See Subsection 723.04 for bid item notes. Additional bid items include the following:

**4.1** Loop Test. The Department will measure the quantity as each individual unit loop tested. The Department will not measure disconnection, reconnection, traffic control, re-splicing per specifications, before and after testing per note above, and any associated hardware for payment and will consider them incidental to this item of work.

**5.0 PAYMENT**. The Department will make payment for the completed and accepted quantities of listed items according to Subsection 723.05 in addition to the following:

Code	Pay Item	<u>Pay Unit</u>
Conduit 1"	4792	Linear Foot
PVC Conduit – 1 ¼ inch – sch 80	24900EC	Linear Foot
PVC Conduit – 2 inch – sch 80	24901EC	Linear Foot
Conduit 2"	4795	Linear Foot
Electrical Junction Box type B	4811	Each
Loop Test	24963ED	Each
Trenching and Backfilling	4820	Linear Foot
Loop Wire	4830	Linear Foot

Traffic Signal Loop Detectors Page 3 of 8

Cable-No. 14/1 Pair	4850	Linear Foot <sup>1</sup>
Loop Saw Slot and Fill	4895	Linear Foot <sup>1</sup>
Bore and Jack Conduit	21543EN	Linear Foot <sup>3</sup>
Open Cut Roadway	4821	Linear Foot <sup>3</sup>


The Department will consider payment as full compensation for all work required under these notes and the Standard Specifications.

Contrary to section 723:

SUBSECTION: 03.13 Loop Installation.


REVISION: Replace first sentence note with the following:

twist unshielded loop wire (imsa 51-7) with 3 to 5 turns from the start of homerun to the inside conduit, junction box, cabinet, or pole. Twist unshielded loop wires (imsa 51-7) with 3 to 5 turns per foot from the start of the homerun to the junction box, cabinet, or pole. Slot can be widen to .5" to .625" to help with the installation of the twisted wire.




TEST/PIPE PLUG(FOR SPARE CONDUITS) AND GROUNDING DETAIL

## Traffic Signal Loop Detectors Page 4 of 8




#### Traffic Signal Loop Detectors Page 5 of 8




6'X30' QUADRAPOLE LOOP


## Traffic Signal Loop Detectors Page 6 of 8




Traffic Signal Loop Detectors Page 7 of 8



Traffic Signal Loop Detectors Page 8 of 8



Revised: August 10, 2021



# MATERIAL SUMMARY

#### CONTRACT ID: 222096

041GR22P005 - FD05

MP04100252201

DIXIE HIGHWAY (US 25) BEGINNING AT RIDGELEA DRIVE/KY 1560 EXTENDING NORTH TO THE PAVEMENT JOINT 0.114 MILES SOUTH OF HOGAN'S PARKWAY. ASPHALT RESURFACING, A DISTANCE OF 1.32 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0060	00001	DGA BASE	205.00	TON
0065	00190	LEVELING & WEDGING PG64-22	100.00	TON
0070	00356	ASPHALT MATERIAL FOR TACK	12.00	TON
0075	00388	CL3 ASPH SURF 0.38B PG64-22	1,820.00	TON
0080	02562	TEMPORARY SIGNS	250.00	SQFT
0085	02650	MAINTAIN & CONTROL TRAFFIC - (US 25)	1.00	LS
0090	02676	MOBILIZATION FOR MILL & TEXT - (US 25)	1.00	LS
0095	02677	ASPHALT PAVE MILLING & TEXTURING	1,820.00	TON
0100	03240	BASE FAILURE REPAIR	300.00	SQYD
0105	06510	PAVE STRIPING-TEMP PAINT-4 IN	24,200.00	LF
0110	06515	PAVE STRIPING-PERM PAINT-6 IN	24,200.00	LF
0115	06568	PAVE MARKING-THERMO STOP BAR-24IN	38.00	LF
0120	06574	PAVE MARKING-THERMO CURV ARROW	7.00	EACH
0125	02569	DEMOBILIZATION	1.00	LS

# MATERIAL SUMMARY

#### CONTRACT ID: 222096

041GR22P005 - FD05

MP041025X2201

DIXIE HIGHWAY (US 25X) BEGINNING AT US 25 EXTENDING NORTH TO US 25. ASPHALT RESURFACING, A DISTANCE OF 2.23 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0130	00001	DGA BASE	230.00	TON
0135	00190	LEVELING & WEDGING PG64-22	102.00	TON
0140	00356	ASPHALT MATERIAL FOR TACK	24.00	TON
0145	00307	CL2 ASPH SURF 0.38B PG64-22	3,735.00	TON
0150	02562	TEMPORARY SIGNS	390.00	SQFT
0155	02650	MAINTAIN & CONTROL TRAFFIC - (US 25X)	1.00	LS
0160	02676	MOBILIZATION FOR MILL & TEXT - (US 25X)	1.00	LS
0165	02677	ASPHALT PAVE MILLING & TEXTURING	3,735.00	TON
0170	04792	CONDUIT-1 IN	60.00	LF
0175	24900EC	PVC CONDUIT-1 1/4 IN-SCHEDULE 80	80.00	LF
0180	04811	ELECTRICAL JUNCTION BOX TYPE B	3.00	EACH
0185	04820	TRENCHING AND BACKFILLING	100.00	LF
0190	04830	LOOP WIRE	1,200.00	LF
0195	04850	CABLE-NO. 14/1 PAIR	1,000.00	LF
0200	04895	LOOP SAW SLOT AND FILL	550.00	LF
0205	06510	PAVE STRIPING-TEMP PAINT-4 IN	51,350.00	LF
0210	06515	PAVE STRIPING-PERM PAINT-6 IN	51,350.00	LF
0215	06565	PAVE MARKING-THERMO X-WALK-6 IN	310.00	LF
0220	06566	PAVE MARKING-THERMO X-WALK-12 IN	175.00	LF
0225	06568	PAVE MARKING-THERMO STOP BAR-24IN	112.00	LF
0230	06573	PAVE MARKING-THERMO STR ARROW	2.00	EACH
0235	06574	PAVE MARKING-THERMO CURV ARROW	15.00	EACH
0240	06600	REMOVE PAVEMENT MARKER TYPE V	145.00	EACH
0245	10020NS	FUEL ADJUSTMENT	4,813.00	DOLL
0250	10030NS	ASPHALT ADJUSTMENT	12,088.00	DOLL
0255	24955ED	REMOVE SIGNAL EQUIPMENT	3.00	EACH
0260	24963ED	LOOP TEST	4.00	EACH
0265	02569	DEMOBILIZATION	1.00	LS

# MATERIAL SUMMARY

#### CONTRACT ID: 222096

041GR22P005 - FD05

MP04130252201

ARNIE RISEN BLVD. (KY 3025) BEGIN AT KY 1560 EXTENDING NORTH TO US 25X ASPHALT RESURFACING, A DISTANCE OF .68 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0005	00190	LEVELING & WEDGING PG64-22	24.00	TON
0010	00301	CL2 ASPH SURF 0.38D PG64-22	675.00	TON
0015	00356	ASPHALT MATERIAL FOR TACK	5.00	TON
0020	02562	TEMPORARY SIGNS	200.00	SQFT
0025	02650	MAINTAIN & CONTROL TRAFFIC - (KY 3025)	1.00	LS
0030	02676	MOBILIZATION FOR MILL & TEXT - (KY 3025)	1.00	LS
0035	02677	ASPHALT PAVE MILLING & TEXTURING	675.00	TON
0040	06510	PAVE STRIPING-TEMP PAINT-4 IN	14,590.00	LF
0045	06515	PAVE STRIPING-PERM PAINT-6 IN	14,590.00	LF
0050	06568	PAVE MARKING-THERMO STOP BAR-24IN	24.00	LF
0055	02569	DEMOBILIZATION	1.00	LS

NOTES										
CATRAXX 6 INCH LF										
"ONLY" "STOP" EA EA										
"ONLY" EA										
s COMB EA										
RROWS STR EA										
ARROWS CURVE STR EA EA										
STP BARS 24 INCH LF	24									24
X-WALKS 6 INCH LF										
INTERSECTION										
MPT.	1.072									TOTAL

# Base Failure Repair Summary FD05 041 0025 012-014

		Total	300
Milepoint	Length	Width	SQYD
12.690	75	9	75
12.820	50	9	50
12.830	50	9	50
13.75	50	9	50
13.84	75	9	75


		-		1	1				 		 	 	_	1
CATRAXX 6 INCH	LF													-
"STOP"	EA													-
"ONLY"	EA													-
COMB	EA													-
ARROWS STR	EA													-
	EA EA EA		۲	£	£		2	2						~
STP BARS 24 INCH	LF	13				25								38
X-WALKS 6 INCH	LF													c
INTERSECTION														
MPT.		12.68	12.83	13.41	13.43	13.45	13.47	13.48						ΤΟΤΔΙ

Grant County THERMOPLASTIC INTERSECTION PAVEMENT MARKINGS SUMMARY FD05 041 025X 000-003

NOTES																						
CATRAXX 6 INCH LF																						
"STOP" EA																						
"ONLY" EA																						
COMB																						
ARROWS STR EA														٢	٢							2
CURVE EA			2	7	7	7	٢			£	٢	٢	٢	٢	٢							15
STP BARS 24 INCH LF	12	12						54	12							28			12	12		112
X-WALK 12" LF																	175					175
X-WALKS 6 INCH LF																		210			100	310
INTERSECTION																					GRANT COUNTY DRUG	
INTE																					GRANT	
MPT.	0.239	0.343	0.813	0.915	0.999	1.16	1.58	1.58	1.6	1.628	1.649	1.708	1.738	1.990	2.010	2.020	2.030	2.040	2.238	2.256		TOTAL

NOTES	1 Stopbar Loop	1 left turn and 1 side street loop	1 left turn loop							
Remove Signal Equipment Ea	1	1	1							с
Loop Test EA	1	2	1							4
JUNCTION TYPE B EA	1	2	0							с
Trenching And Backfilling LF	35	50	15							100
CABLE NO. 14 LF	200	400	400							1000
CONDUIT 1 1/4 INCH PVC LF	30	50	0							80
Conduit 1" Lf	20	25	15							60
LOOP WIRE LF	300	600	300							1200
SAW, SLOT AND FILL LF	150	250	150							550
INTERSECTION	N Main Street	Brentwood Drive	Broadway Street							
MPT.	0	1.55	2.1							TOTAL


NOTES:




KY 3025 Typ 1.xls

 $\overline{}$ 


FD05-041-3025-001-002 TYP SECT2.xls





**Grant County** 



\*Where Existing Site Conditions Permit










#### CONSTRUCTION DETAIL FOR BRIDGE WITHIN LIMITS OF PAVING PROJECT (US 25X) FD05 041 025X 000-003



W = bridge width curb to curbT = thickness of existing bituminous overlayL = length of bridge $L_1 \& L_2$  = length of approach pavement to be removed $P_R$  = thickness to be removed and replaced on bridge $P_R$  = thickness to be removed and replaced on pavementNote:  $L_1 \& L_2$  lengths shall be determined by using a transition rate of 100 ft / inch of thickness

BRIDGE NO	MP	W (ft)	T (in)	L <sub>1</sub> (ft)	L <sub>2</sub> (ft)	T <sub>R</sub> (in)	L (ft)	P <sub>R</sub> (in)
B00045N	0.060	28.00	0.00	0.00	0.00	0.00	365.00	1.25

# PART II

## SPECIFICATIONS AND STANDARD DRAWINGS

### **SPECIFICATIONS REFERENCE**

Any reference in the plans or proposal to previous editions of the *Standard Specifications* for Road and Bridge Construction and Standard Drawings are superseded by Standard Specifications for Road and Bridge Construction, Edition of 2019 and Standard Drawings, Edition of 2020.

## SUPPLEMENTAL SPECIFICATIONS

The contractor shall use the Supplemental Specifications that are effective at the time of letting. The Supplemental Specifications can be found at the following link:

http://transportation.ky.gov/Construction/Pages/Kentucky-Standard-Specifications.aspx

## 2020 KENTUCKY STANDARD DRAWINGS

CURVE WIDENING AND SUPERELEVATION TRANSITIONS	RGS-001-07
SUPERELEVATION FOR MULTILANE PAVEMENT	
MISCELLANEOUS STANDARDS	RGX-001-06
APPROACHES, ENTRANCES, AND MAIL BOX TURNOUT	RPM-110-07
LANE CLOSURE TWO-LANE HIGHWAY	TTC-100-04
SHOULDER CLOSURE	TTC-135-02
PAVEMENT CONDITION WARNING SIGNS	TTD-125-02
MOBILE OPERATION FOR PAINT STRIPING CASE I	TTS-100-02
MOBILE OPERATION FOR PAINT STRIPING CASE II	TTS-105-02

# PART III

# EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

#### TRANSPORTATION CABINET DEPARTMENT OF HIGHWAYS

#### LABOR AND WAGE REQUIREMENTS APPLICABLE TO OTHER THAN FEDERAL-AID SYSTEM PROJECTS

#### I. Application

II. Nondiscrimination of Employees (KRS 344)

#### I. APPLICATION

1. These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to all work performed on the contract by piecework, station work or by subcontract. The contractor's organization shall be construed to include only workmen employed and paid directly by the contractor and equipment owned or rented by him, with or without operators.

2. The contractor shall insert in each of his subcontracts all of the stipulations contained in these Required Provisions and such other stipulations as may be required.

3. A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

#### II. NONDISCRIMINATION OF EMPLOYEES

#### AN ACT OF THE KENTUCKY GENERAL ASSEMBLY TO PREVENT DISCRIMINATION IN EMPLOYMENT KRS CHAPTER 344 EFFECTIVE JUNE 16, 1972

The contract on this project, in accordance with KRS Chapter 344, provides that during the performance of this contract, the contractor agrees as follows:

1. The contractor shall not fail or refuse to hire, or shall not discharge any individual, or otherwise discriminate against an individual with respect to his compensation, terms, conditions, or privileges of employment, because of such individual's race, color, religion, national origin, sex, disability or age (forty and above); or limit, segregate, or classify his employees in any way which would deprive or tend to deprive an individual of employment opportunities or otherwise adversely affect his status as an employee, because of such individual's race, color, religion, national origin, sex, disability or age forty (40) and over. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.

2. The contractor shall not print or publish or cause to be printed or published a notice or advertisement relating to employment by such an employer or membership in or any classification or referral for employment by the employment agency, indicating any preference, limitation, specification, or discrimination, based on race, color, religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, except that such a notice or advertisement may indicate a preference, limitation, or specification based on religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, when religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, is a bona fide occupational qualification for employment. 3. If the contractor is in control of apprenticeship or other training or retraining, including on-the-job training programs, he shall not discriminate against an individual because of his race, color, religion, national origin, sex, disability or age forty (40) and over, in admission to, or employment in any program established to provide apprenticeship or other training.

4. The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representative of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment. The contractor will take such action with respect to any subcontract or purchase order as the administrating agency may direct as a means of enforcing such provisions, including sanctions for non-compliance.

Revised: January 25, 2017

### **EXECUTIVE BRANCH CODE OF ETHICS**

In the 1992 regular legislative session, the General Assembly passed and Governor Brereton Jones signed Senate Bill 63 (codified as KRS 11A), the Executive Branch Code of Ethics, which states, in part:

KRS 11A.040 (7) provides:

No present or former public servant shall, within six (6) months following termination of his office or employment, accept employment, compensation, or other economic benefit from any person or business that contracts or does business with, or is regulated by, the state in matters in which he was directly involved during the last thirty-six (36) months of his tenure. This provision shall not prohibit an individual from returning to the same business, firm, occupation, or profession in which he was involved prior to taking office or beginning his term of employment, or for which he received, prior to his state employment, a professional degree or license, provided that, for a period of six (6) months, he personally refrains from working on any matter in which he was directly involved during the last thirtysix (36) months of his tenure in state government. This subsection shall not prohibit the performance of ministerial functions, including but not limited to filing tax returns, filing applications for permits or licenses, or filing incorporation papers, nor shall it prohibit the former officer or public servant from receiving public funds disbursed through entitlement programs.

KRS 11A.040 (9) states:

A former public servant shall not represent a person or business before a state agency in a matter in which the former public servant was directly involved during the last thirty-six (36) months of his tenure, for a period of one (1) year after the latter of:

- a) The date of leaving office or termination of employment; or
- b) The date the term of office expires to which the public servant was elected.

This law is intended to promote public confidence in the integrity of state government and to declare as public policy the idea that state employees should view their work as a public trust and not as a way to obtain private benefits.

If you have worked for the executive branch of state government within the past six months, you may be subject to the law's prohibitions. The law's applicability may be different if you hold elected office or are contemplating representation of another before a state agency.

Also, if you are affiliated with a firm which does business with the state and which employs former state executive-branch employees, you should be aware that the law may apply to them.

In case of doubt, the law permits you to request an advisory opinion from the Executive Branch Ethics Commission, 3 Fountain Place, Frankfort, Kentucky 40601; telephone (502) 564-7954.

Revised: January 27, 2017

### Kentucky Equal Employment Opportunity Act of 1978


The requirements of the Kentucky Equal Employment Opportunity Act of 1978 (KRS 45.560-45.640) shall apply to this Contract. The apparent low Bidder will be required to submit EEO forms to the Division of Construction Procurement, which will then forward to the Finance and Administration Cabinet for review and approval. No award will become effective until all forms are submitted and EEO/CC has certified compliance. The required EEO forms are as follows:

- EEO-1: Employer Information Report
- Affidavit of Intent to Comply
- Employee Data Sheet
- Subcontractor Report

These forms are available on the Finance and Administration's web page under *Vendor Information, Standard Attachments and General Terms* at the following address: <u>https://www.eProcurement.ky.gov</u>.

Bidders currently certified as being in compliance by the Finance and Administration Cabinet may submit a copy of their approval letter in lieu of the referenced EEO forms.

For questions or assistance please contact the Finance and Administration Cabinet by email at **finance.contractcompliance@ky.gov** or by phone at 502-564-2874.



U.S. Department of Labor | Wage and Hour Division

# PART IV

# **INSURANCE**

Refer to Kentucky Standard Specifications for Road and Bridge Construction, current edition

# PART V

# **BID ITEMS**

222096

### **PROPOSAL BID ITEMS**

Page 1 of 1

Report Date 4/22/22

## Section: 0001 - PAVING

LINE	BID CODE	ALT DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0010	00001	DGA BASE	435.00	TON		\$	
0020	00190	LEVELING & WEDGING PG64-22	226.00	TON		\$	
0030	00301	CL2 ASPH SURF 0.38D PG64-22	675.00	TON		\$	
0040	00307	CL2 ASPH SURF 0.38B PG64-22	3,735.00	TON		\$	
0050	00356	ASPHALT MATERIAL FOR TACK	41.00	TON		\$	
0060	00388	CL3 ASPH SURF 0.38B PG64-22	1,820.00	TON		\$	
0070	02562	TEMPORARY SIGNS	840.00	SQFT		\$	
0080	02650	MAINTAIN & CONTROL TRAFFIC (KY 3025)	1.00	LS		\$	
0090	02650	MAINTAIN & CONTROL TRAFFIC (US 25)	1.00	LS		\$	
0100	02650	MAINTAIN & CONTROL TRAFFIC (US 25X)	1.00	LS		\$	
0110	02676	MOBILIZATION FOR MILL & TEXT (KY 3025)	1.00	LS		\$	
0120	02676	MOBILIZATION FOR MILL & TEXT (US 25)	1.00	LS		\$	
0130	02676	MOBILIZATION FOR MILL & TEXT (US 25X)	1.00	LS		\$	
0140	02677	<b>ASPHALT PAVE MILLING &amp; TEXTURING</b>	6,230.00	TON		\$	
0150	03240	BASE FAILURE REPAIR	300.00	SQYD		\$	
0160	04792	CONDUIT-1 IN	60.00	LF		\$	
0170	04811	<b>ELECTRICAL JUNCTION BOX TYPE B</b>	3.00	EACH		\$	
0180	04820	TRENCHING AND BACKFILLING	100.00	LF		\$	
0190	04830	LOOP WIRE	1,200.00	LF		\$	
0200	04850	CABLE-NO. 14/1 PAIR	1,000.00	LF		\$	
)210	04895	LOOP SAW SLOT AND FILL	550.00	LF		\$	
)220	06510	PAVE STRIPING-TEMP PAINT-4 IN	90,140.00	LF		\$	
)230	06515	PAVE STRIPING-PERM PAINT-6 IN	90,140.00	LF		\$	
)240	06565	PAVE MARKING-THERMO X-WALK-6 IN	310.00	LF		\$	
0250	06566	PAVE MARKING-THERMO X-WALK-12 IN	175.00	LF		\$	
0260	06568	PAVE MARKING-THERMO STOP BAR-24IN	174.00	LF		\$	
0270	06573	PAVE MARKING-THERMO STR ARROW	2.00	EACH		\$	
0280	06574	PAVE MARKING-THERMO CURV ARROW	22.00	EACH		\$	
)290	06600	<b>REMOVE PAVEMENT MARKER TYPE V</b>	145.00	EACH		\$	
0300	10020NS	FUEL ADJUSTMENT	4,813.00	DOLL	\$1.00	\$	\$4,813.00
0310	10030NS	ASPHALT ADJUSTMENT	12,088.00	DOLL	\$1.00	\$	\$12,088.00
0320	24900EC	PVC CONDUIT-1 1/4 IN-SCHEDULE 80	80.00	LF		\$	
)330	24955ED	REMOVE SIGNAL EQUIPMENT	3.00	EACH		\$	
)340	24963ED	LOOP TEST	4.00	EACH		\$	

### Section: 0002 - DEMOBILIZATION

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0350	02569		DEMOBILIZATION	1.00	LS		\$	