



CALL NO. 433

CONTRACT ID. 193136

WHITLEY COUNTY

FED/STATE PROJECT NUMBER 118GR19R039-CB06

DESCRIPTION VARIOUS ROUTES IN WHITLEY COUNTY

WORK TYPE ASPHALT RESURFACING

PRIMARY COMPLETION DATE 11/30/2019

LETTING DATE: June 21,2019

Sealed Bids will be received electronically through the Bid Express bidding service until 10:00 AM EASTERN DAYLIGHT TIME June 21,2019. Bids will be publicly announced at 10:00 AM EASTERN DAYLIGHT TIME.

NO PLANS ASSOCIATED WITH THIS PROJECT.

REQUIRED BID PROPOSAL GUARANTY: Not less than 5% of the total bid.

TABLE OF CONTENTS

PART I	SCOPE OF WORK
	<ul style="list-style-type: none">• PROJECT(S), COMPLETION DATE(S), & LIQUIDATED DAMAGES• CONTRACT NOTES• STATE CONTRACT NOTES• ASPHALT MIXTURE• INCIDENTAL SURFACING• FUEL AND ASPHALT PAY ADJUSTMENT• COMPACTION OPTION B• SPECIAL NOTE(S) APPLICABLE TO PROJECT• WASTE AND BORROW SITES• ASPHALT MIX PAVEMENT WEDGE MONOLITHIC OPERATION• ASPHALT MILLING AND TEXTURING• BASE FAILURE REPAIR• TYPICAL SECTION DIMENSIONS• TRAFFIC CONTROL PLAN 2 LANE• DURABLE PAVEMENT EDGE DETAILS• SKETCH MAP(S)• MATERIAL SUMMARY• SUMMARY SHEET(S)• TYPICAL SECTION(S)• BRIDGE DETAIL FOR PAVING PROJECT
PART II	SPECIFICATIONS AND STANDARD DRAWINGS
	<ul style="list-style-type: none">• SPECIFICATIONS REFERENCE• SUPPLEMENTAL SPECIFICATION• STANDARD DRAWINGS THAT APPLY
PART III	EMPLOYMENT, WAGE AND RECORD REQUIREMENTS
	<ul style="list-style-type: none">• LABOR AND WAGE REQUIREMENTS• EXECUTIVE BRANCH CODE OF ETHICS• KENTUCKY EQUAL EMPLOYMENT OPPORTUNITY ACT OF 1978 LOCALITY / STATE• PROJECT WAGE RATES / STATE
PART IV	INSURANCE
PART V	BID ITEMS

PART I
SCOPE OF WORK

ADMINISTRATIVE DISTRICT - 11

CONTRACT ID - 193136

118GR19R039-CB06

COUNTY - WHITLEY

PCN - 1111805111906

CB06 118 0511 001-006

HIGHWAY 511 (KY 511) (MP 1.859) FROM 0.260 MILES EAST OF OLD SHINER SCHOOL ROAD EXTENDING EAST TO 0.189 MILES WEST OF SPENCER HILL ROAD (MP 5.012), A DISTANCE OF 03.15 MILES.ASPHALT SURFACING ULTRA THIN

GEOGRAPHIC COORDINATES LATITUDE 36:50:55.27 LONGITUDE 84:10:08.12

PCN - 1111809041907

CB06 118 0904 010-012

HIGHWAY 904 EAST (KY 904) (MP 10.827) FROM 0.391 MILES EAST OF PRIVATE ROAD EXTENDING EAST TO 1.374 MILES WEST OF MCKIDDY CEMETERY - COALSTONE ROAD (MP 11.612), A DISTANCE OF 0.79 MILES.ASPHALT PAVEMENT PATCHING

GEOGRAPHIC COORDINATES LATITUDE 36:41:24.73 LONGITUDE 83:59:21.20

PCN - 1111810641904

CB06 118 1064 005-010

WHETSTONE ROAD (KY 1064) (MP 5.624) FROM 0.065 MILES NORTH OF BUNCH CEMETERY ROAD EXTENDING NORTH TO KY 779 (MP 9.305), A DISTANCE OF 03.68 MILES.ASPHALT PAVEMENT PATCHING

GEOGRAPHIC COORDINATES LATITUDE 36:46:42.47 LONGITUDE 84:02:53.95

PCN - 1111815951905

CB06 118 1595 000-003

HIGHWAY 1595 (KY 1595) (MP 0.662) FROM THE BELL COUNTY LINE EXTENDING NORTH TO 0.612 MILES SOUTH OF CALDWELL CEMETERY ROAD (MP 2.587), A DISTANCE OF 01.93 MILES.ASPHALT PAVEMENT PATCHING

GEOGRAPHIC COORDINATES LATITUDE 36:39:06.82 LONGITUDE 83:57:11.24

PCN - 1111829951908

CB06 118 2995 000-001

ELLISON BEND ROAD (KY 2995) (MP 0.000) FROM KY 2996 EXTENDING NORTH TO END OF STATE MAINTENANCE (MP 0.952), A DISTANCE OF 0.95 MILES.ASPHALT RESURFACING

GEOGRAPHIC COORDINATES LATITUDE 36:38:47.32 LONGITUDE 84:07:45.15

PCN - 1111829961902

CB06 118 2996 002-005

WOLF CREEK RIVER ROAD (KY 2996) (MP 2.000) FROM 1.258 MILES NORTH OF ELLISON BEND ROAD EXTENDING NORTH TO KY 628 (MP 4.288), A DISTANCE OF 02.29 MILES.ASPHALT RESURFACING

GEOGRAPHIC COORDINATES LATITUDE 36:39:41.47 LONGITUDE 84:08:30.04

PCN - 1111834211903

CB06 118 3421 000-002

BARTON MILL CUTOFF ROAD (KY 3421) (MP 0.000) FROM KY 727 EXTENDING NORTH TO KY 1259 (MP 1.154), A DISTANCE OF 01.15 MILES.ASPHALT SURFACING ULTRA THIN

GEOGRAPHIC COORDINATES LATITUDE 36:56:09.00 LONGITUDE 84:08:31.00

PCN - 1111834231901

CB06 118 3423 000-005

TYES FERRY ROAD (KY 3423) (MP 0.000) FROM KY 26 EXTENDING EAST TO KY 779 (MP 4.870), A DISTANCE OF 04.87 MILES.ASPHALT PAVEMENT PATCHING

GEOGRAPHIC COORDINATES LATITUDE 36:49:45.63 LONGITUDE 84:05:51.19

COMPLETION DATE(S):

COMPLETED BY 11/30/2019

APPLIES TO ENTIRE CONTRACT

CONTRACT NOTES

PROPOSAL ADDENDA

All addenda to this proposal must be applied when calculating bid and certified in the bid packet submitted to the Kentucky Department of Highways. Failure to use the correct and most recent addenda may result in the bid being rejected.

BID SUBMITTAL

Bidder must use the Department's electronic bidding software. The Bidder must download the bid file located on the Bid Express website (www.bidx.com) to prepare a bid packet for submission to the Department. The bidder must submit electronically using Bid Express.

JOINT VENTURE BIDDING

Joint venture bidding is permissible. All companies in the joint venture must be prequalified in one of the work types in the Qualifications for Bidders for the project. The bidders must get a vendor ID for the joint venture from the Division of Construction Procurement and register the joint venture as a bidder on the project. Also, the joint venture must obtain a digital ID from Bid Express to submit a bid. A joint bid bond of 5% may be submitted for both companies or each company may submit a separate bond of 5%.

UNDERGROUND FACILITY DAMAGE PROTECTION

The contractor shall make every effort to protect underground facilities from damage as prescribed in the Underground Facility Damage Protection Act of 1994, Kentucky Revised Statute KRS 367.4901 to 367.4917. It is the contractor's responsibility to determine and take steps necessary to be in compliance with federal and state damage prevention directives. When prescribed in said directives, the contractor shall submit Excavation Locate Requests to the Kentucky Contact Center (KY811) via web ticket entry. The submission of this request does not relieve the contractor from the responsibility of contacting non-member facility owners, whom shall be contacted through their individual Protection Notification Center. Non-compliance with these directives can result in the enforcement of penalties.

REGISTRATION WITH THE SECRETARY OF STATE BY A FOREIGN ENTITY

Pursuant to KRS 176.085(1)(b), an agency, department, office, or political subdivision of the Commonwealth of Kentucky shall not award a state contract to a person that is a foreign entity required by [KRS 14A.9-010](#) to obtain a certificate of authority to transact business in the Commonwealth ("certificate") from the Secretary of State under [KRS 14A.9-030](#) unless the person produces the certificate within fourteen (14) days of the bid or proposal opening. If the foreign entity is not required to obtain a certificate as provided in [KRS 14A.9-010](#), the foreign entity should identify the applicable exception. Foreign entity is defined within [KRS 14A.1-070](#).

For all foreign entities required to obtain a certificate of authority to transact business in the Commonwealth, if a copy of the certificate is not received by the contracting agency within the time frame identified above, the foreign entity's solicitation response shall be deemed non-responsive or the awarded contract shall be cancelled.

Businesses can register with the Secretary of State at <https://secure.kentucky.gov/sos/ftbr/welcome.aspx>.

SPECIAL NOTE FOR PROJECT QUESTIONS DURING ADVERTISEMENT

Questions about projects during the advertisement should be submitted in writing to the Division of Construction Procurement. This may be done by fax (502) 564-7299 or email to kytc.projectquestions@ky.gov. The Department will attempt to answer all submitted questions. The Department reserves the right not to answer if the question is not pertinent or does not aid in clarifying the project intent.

The deadline for posting answers will be 3:00 pm Eastern Daylight Time, the day preceding the Letting. Questions may be submitted until this deadline with the understanding that the later a question is submitted, the less likely an answer will be able to be provided.

The questions and answers will be posted for each Letting under the heading "Questions & Answers" on the Construction Procurement website (www.transportation.ky.gov/contract). The answers provided shall be considered part of this Special Note and, in case of a discrepancy, will govern over all other bidding documents.

HARDWOOD REMOVAL RESTRICTIONS

The US Department of Agriculture has imposed a quarantine in Kentucky and several surrounding states, to prevent the spread of an invasive insect, the emerald ash borer. Hardwood cut in conjunction with the project may not be removed from the state. Chipping or burning on site is the preferred method of disposal.

INSTRUCTIONS FOR EXCESS MATERIAL SITES AND BORROW SITES

Identification of excess material sites and borrow sites shall be the responsibility of the Contractor. The Contractor shall be responsible for compliance with all applicable state and federal laws and may wish to consult with the US Fish and Wildlife Service to seek protection under Section 10 of the Endangered Species Act for these activities.

ACCESS TO RECORDS

The contractor, as defined in KRS 45A.030 (9) agrees that the contracting agency, the Finance and Administration Cabinet, the Auditor of Public Accounts, and the Legislative Research Commission, or their duly authorized representatives, shall have access to any books, documents, papers, records, or other evidence, which are directly pertinent to this contract for the purpose of financial audit or program review. Records and other prequalification information confidentially

disclosed as part of the bid process shall not be deemed as directly pertinent to the contract and shall be exempt from disclosure as provided in KRS 61.878(1)(c). The contractor also recognizes that any books, documents, papers, records, or other evidence, received during a financial audit or program review shall be subject to the Kentucky Open Records Act, KRS 61.870 to 61.884.

In the event of a dispute between the contractor and the contracting agency, Attorney General, or the Auditor of Public Accounts over documents that are eligible for production and review, the Finance and Administration Cabinet shall review the dispute and issue a determination, in accordance with Secretary's Order 11-004.

April 30, 2018

SPECIAL NOTE FOR RECIPROCAL PREFERENCE

RECIPROCAL PREFERENCE TO BE GIVEN BY PUBLIC AGENCIES TO RESIDENT BIDDERS

By reference, KRS 45A.490 to 45A.494 are incorporated herein and in compliance regarding the bidders residency. Bidders who want to claim resident bidder status should complete the Affidavit for Claiming Resident Bidder Status along with their bid in the electronic bidding software. Submittal of the Affidavit should be done along the bid in Bid Express.

April 30, 2018

ASPHALT MIXTURE

Unless otherwise noted, the Department estimates the rate of application for all asphalt mixtures to be 110 lbs/sy per inch of depth.

INCIDENTAL SURFACING

The Department has included in the quantities of asphalt mixtures established in the proposal estimated quantities required for resurfacing or surfacing mailbox turnouts, farm field entrances, residential and commercial entrances, curve widening, ramp gores and tapers, and road and street approaches, as applicable. Pave these areas to the limits as shown on Standard Drawing RPM-110-06 or as directed by the Engineer. In the event signal detectors are present in the intersecting streets or roads, pave the crossroads to the right of way limit or back of the signal detector, whichever is the farthest back of the mainline. Surface or resurface these areas as directed by the Engineer. The Department will not measure placing and compacting for separate payment but shall be incidental to the Contract unit price for the asphalt mixtures.

FUEL AND ASPHALT PAY ADJUSTMENT

The Department has included the Contract items Asphalt Adjustment and Fuel Adjustment for possible future payments at an established Contract unit price of \$1.00. The Department will calculate actual adjustment quantities after work is completed. If existing Contract amount is insufficient to pay all items on the contract with the adjustments, the Department will establish additional monies with a change order.

OPTION B

Be advised that the Department will control and accept compaction of asphalt mixtures furnished on this project under OPTION B in accordance with Sections 402 and 403.

October, 2018

**SPECIAL NOTE FOR POLISH-RESISTANT AGGREGATE IN NO 4 THINLAY
ASPHALT MIXTURES**

(KY 3421 & KY 511)

Contrary to Subsection 403.03.03, provide polish-resistant aggregate in the ASPH SURF NO.4 asphalt mixture conforming to one of the following requirements:

ASPH SURF NO.4A

- 100 percent of total combined aggregate is Class A polish-resistant aggregate.

ASPH SURF NO.4B

- Total combined aggregate is composed of a Class A and Class B polish-resistant aggregate; or
- Minimum of 85 percent Class B polish-resistant aggregate and maximum 15% Class D aggregate of the total combined aggregate.

Contrary to Section 409.03.03 of the *Standards and Specifications*, for a 4.75mm asphalt mixture requiring a Class A or B polish resistant aggregate, the use of recycled/reclaimed materials is prohibited. For 4.75mm asphalt mixtures requiring Class D aggregate, recycled asphalt pavement (RAP) shall not exceed 15% of cold feed percentage, and the use of recycled asphalt shingles (RAS) is prohibited.

SPECIAL PROVISION FOR WASTE AND BORROW SITES

Obtain U.S. Army Corps of Engineer's approval before utilizing a waste or borrow site that involves "Waters of the United States". The Corps of Engineers defines "Waters of the United States" as perennial or intermittent streams, ponds or wetlands. The Corps of Engineers also considers ephemeral streams, typically dry except during rainfall but having a defined drainage channel, to be jurisdictional waters. Direct questions concerning any potential impacts to "Waters of the United States" to the attention of the appropriate District Office for the Corps of Engineers for a determination prior to disturbance. Be responsible for any fees associated with obtaining approval for waste and borrow sites from the U.S. Army Corps of Engineer or other appropriate regulatory agencies.

1-296 Waste & Borrow Sites
01/02/2012

SPECIAL NOTE FOR PAVEMENT WEDGE AND SHOULDER MONOLITHIC OPERATION


1.0 MATERIALS. Provide an Asphalt Surface Mixture conforming to Section 403 of the Standard Specifications, as applicable to the project, for the pavement wedge.

2.0 CONSTRUCTION. Place the specified Asphalt Surface Mixture on shoulders monolithically with the driving lane. Prime the existing shoulder with tack material as the Engineer directs before placing the wedge. Construct according to Section 403.03 of the Standard Specifications.

Equip the paver with a modified screed that extends the full width of the wedge being placed and is tapered to produce a wedge. Obtain the Engineer's approval of the modified screed before placing shoulder wedge monolithically with the driving lane.

The wedge may vary in thickness at the edge of the milled area in the shoulder. If the area to receive the shoulder wedge is milled prior to placement, during rolling operations pinch the outside edge of the new inlay wedge to match the existing shoulder elevation not being resurfaced. Unless required otherwise by the Contract, construct rolled or sawed rumble strips according to Section 403.03.08, as applicable.

The following sketch is primarily for the computation of quantities; however, the wedge will result in a similar cross-section where sufficient width exists. Do not construct a shoulder for placing the wedge unless specified elsewhere in the Contract.



3.0 MEASUREMENT. The Department will measure Asphalt Surface Mixture placed as the pavement wedge according to Section 403.

4.0 PAYMENT. The Department will make payment for the completed and accepted quantities of Asphalt Surface Mixtures on pavement wedges according to Section 403.

**SPECIAL NOTE FOR
ASPHALT MILLING AND TEXTURING**

Begin paving operations within **two weeks** of commencement of the milling operation. Continue paving operations continuously until completed. If paving operations are not begun within this time period, the Department will assess liquidated damages at the rate prescribed by Section 108.09 until such time as paving operations are begun.

Take possession of the millings and recycle the millings or dispose of the millings off the Right-of-Way at sites obtained by the Contractor at no additional cost to the Department.

1-3505 2 weeks Contractor keeps millings
01/2/2012

SPECIAL NOTE FOR BASE FAILURE REPAIR

Repair locations listed on the summary are approximate only. The Engineer will determine actual repair locations and dimensions at the time of construction. Prior to overall milling and/or leveling and wedging, excavate the designated base failure areas by milling to a depth of 2-8 inches (see road specific summary sheets for depth per road) below the existing asphalt pavement surface level. Dispose of the excavated materials at waste sites off the Right-of-Way obtained by the Contractor at no additional cost to the Department. See Special Note for Waste and Borrow.

Backfill the excavated areas with Class 2 Asphalt Base 0.75D PG 64-22. Compact the asphalt base to the compaction required in Section 403.03.10. Seal the asphalt base with leveling and wedging. Perform all base failure repairs in such a manner that removal and replacement are completed on the same day. Do this work as one of the Contractor's first operations in order to allow further compaction by traffic. Do not mill or place new asphalt surface over repaired base failure areas until a minimum of 7 calendar days have elapsed after placement of the asphalt base. After a minimum of 7 calendar days and when the Engineer determines the base failure repair areas have sufficiently stabilized, begin milling and/or resurfacing operations. Prior to milling and/or constructing the new asphalt surface, level and wedge any settlement of the repair areas.

The bidder must draw conclusions as to the conditions encountered. The Department does not give any guarantee as to the accuracy of the data and will not consider any claim for additional compensation if the materials encountered that are not in accord with the classification shown.

Accept payment at the Contract unit prices per ton for Asphalt Milling and Texturing, Asphalt Base, and Leveling and Wedging as full compensation for all labor, materials, equipment, and incidentals for removing pavement and disposing of the materials, furnishing and placing asphalt base, leveling and wedging, and all other items necessary to complete the work according to these notes to the satisfaction of the Engineer.

1-3605 basefailurerepairmillinlaypayton
01/02/2012

SPECIAL NOTE FOR TYPICAL SECTION DIMENSIONS

Consider the dimensions shown on the typical sections for pavement and shoulder widths and thickness' to be nominal or typical dimensions. The Engineer may direct or approve varying the actual dimensions to be constructed to fit existing conditions. Do not widen existing pavement or shoulders unless specified elsewhere in this proposal or directed by the engineer.

1-3725 Typical Section Dimensions
01/02/2012

TRAFFIC CONTROL PLAN

TRAFFIC CONTROL GENERAL

Except as provided herein, maintain and control traffic in accordance with the Standard and Supplemental Specifications and the Standard and Sepia Drawings, current editions. Except for the roadway and traffic control bid items listed, all items of work necessary to maintain and control traffic will be paid at the lump sum bid price to "Maintain and Control Traffic".

Contrary to Section 106.01, furnish new, or used in like new condition, traffic control devices at the beginning of the work and maintain in like new condition until completion of the work.

PROJECT PHASING & CONSTRUCTION PROCEDURES

The Engineer may specify days and hours when lane closures will not be allowed.

Maintain alternating one way traffic during construction. Provide a minimum clear lane width of 8 feet; however, provide for passage of vehicles of up to 16 feet in width. If traffic should be stopped due to construction operations, and a school bus on an official run arrives on the scene, make provisions for the passage of the bus as quickly as possible.

LANE CLOSURES

Do not leave lane closures in place during non-working hours.

SIGNS

Sign posts and splices shall be compliant with NCHRP 350 or MASH. Manufacturer's documentation validating this compliance shall be provided to the Engineer prior to installation. Signs, including any splices, shall be installed according to manufacturer's specifications and installation recommendations. Contrary to section 112.04.02, only long-term signs (signs intended to be continuously in place for more than 3 days) will be measured for payment. Short-term signs (signs intended to be left in place for 3 days or less) will not be measured for payment but will be incidental to Maintain and Control Traffic.

CHANGEABLE MESSAGE SIGNS

If deemed necessary by the Engineer, the Department will furnish, operate, and maintain Changeable Message Signs.

Traffic Control Plan
Page 2 of 3

TEMPORARY ENTRANCES

The Engineer will not require the Contractor to provide continuous access to farms, single family, duplex, or triplex residential properties during working hours; however, provide reasonable egress and ingress to each such property when actual operations are not in progress at that location. Limit the time during which a farm or residential entrance is blocked to the minimum length of time required for actual operations, not extended for the Contractor's convenience, and in no case exceeding six (6) hours. Notify all residents twenty-four hours in advance of any driveway or entrance closings and make any accommodations necessary to meet the access needs of disabled residents.

Except as allowed by the Phasing as specified above, maintain direct access to all side streets and roads, schools, churches, commercial properties and apartments or apartment complexes of four or more units at all times.

The Department will measure asphalt materials required to construct and maintain any temporary entrances which may be necessary to provide temporary access; however, the Department will not measure aggregates, excavation, and/or embankment, but shall be incidental to Maintain and Control Traffic. The Engineer will determine the type of surfacing material, asphalt or aggregate, to be used at each entrance.

THERMOPLASTIC INTERSECTION MARKINGS

Consider the locations listed on the summary as approximate only. Prior to milling and/or resurfacing, locate and document the locations of the existing markings. After resurfacing, replace the markings at their approximate existing locations or as directed by Engineer. Place markings not existing prior to resurfacing as directed by the Engineer.

BARRICADES

The Department will not measure barricades used in lieu of barrels and cones for channelization or delineation, but shall be incidental to Maintain and Control Traffic according to Section 112.04.01.

The Department will measure barricades used to protect pavement removal areas in individual units Each. The Department will measure for payment the maximum number of barricades in concurrent use at the same time on a single day on all sections of the contract. The Department will measure individual barricades only once for payment, regardless of how many times they are set, reset, removed, and relocated during the duration of the project. The Department will not measure replacements for damaged barricades the Engineer directs to be replaced due to poor condition or reflectivity. Retain possession of the Barricades upon completion of construction.

Traffic Control Plan
Page 3 of 3

PAVEMENT MARKINGS

If there is to be a deviation from the existing striping plan, the Engineer will furnish the Contractor a striping plan prior to placement of the final surface course.

Install Temporary Striping according to Section 112 with the following exception:

If the Contractor's operations or phasing requires temporary markings that must subsequently be removed from the final surface course, use an approved removable lane tape; however, the Department will not measure removable lane tape for separate payment, but will measure and pay for removable lane tape as temporary striping.

PAVEMENT EDGE DROP-OFFS

Do not allow a pavement edge between opposing directions of traffic or lanes that traffic is expected to cross in a lane change situation with an elevation difference greater than 1½". Place Warning signs (MUTCD W8-11 or W8-9A) in advance of and at 1500' intervals throughout the drop-off area. Dual post the signs on both sides of the traveled way. Wedge all transverse transitions between resurfaced and unresurfaced areas which traffic may cross with asphalt mixture for leveling and wedging. Remove the wedges prior to placement of the final surface course.

Protect pavement edges that traffic is not expected to cross, except accidentally, as follows:

Less than 2" - No protection required.


2" to 4" - Place plastic drums, vertical panels, or barricades every 50 feet. During daylight working hours only, the Engineer will allow the Contractor to use cones in lieu of plastic drums, panels, and barricades. Wedge the drop-off with DGA or asphalt mixture for leveling and wedging with a 1:1 or flatter slope in daylight hours, or 3:1 or flatter slope during nighttime hours, when work is not active in the drop-off area.

Greater than 4" - Protect drop-offs greater than 4 inches within 10 feet of traffic by placing drums, vertical panels, or barricades every 25 feet. The Engineer will not allow the use of cones in lieu of drums, vertical panels, or barricades for drop-offs greater than 4". Place Type III Barricades directly in front of the drop-off facing on coming traffic in both directions of travel. Provide warning signs as shown on the Standard Drawings or as directed by the Engineer

Pedestrians & Bicycles - Protect pedestrian and bicycle traffic as directed by the engineer.

DURABLE PAVEMENT EDGE DETAIL


(Resurfacing adjacent to fill slope or ditch foreslope that is 3:1 or less)



PREPARE SHOULDER ACCORDING TO STANDARD SPECIFICATIONS


DURABLE PAVEMENT EDGE DETAIL

(Resurfacing adjacent to fill slope or ditch foreslope that is steeper than 3:1)




DURABLE PAVEMENT EDGE DETAIL

(Resurfacing adjacent to low shoulder with dropoff of 5 inches or less)




DURABLE PAVEMENT EDGE DETAIL

(Resurfacing adjacent to low shoulder with dropoff of more than 5 inches)



DURABLE PAVEMENT EDGE DETAIL

(Resurfacing adjacent to an obstruction, such as an existing headwall)




NOTES


1. DETAILS DO NOT APPLY TO OVERLAYS LESS THAN 1 INCH THICK.
2. THE DURABLE PAVEMENT EDGE DEVICE MAY BE DISENGAGED AT DRIVEWAYS, SIDE STREETS, HIGH SHOULDERS, AND OTHER LOCATIONS NOT FEASIBLE TO CONSTRUCT, AS APPROVED BY THE ENGINEER.


DRAWING NOT TO SCALE


DURABLE PAVEMENT EDGE DETAILS




















MATERIAL SUMMARY

CONTRACT ID: 193136

118GR19R039-CB06

1111805111906

HIGHWAY 511 (KY 511) FROM 0.260 MILES EAST OF OLD SHINER SCHOOL ROAD EXTENDING EAST TO 0.189 MILES WEST OF SPENCER HILL ROAD ASPHALT SURFACING ULTRA THIN, A DISTANCE OF 3.15 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0425	00190	LEVELING & WEDGING PG64-22	384.00	TON
0430	00356	ASPHALT MATERIAL FOR TACK	18.00	TON
0435	02562	TEMPORARY SIGNS	270.00	SQFT
0440	02650	MAINTAIN & CONTROL TRAFFIC - (KY 511)	1.00	LS
0445	06510	PAVE STRIPING-TEMP PAINT-4 IN	16,700.00	LF
0450	06514	PAVE STRIPING-PERM PAINT-4 IN	33,400.00	LF
0455	06568	PAVE MARKING-THERMO STOP BAR-24IN	72.00	LF
0460	10020NS	FUEL ADJUSTMENT	3,924.00	DOLL
0465	10030NS	ASPHALT ADJUSTMENT	9,856.00	DOLL
0470	21653ES403	CL2 ASPH SURF NO.4D PG64-22	2,137.00	TON
0475	02569	DEMOBILIZATION	1.00	LS
0480	02676	MOBILIZATION FOR MILL & TEXT - (KY 511)	1.00	LS
0485	02677	ASPHALT PAVE MILLING & TEXTURING	20.00	TON

CONTRACT ID: 193136

118GR19R039-CB06

1111809041907

HIGHWAY 904 EAST (KY 904) FROM 0.391 MILES EAST OF PRIVATE ROAD EXTENDING EAST TO 1.374 MILES WEST OF MCKIDDY CEMETERY - COALSTONE ROAD ASPHALT PAVEMENT PATCHING, A DISTANCE OF .79 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0255	00221	CL2 ASPH BASE 0.75D PG64-22	319.00	TON
0260	00301	CL2 ASPH SURF 0.38D PG64-22	125.00	TON
0265	00356	ASPHALT MATERIAL FOR TACK	1.00	TON
0270	02562	TEMPORARY SIGNS	150.00	SQFT
0275	02650	MAINTAIN & CONTROL TRAFFIC - (KY 904)	1.00	LS
0280	02676	MOBILIZATION FOR MILL & TEXT - (KY 904)	1.00	LS
0285	02677	ASPHALT PAVE MILLING & TEXTURING	367.00	TON
0290	06510	PAVE STRIPING-TEMP PAINT-4 IN	500.00	LF
0295	06514	PAVE STRIPING-PERM PAINT-4 IN	1,500.00	LF
0300	10020NS	FUEL ADJUSTMENT	691.00	DOLL
0305	10030NS	ASPHALT ADJUSTMENT	1,736.00	DOLL
0310	02569	DEMOBILIZATION	1.00	LS

MATERIAL SUMMARY

CONTRACT ID: 193136

118GR19R039-CB06

1111810641904

WHETSTONE ROAD (KY 1064) FROM 0.065 MILES NORTH OF BUNCH CEMETERY ROAD EXTENDING NORTH TO KY 779 ASPHALT PAVEMENT PATCHING, A DISTANCE OF 3.68 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0135	00221	CL2 ASPH BASE 0.75D PG64-22	218.00	TON
0140	00301	CL2 ASPH SURF 0.38D PG64-22	564.00	TON
0145	00356	ASPHALT MATERIAL FOR TACK	4.00	TON
0150	02562	TEMPORARY SIGNS	310.00	SQFT
0155	02650	MAINTAIN & CONTROL TRAFFIC - (KY 1064)	1.00	LS
0160	02676	MOBILIZATION FOR MILL & TEXT - (KY 1064)	1.00	LS
0165	02677	ASPHALT PAVE MILLING & TEXTURING	249.00	TON
0170	06510	PAVE STRIPING-TEMP PAINT-4 IN	3,500.00	LF
0175	06514	PAVE STRIPING-PERM PAINT-4 IN	7,000.00	LF
0180	10020NS	FUEL ADJUSTMENT	1,217.00	DOLL
0185	10030NS	ASPHALT ADJUSTMENT	3,057.00	DOLL
0190	02569	DEMOBILIZATION	1.00	LS

CONTRACT ID: 193136

118GR19R039-CB06

1111815951905

HIGHWAY 1595 (KY 1595) FROM THE BELL COUNTY LINE EXTENDING NORTH TO 0.612 MILES SOUTH OF CALDWELL CEMETERY ROAD ASPHALT PAVEMENT PATCHING, A DISTANCE OF 1.93 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0195	00221	CL2 ASPH BASE 0.75D PG64-22	81.00	TON
0200	00301	CL2 ASPH SURF 0.38D PG64-22	683.00	TON
0205	00356	ASPHALT MATERIAL FOR TACK	4.00	TON
0210	02562	TEMPORARY SIGNS	170.00	SQFT
0215	02650	MAINTAIN & CONTROL TRAFFIC - (KY 1595)	1.00	LS
0220	02676	MOBILIZATION FOR MILL & TEXT - (KY 1595)	1.00	LS
0225	02677	ASPHALT PAVE MILLING & TEXTURING	101.00	TON
0230	06510	PAVE STRIPING-TEMP PAINT-4 IN	3,500.00	LF
0235	06514	PAVE STRIPING-PERM PAINT-4 IN	7,000.00	LF
0240	10020NS	FUEL ADJUSTMENT	1,189.00	DOLL
0245	10030NS	ASPHALT ADJUSTMENT	2,987.00	DOLL
0250	02569	DEMOBILIZATION	1.00	LS

MATERIAL SUMMARY

CONTRACT ID: 193136

118GR19R039-CB06

1111829951908

ELLISON BEND ROAD (KY 2995) FROM KY 2996 EXTENDING NORTH TO END OF STATE MAINTENANCE ASPHALT RESURFACING, A DISTANCE OF .95 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0315	00190	LEVELING & WEDGING PG64-22	74.00	TON
0320	00301	CL2 ASPH SURF 0.38D PG64-22	730.00	TON
0325	00356	ASPHALT MATERIAL FOR TACK	5.00	TON
0330	02562	TEMPORARY SIGNS	170.00	SQFT
0335	02650	MAINTAIN & CONTROL TRAFFIC - (KY 2995)	1.00	LS
0340	06510	PAVE STRIPING-TEMP PAINT-4 IN	5,050.00	LF
0345	06514	PAVE STRIPING-PERM PAINT-4 IN	10,100.00	LF
0350	06568	PAVE MARKING-THERMO STOP BAR-24IN	26.00	LF
0355	10020NS	FUEL ADJUSTMENT	1,251.00	DOLL
0360	10030NS	ASPHALT ADJUSTMENT	3,143.00	DOLL
0365	02569	DEMOBILIZATION	1.00	LS

CONTRACT ID: 193136

118GR19R039-CB06

1111829961902

WOLF CREEK RIVER ROAD (KY 2996) FROM 1.258 MILES NORTH OF ELLISON BEND ROAD EXTENDING NORTH TO KY 628 ASPHALT RESURFACING, A DISTANCE OF 2.29 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0070	00301	CL2 ASPH SURF 0.38D PG64-22	1,910.00	TON
0075	00356	ASPHALT MATERIAL FOR TACK	12.00	TON
0080	02562	TEMPORARY SIGNS	190.00	SQFT
0085	02650	MAINTAIN & CONTROL TRAFFIC - (KY 2996)	1.00	LS
0090	02676	MOBILIZATION FOR MILL & TEXT - (KY 2996)	1.00	LS
0095	02677	ASPHALT PAVE MILLING & TEXTURING	35.00	TON
0100	06510	PAVE STRIPING-TEMP PAINT-4 IN	12,100.00	LF
0105	06514	PAVE STRIPING-PERM PAINT-4 IN	24,200.00	LF
0110	06568	PAVE MARKING-THERMO STOP BAR-24IN	14.00	LF
0115	10020NS	FUEL ADJUSTMENT	3,364.00	DOLL
0120	10030NS	ASPHALT ADJUSTMENT	8,449.00	DOLL
0125	02569	DEMOBILIZATION	1.00	LS
0130	00190	LEVELING & WEDGING PG64-22	251.00	TON

MATERIAL SUMMARY

CONTRACT ID: 193136

118GR19R039-CB06

1111834211903

BARTON MILL CUTOFF ROAD (KY 3421) FROM KY 727 EXTENDING NORTH TO KY 1259 ASPHALT SURFACING ULTRA THIN, A DISTANCE OF 1.15 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0370	00190	LEVELING & WEDGING PG64-22	133.00	TON
0375	00356	ASPHALT MATERIAL FOR TACK	7.00	TON
0380	02562	TEMPORARY SIGNS	250.00	SQFT
0385	02650	MAINTAIN & CONTROL TRAFFIC - (KY 3421)	1.00	LS
0390	06510	PAVE STRIPING-TEMP PAINT-4 IN	6,100.00	LF
0395	06514	PAVE STRIPING-PERM PAINT-4 IN	12,200.00	LF
0400	06568	PAVE MARKING-THERMO STOP BAR-24IN	64.00	LF
0405	10020NS	FUEL ADJUSTMENT	1,382.00	DOLL
0410	10030NS	ASPHALT ADJUSTMENT	3,472.00	DOLL
0415	02569	DEMOBILIZATION	1.00	LS
0420	21653ES403	CL2 ASPH SURF NO.4D PG64-22	755.00	TON

CONTRACT ID: 193136

118GR19R039-CB06

1111834231901

TYES FERRY ROAD (KY 3423) FROM KY 26 EXTENDING EAST TO KY 779 ASPHALT PAVEMENT PATCHING, A DISTANCE OF 4.87 MILES.

Project Line No	Bid Code	DESCRIPTION	Quantity	Unit
0005	02562	TEMPORARY SIGNS	290.00	SQFT
0010	02650	MAINTAIN & CONTROL TRAFFIC - (KY 3423)	1.00	LS
0015	00301	CL2 ASPH SURF 0.38D PG64-22	396.00	TON
0020	00356	ASPHALT MATERIAL FOR TACK	3.00	TON
0025	00221	CL2 ASPH BASE 0.75D PG64-22	762.00	TON
0030	02676	MOBILIZATION FOR MILL & TEXT - (KY 3423)	1.00	LS
0035	02677	ASPHALT PAVE MILLING & TEXTURING	956.00	TON
0040	06568	PAVE MARKING-THERMO STOP BAR-24IN	12.00	LF
0045	06514	PAVE STRIPING-PERM PAINT-4 IN	10,800.00	LF
0050	06510	PAVE STRIPING-TEMP PAINT-4 IN	5,400.00	LF
0055	02569	DEMOBILIZATION	1.00	LS
0060	10030NS	ASPHALT ADJUSTMENT	4,527.00	DOLL
0065	10020NS	FUEL ADJUSTMENT	1,802.00	DOLL

KY 3423 Whitley County

South Bound Lane

Begin MP	End MP	Length LF	Mill Depth	Base Depth	Mill Tons	Base Tons	Surface Tons
4.870	4.860	52.800	5.0	4.0	19.360	15.488	3.872
4.738	4.728	52.800	5.0	4.0	19.360	15.488	3.872
4.466	4.446	105.600	5.0	4.0	38.720	30.976	7.744
4.259		100.000					7.333
4.125	4.111	73.920	5.0	4.0	27.104	21.683	5.421
2.998		100.000					7.333
2.868	2.686	960.960					70.470
0.908	0.884	126.720	5.0	4.0	46.464	37.171	9.293
0.391		100.000					7.333
0.100	0.085	79.200	2.0		11.616		5.808
Totals					162.624	120.806	128.480

North Bound Lane

Begin MP	End MP	Length LF	Mill Depth	Base Depth	Mill Tons	Base Tons	Surface Tons
0.391		100.000					7.333
1.024		100.000					7.333
2.000		100.000					7.333
2.197	2.225	147.840	8.0	7.0	86.733	75.891	10.842
2.289		100.000					7.333
2.434	2.461	142.560	5.0	4.0	52.272	41.818	10.454
2.686	2.868	960.960					70.470
2.998		100.000					7.333
3.540	3.566	137.280	4.0	3.0	40.269	30.202	10.067
3.713	3.737	126.720	5.0	4.0	46.464	37.171	9.293
4.038	4.120	432.960	5.0	4.0	158.752	127.002	31.750
4.259		100					7.333
4.326	4.344	95.040	5.0	4.0	34.848	27.878	6.970
4.380	4.397	89.760	5.0	4.0	32.912	26.330	6.582
4.508	4.530	116.160	6.0	5.0	51.110	42.592	8.518
4.601	4.724	649.440	5.0	4.0	238.128	190.502	47.626
4.767	4.794	142.560	5.0	4.0	52.272	41.818	10.454
Totals					793.760	641.203	267.027

Summary	Milling	Base	Surface
	162.624	120.806	128.480
	793.760	641.203	267.027
	956	762	396

**Whitley County
KY 904
MP 10.827 - 11.612**

Base Failure Repair

MP	Lane	Length	Mill Depth	Milling Tons	Base Tons	Surface Tons
11.612	WB	50	8	29.33	25.67	3.67
11.445	Both	100	8	117.33	102.67	14.67
11.27	EB	50	8	29.33	25.67	3.67
11.171	WB	50	4	14.67	11.00	3.67
10.827	Both	150	8	176.00	154.00	22.00
Total				367	319	48

Strip Patches

MP	Lane	Length	Surface Tons
10.982	Both	350	77
Total			77

Summary

	Milling	Asphalt Base	Asphalt Surface
Base Failure	367	319	48
Strip Patch			77
	367	319	125

**Whitley County
KY 1595
MP 0.662 - 2.587**

Base Failure Repair

MP	Lane	Length	Mill Depth	Milling Tons	Base Tons	Surface Tons
1.637	LT	75	5	27.50	22.00	5.50
2.105	LT	50	5	18.33	14.67	3.67
2.348	LT	50	5	18.33	14.67	3.67
2.559	LT	50	5	18.33	14.67	3.67
2.587	LT	50	5	18.33	14.67	3.67
				101	81	20

Strip Patches

MP	Lane	Width	Length	Surface Tons
0.662	Both	24	440	96.8
0.746	LT	12	75	8.25
0.862	Both	24	100	22.00
1.154	Both	24	150	33.00
1.537	LT	12	100	11.00
1.661	RT	12	75	8.25
1.886	Both	24	600	132.00
2.348	Both	24	1600	352.00
Total				663

Summary

	Milling	Asphalt Base	Asphalt Surface
Base Failure	101	81	20
Strip Patch			663
	101	81	683

**Whitley County
KY 1064
MP 5.624 - 9.305**

Base Failure Repair

MP	Lane	Length	Mill Depth	Milling Tons	Base Tons	Surface Tons
8.955	WB	50	8	29.33	25.67	3.67
8.155	WB	75	8	44.00	38.50	5.50
7.828	WB	50	8	29.33	25.67	3.67
7.778	EB	100	8	58.67	51.33	7.33
7.495	WB	50	8	29.33	25.67	3.67
7.415	EB	50	8	29.33	25.67	3.67
7.106	WB	50	8	29.33	25.67	3.67
Total				249	218	31

Strip Patches

Beginning MP	Ending MP	Lane	Length	Surface Tons
9.262	9.305	Both	227.04	41.624
9.188	9.235	Both	248.16	45.496
8.391	8.531	Both	739.2	135.52
8.266	8.328	Both	327.36	60.016
7.339	7.439	Both	528	96.8
6.209	6.279	Both	369.6	67.76
5.803	5.843	Both	211.2	38.72
5.624	5.672	Both	253.44	46.464
Total				532

Summary


	Milling	Asphalt Base	Asphalt Surface
Base Failure	249	218	31
Strip Patch			532
Totals	249	218	564

WHITLEY COUNTY

CB06 118 2995 000-001


TYPICAL SECTION

MILEPOINTS 0.000 - 0.952



***Where Existing Site Conditions Permit**

Whitley County
CB06 118 0904 010-012
Typical Section
Milepoints 10.827 - 11.612



Shoulders
Average Depth =

1 Inch
1.5 FT

Max. Width =

Shoulders
Average Depth =


1 Inch
1.5 FT

Max. Width =

***Where Existing Site Conditions Permit** Patching as directed by the Project Engineer


WHITLEY COUNTY

**CB06-118 0511 001-006
TYPICAL SECTION
MILEPOINTS 1.859 - 5.012**




***Where Existing Site Conditions Permit**

Whitley County
CB06 118 1595 000-003
Typical Section
Milepoints 0.746 - 2.587



***Where Existing Site Conditions Permit** Patching as directed by the Project Engineer

Whitley County
CB06 118 1064 005-010
Typical Section
Milepoints 5.624 - 9.305




Shoulders
Average Depth = 1 Inch
Max. Width = 1.5 FT

Patching as directed by the Project Engineer

***Where Existing Site Conditions Permit**

WHITLEY COUNTY


CB06-118 3421 000-002
TYPICAL SECTION
MILEPOINTS 0.000 - 1.154



***Where Existing Site Conditions Permit**


WHITLEY COUNTY

CB06-118 2996-002-005
TYPICAL SECTION
MILEPOINTS 2.000 - 4.288



***Where Existing Site Conditions Permit**

Whitley County
CB06 118 3423 000-005
Typical Section
Milepoints 0.000 - 4.870




Shoulders
Average Depth = 1 Inch
Max. Width = 1.5 FT

Shoulders
Average Depth = 1 Inch
Max. Width = 1.5 FT

***Where Existing Site Conditions Permit** Patching as directed by the Project Engineer

**CONSTRUCTION DETAIL FOR BRIDGE WITHIN LIMITS OF
PAVING PROJECT
CB06 118 0511 001-006**



W = bridge width curb to curb **T** = thickness of existing bituminous overlay **L** = length of bridge
L₁ & L₂ = length of approach pavement to be removed
T_R = thickness to be removed and replaced on bridge **P_R** = thickness to be removed and replaced on pavement
Note: **L₁ & L₂** lengths shall be determined by using a transition rate of 100 ft / inch of thickness

BRIDGE NO	MP	W (ft)	T (in)	L ₁ (ft)	L ₂ (ft)	T _R (in)	L (ft)	P _R (in)
118B00011N	3.148	24.00	1.00	75.00	75.00	1.00	12.00	0.75
118B00010N	4.487	24.00		75.00	75.00		257.00	0.75

PART II
SPECIFICATIONS AND STANDARD DRAWINGS

SPECIFICATIONS REFERENCE

Any reference in the plans or proposal to previous editions of the *Standard Specifications for Road and Bridge Construction* and *Standard Drawings* are superseded by *Standard Specifications for Road and Bridge Construction, Edition of 2019* and *Standard Drawings, Edition of 2016*.

SUPPLEMENTAL SPECIFICATIONS

The contractor shall use the Supplemental Specifications that are effective at the time of letting.
The Supplemental Specifications can be found at the following link:

<http://transportation.ky.gov/Construction/Pages/Kentucky-Standard-Specifications.aspx>

2016 STANDARD DRAWINGS THAT APPLY

ROADWAY ~GENERAL~

MISCELLANEOUS STANDARDS

MISCELLANEOUS STANDARDS PART 1.....RGX-001-06

~PAVEMENT~

MEDIANS, CURBS, APPROACHES, ENTRANCES, ETC.

APPROACHES, ENTRANCES, AND MAIL BOX TURNOUT.....RPM-110-07

TRAFFIC ~TEMPORARY~

DEVICES

LANE CLOSURE TWO-LANE HIGHWAYTTC-100-04

PART III

EMPLOYMENT, WAGE AND RECORD REQUIREMENTS

**TRANSPORTATION CABINET
DEPARTMENT OF HIGHWAYS**

**LABOR AND WAGE REQUIREMENTS
APPLICABLE TO OTHER THAN FEDERAL-AID SYSTEM PROJECTS**

- I. Application
- II. Nondiscrimination of Employees (KRS 344)

I. APPLICATION

1. These contract provisions shall apply to all work performed on the contract by the contractor with his own organization and with the assistance of workmen under his immediate superintendence and to all work performed on the contract by piecework, station work or by subcontract. The contractor's organization shall be construed to include only workmen employed and paid directly by the contractor and equipment owned or rented by him, with or without operators.

2. The contractor shall insert in each of his subcontracts all of the stipulations contained in these Required Provisions and such other stipulations as may be required.

3. A breach of any of the stipulations contained in these Required Provisions may be grounds for termination of the contract.

3. If the contractor is in control of apprenticeship or other training or retraining, including on-the-job training programs, he shall not discriminate against an individual because of his race, color, religion, national origin, sex, disability or age forty (40) and over, in admission to, or employment in any program established to provide apprenticeship or other training.

4. The contractor will send to each labor union or representative of workers with which he has a collective bargaining agreement or other contract or understanding, a notice to be provided advising the said labor union or workers' representative of the contractor's commitments under this section, and shall post copies of the notice in conspicuous places available to employees and applicants for employment. The contractor will take such action with respect to any subcontract or purchase order as the administrating agency may direct as a means of enforcing such provisions, including sanctions for non-compliance.

Revised: January 25, 2017

II. NONDISCRIMINATION OF EMPLOYEES

**AN ACT OF THE KENTUCKY
GENERAL ASSEMBLY TO PREVENT
DISCRIMINATION IN EMPLOYMENT
KRS CHAPTER 344
EFFECTIVE JUNE 16, 1972**

The contract on this project, in accordance with KRS Chapter 344, provides that during the performance of this contract, the contractor agrees as follows:

1. The contractor shall not fail or refuse to hire, or shall not discharge any individual, or otherwise discriminate against an individual with respect to his compensation, terms, conditions, or privileges of employment, because of such individual's race, color, religion, national origin, sex, disability or age (forty and above); or limit, segregate, or classify his employees in any way which would deprive or tend to deprive an individual of employment opportunities or otherwise adversely affect his status as an employee, because of such individual's race, color, religion, national origin, sex, disability or age forty (40) and over. The contractor agrees to post in conspicuous places, available to employees and applicants for employment, notices to be provided setting forth the provisions of this nondiscrimination clause.

2. The contractor shall not print or publish or cause to be printed or published a notice or advertisement relating to employment by such an employer or membership in or any classification or referral for employment by the employment agency, indicating any preference, limitation, specification, or discrimination, based on race, color, religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, except that such a notice or advertisement may indicate a preference, limitation, or specification based on religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, when religion, national origin, sex, or age forty (40) and over, or because the person is a qualified individual with a disability, is a bona fide occupational qualification for employment.

EXECUTIVE BRANCH CODE OF ETHICS

In the 1992 regular legislative session, the General Assembly passed and Governor Brereton Jones signed Senate Bill 63 (codified as KRS 11A), the Executive Branch Code of Ethics, which states, in part:

KRS 11A.040 (7) provides:

No present or former public servant shall, within six (6) months following termination of his office or employment, accept employment, compensation, or other economic benefit from any person or business that contracts or does business with, or is regulated by, the state in matters in which he was directly involved during the last thirty-six (36) months of his tenure. This provision shall not prohibit an individual from returning to the same business, firm, occupation, or profession in which he was involved prior to taking office or beginning his term of employment, or for which he received, prior to his state employment, a professional degree or license, provided that, for a period of six (6) months, he personally refrains from working on any matter in which he was directly involved during the last thirty-six (36) months of his tenure in state government. This subsection shall not prohibit the performance of ministerial functions, including but not limited to filing tax returns, filing applications for permits or licenses, or filing incorporation papers, nor shall it prohibit the former officer or public servant from receiving public funds disbursed through entitlement programs.

KRS 11A.040 (9) states:

A former public servant shall not represent a person or business before a state agency in a matter in which the former public servant was directly involved during the last thirty-six (36) months of his tenure, for a period of one (1) year after the latter of:

- a) The date of leaving office or termination of employment; or
- b) The date the term of office expires to which the public servant was elected.

This law is intended to promote public confidence in the integrity of state government and to declare as public policy the idea that state employees should view their work as a public trust and not as a way to obtain private benefits.

If you have worked for the executive branch of state government within the past six months, you may be subject to the law's prohibitions. The law's applicability may be different if you hold elected office or are contemplating representation of another before a state agency.

Also, if you are affiliated with a firm which does business with the state and which employs former state executive-branch employees, you should be aware that the law may apply to them.

In case of doubt, the law permits you to request an advisory opinion from the Executive Branch Ethics Commission, 3 Fountain Place, Frankfort, Kentucky 40601; telephone (502) 564-7954.

Revised: January 27, 2017

Kentucky Equal Employment Opportunity Act of 1978

The requirements of the Kentucky Equal Employment Opportunity Act of 1978 (KRS 45.560-45.640) shall apply to this Contract. The apparent low Bidder will be required to submit EEO forms to the Division of Construction Procurement, which will then forward to the Finance and Administration Cabinet for review and approval. No award will become effective until all forms are submitted and EEO/CC has certified compliance. The required EEO forms are as follows:

- EEO-1: Employer Information Report
- Affidavit of Intent to Comply
- Employee Data Sheet
- Subcontractor Report

These forms are available on the Finance and Administration's web page under ***Vendor Information, Standard Attachments and General Terms*** at the following address:
<https://www.eProcurement.ky.gov>.

Bidders currently certified as being in compliance by the Finance and Administration Cabinet may submit a copy of their approval letter in lieu of the referenced EEO forms.

For questions or assistance please contact the Finance and Administration Cabinet by email at **finance.contractcompliance@ky.gov** or by phone at 502-564-2874.

EMPLOYEE RIGHTS UNDER THE FAIR LABOR STANDARDS ACT

THE UNITED STATES DEPARTMENT OF LABOR WAGE AND HOUR DIVISION

FEDERAL MINIMUM WAGE

\$7.25 PER HOUR

BEGINNING JULY 24, 2009

OVERTIME PAY At least 1½ times your regular rate of pay for all hours worked over 40 in a workweek.

CHILD LABOR An employee must be at least **16** years old to work in most non-farm jobs and at least **18** to work in non-farm jobs declared hazardous by the Secretary of Labor.

Youths **14** and **15** years old may work outside school hours in various non-manufacturing, non-mining, non-hazardous jobs under the following conditions:

No more than

- **3** hours on a school day or **18** hours in a school week;
- **8** hours on a non-school day or **40** hours in a non-school week.

Also, work may not begin before **7 a.m.** or end after **7 p.m.**, except from June 1 through Labor Day, when evening hours are extended to **9 p.m.** Different rules apply in agricultural employment.

TIP CREDIT Employers of “tipped employees” must pay a cash wage of at least \$2.13 per hour if they claim a tip credit against their minimum wage obligation. If an employee’s tips combined with the employer’s cash wage of at least \$2.13 per hour do not equal the minimum hourly wage, the employer must make up the difference. Certain other conditions must also be met.

ENFORCEMENT The Department of Labor may recover back wages either administratively or through court action, for the employees that have been underpaid in violation of the law. Violations may result in civil or criminal action.

Employers may be assessed civil money penalties of up to \$1,100 for each willful or repeated violation of the minimum wage or overtime pay provisions of the law and up to \$11,000 for each employee who is the subject of a violation of the Act’s child labor provisions. In addition, a civil money penalty of up to \$50,000 may be assessed for each child labor violation that causes the death or serious injury of any minor employee, and such assessments may be doubled, up to \$100,000, when the violations are determined to be willful or repeated. The law also prohibits discriminating against or discharging workers who file a complaint or participate in any proceeding under the Act.

ADDITIONAL INFORMATION

- Certain occupations and establishments are exempt from the minimum wage and/or overtime pay provisions.
- Special provisions apply to workers in American Samoa and the Commonwealth of the Northern Mariana Islands.
- Some state laws provide greater employee protections; employers must comply with both.
- The law requires employers to display this poster where employees can readily see it.
- Employees under 20 years of age may be paid \$4.25 per hour during their first 90 consecutive calendar days of employment with an employer.
- Certain full-time students, student learners, apprentices, and workers with disabilities may be paid less than the minimum wage under special certificates issued by the Department of Labor.

For additional information:



1-866-4-USWAGE

(1-866-487-9243) TTY: 1-877-889-5627



WWW.WAGEHOUR.DOL.GOV

PART IV
INSURANCE

INSURANCE

The Contractor shall procure and maintain the following insurance in addition to the insurance required by law:

- 1) Commercial General Liability-Occurrence form – not less than \$2,000,000 General aggregate, \$2,000,000 Products & Completed Aggregate, \$1,000,000 Personal & Advertising, \$1,000,000 each occurrence.
- 2) Automobile Liability- \$1,000,000 per accident
- 3) Employers Liability:
 - a) \$100,000 Each Accident Bodily Injury
 - b) \$500,000 Policy limit Bodily Injury by Disease
 - c) \$100,000 Each Employee Bodily Injury by Disease
- 4) The insurance required above must be evidenced by a Certificate of Insurance and this Certificate of Insurance must contain one of the following statements:
 - a) "policy contains no deductible clauses."
 - b) "policy contains _____ (amount) deductible property damage clause but company will pay claim and collect the deductible from the insured."
- 5) KENTUCKY WORKMEN'S COMPENSATION INSURANCE. The contractor shall furnish evidence of coverage of all his employees or give evidence of self-insurance by submitting a copy of a certificate issued by the Workmen's Compensation Board.

The cost of insurance is incidental to all contract items. All subcontractors must meet the same minimum insurance requirements.

PART V
BID ITEMS

PROPOSAL BID ITEMS

193136

Page 1 of 1

Report Date 5/29/19

Section: 0001 - PAVING

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0010	00190		LEVELING & WEDGING PG64-22	842.00	TON		\$	
0020	00221		CL2 ASPH BASE 0.75D PG64-22	1,380.00	TON		\$	
0030	00301		CL2 ASPH SURF 0.38D PG64-22	4,408.00	TON		\$	
0040	00356		ASPHALT MATERIAL FOR TACK	54.00	TON		\$	
0050	02562		TEMPORARY SIGNS	1,800.00	SQFT		\$	
0060	02650		MAINTAIN & CONTROL TRAFFIC (KY 1064)	1.00	LS		\$	
0070	02650		MAINTAIN & CONTROL TRAFFIC (KY 1595)	1.00	LS		\$	
0080	02650		MAINTAIN & CONTROL TRAFFIC (KY 2995)	1.00	LS		\$	
0090	02650		MAINTAIN & CONTROL TRAFFIC (KY 2996)	1.00	LS		\$	
0100	02650		MAINTAIN & CONTROL TRAFFIC (KY 3421)	1.00	LS		\$	
0110	02650		MAINTAIN & CONTROL TRAFFIC (KY 3423)	1.00	LS		\$	
0120	02650		MAINTAIN & CONTROL TRAFFIC (KY 511)	1.00	LS		\$	
0130	02650		MAINTAIN & CONTROL TRAFFIC (KY 904)	1.00	LS		\$	
0140	02676		MOBILIZATION FOR MILL & TEXT (KY 1064)	1.00	LS		\$	
0150	02676		MOBILIZATION FOR MILL & TEXT (KY 1595)	1.00	LS		\$	
0160	02676		MOBILIZATION FOR MILL & TEXT (KY 2996)	1.00	LS		\$	
0170	02676		MOBILIZATION FOR MILL & TEXT (KY 3423)	1.00	LS		\$	
0180	02676		MOBILIZATION FOR MILL & TEXT (KY 511)	1.00	LS		\$	
0190	02676		MOBILIZATION FOR MILL & TEXT (KY 904)	1.00	LS		\$	
0200	02677		ASPHALT PAVE MILLING & TEXTURING	1,728.00	TON		\$	
0210	06510		PAVE STRIPING-TEMP PAINT-4 IN	52,850.00	LF		\$	
0220	06514		PAVE STRIPING-PERM PAINT-4 IN	106,200.00	LF		\$	
0230	06568		PAVE MARKING-THERMO STOP BAR-24IN	188.00	LF		\$	
0240	10020NS		FUEL ADJUSTMENT	14,820.00	DOLL	\$1.00	\$	\$14,820.00
0250	10030NS		ASPHALT ADJUSTMENT	37,227.00	DOLL	\$1.00	\$	\$37,227.00
0260	21653ES403		CL2 ASPH SURF NO.4D PG64-22	2,892.00	TON		\$	

Section: 0002 - DEMOBILIZATION

LINE	BID CODE	ALT	DESCRIPTION	QUANTITY	UNIT	UNIT PRIC	FP	AMOUNT
0270	02569		DEMOBILIZATION	1.00	LS		\$	