THIRD-ORDER LEVELING
NATIONAL GEODETIC VERTICAL DATUM OF 1929

38-082-31
CEREDO QUADRANGLE
177 KY-57 W.VA. -2 0810
#3815-18230/15
BIAGRAM RJ 17-4
#EMILINGION

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

IRCHION
(5 OHIO-191 KY.)

Boyd, Greenup, and Lawrence Counties, Ky.; Wayne and Cabell Counties, W.YA.; Lawrence County, Ohio

Final adjustment of 1973

Edition of 1/3/77

PR: LFB/mjh

Ashland The Cannonsburg

Cannon

11

GRAYSON (178 KY.)

LOUISA (160 KY.--12 W.VA.)

MES (USCRES) VERTICAL CONTROL DATA

14

14

Boltsfork

A. Quadrangle 380823

INDEX OF PERMANENT MARKS

MARK (US6S)	PAGE NO.	MARK (USCS)	PAGE NO.
549 K 1900	3	66 JJS 1956 646	5,6
556 K RESET 1961	3	67 JJS 1956 924	5
565 GRAFTON	3	68 JJS 1956 565	6
567 K	. 3	69 JJS 1956 RESET 1958	7
586 K	3	96 JJS 1956 560	8
604 K	3	97 JJS 1956 629	9
638 K	3	.98 JJS 1956 651	9
652 K	3	99 JUS 1956 567	9
TVA TT 31 NY 1952	11	100 JJS 1956 RESET 1965 609	9,10
TVA TT 32 NY 1952	12	101 JJS 1956 790	10
TVA TT 33 NY 1952	12	102 JJS 1956 610	10,11
TVA TT 49 NY 1952	12	103 JJS 1956 682	10
60 NY 1952	13	104 JJS 1956 670	11
61 NY 1952	13	105 JJS 1956 596	11,11
62 NY 1952	13	121 JJS 1956 620	11
63 NY 1952	13	GAGING REFERENCE MARK	8
64 NY 1952	14		
65 NY 1952 REPT. DEST. 1191	14	SSED	
TVA 66 NY 1952 RESET 1965	14		
TT 1 RCD 1955 674	6	BM 520	3,4,7
TT 4 GBG 1955 574	6,6	OR 510	4,6
TT 6 GBG 1955 562	7,8	566.31	6,8
TT 7 GBG 1955 578	. 7	B 3 A	8
TT 8 GBG 1955 568	8	8 4 B	10
TT 9 GBG 1955 581	8,9	GYP	4
60 JJS 1956 601	3		
61 JJS 1956 RESET 1967 656	4,5	<u>NGS</u>	
63 JJS 1956 579	4		
64 JJS 1956 576	5 , 7	H 84 1935	8
65 JJS 1956 623	5		

CEREDO CHADRANGLE 177 KY-57 W. VA-2 9HIO Bks. 2086 and 8664	38-082-31 3
ISOLATED BENCH MARKS (By W. N. Morrill, 1900-01; Books 8086, 8664	Feet
Savage Branch, 1.0 mi S. of station; at two-story brick residence of Lawrence Bowling; on W. side of rd.; about 120 ft from centerline of rd.; in foundation on left side of perch; standard tablet stamped **586 K** (partly covered by porch)	536.517
Boltsfork; 600 ft N. of post office; at hwy. bridge ever Bolts Fork; is SE. corser bridge seat; standard tablet stamped 7652 KT (Reported not found, 1953)	6 52.875
Cannonsburg; 93 ft from RR. crossing; in SE. corner of post effice building; standard tablet stamped *604 K**	605.2 59
Meads; 1.0 mi NE. of station; 81 ft N. of small bridge; 15 ft E. of conterline of rd.; in sandstone boulder; standard tablet stamped *638 K** (Reported not found, 1953)	638.600
Achland; at intersection of Chesapeake and Ohio Railroad and Twelfth Street W. of station; at valuation station No. 4853+06; 14 ft N. of centerline of westbound main—line track; 4 ft W. of W. curb of Twelfth Street; in concrete pavement; standard tablet stamped **556 K RESEI 1961**	557.336
Catlettsburg; on Louisa Street between Franklin and Clay Streets; in courthouse yard; in MW. corner of clerk's office; 1 ft above water table; standard tablet stamped *549 K 1900* (Reported not found, 1953)	550.824
Keneva; at Union Station; in W. side of doorsill of men's entrance to waiting room; standard tablet stamped **567 K** (Reported destroyed, 1956)	567.481
Buffalo Creek; at station; 7 ft from track; in SW. abutment of bridge over Buffalo Creek; standard tablet stamped #565 GRAFTON* (Reported not found, 1956)	5 64 .476
LIME 1.	
By J. J. Spahr, 1956; Book AV 480	
Sheridan; 2.4 mi SE. of NE. end of Ohio River bridge at Ashland; about 500 ft NW. of first grade crossing S. of mouth of Lick Crock; on Norfolk & Western Railroad property adjacent to property of Charles Hoffman; 34 ft SW. of conterline of eastbound track; 32 ft NW. of power pole; at lower end of small orchard; 18 ft from river bank; in concrete pedestal; on 2—in. galvanized pipe; standard copper belt designated NBM 520 (USED)	549.680
U. E., Sheridan, 1.1 mi E. of; 15 ft SW. of conterline of junction of Y-rd. S.; in root on NE. side of 36-in. tree; copper nail and washer	557.68
Sheridan, 2.4 mi E. of junction of Lick Creek Road and U. S. Highway 52; 21 ft S. of center- line of junction of Y-rd. N. to Dearing; 2 ft S. of fenceline; 4 ft SE. of corner fencepost; 32 ft E. of 24-in. walnut tree in center of junction of private drive S.; 14 ft WSW. of 24-in. walnut tree; in concrete post; standard tablet stamped *60 JJS 1956 601* (Tied by NGS, 1958)	601.131
U. E., Ryansville, 1.1 mi W. ef, thence 0.8 mi S.; on center ef SE. concrete wingwall ef culvert in front of large white frame house; chiseled square	637.29

	4
LIME 1 (Cont'd.)	Feet
Caal Grove, 6.0 mi E. of intersection of U. S. Highway 52 and State Highway 243, along Highway 243; 1.7 mi SE. of Dawson Bryant Elementary School; 0.9 mi SE. of Ice Creek Baptist Church; 1.1 mi W. of Ryansville; in frontyard of residence of Lawrence Porter (red brick house on M. side of hwy.); 31 ft S. of SW. corner of house; 25 ft W. of W. edge of sidewalk to front door; 15 ft E. of centerline of drive M.; 2 ft E. of small bush; in concrete post 0.2 ft under surface of ground; standard tablet stamped M61 JJS 1956 RESET 1967 656	
01 333 1970 KCIE1 1907 070"	65 6.115
Reference mark; about 160 ft SE. of tablet; on M. corner of concrete bridge over crock; chiseled square	6 56 . 10
U. E., Dearing, O.6 mi SE. of; 50 ft NHE. of, and O.5 ft higher than conterline of junction of I—rd. NE.; in root on SW. side of multiple trunk tree; capper nail and washer	65 8.24
[Jogs into Irentem quadrangle/	
U. E., Forestdale, U.4 mi ME. of; 60 ft E. of centerline of junction of Tard. with drive M.; on E. and of M. concrete headwall of culvert; chiseled square	613.48
Ferestdale, 0.6 mi S. of, along Little Ice Creek rd.; near center of sec. 1, T. 1, R. 18; 42 ft NW. of centerline of junction of Y-rd. at powerline crossing; 6 ft S. of westernmost power pole; 16 ft E. of creek bank; in concrete post; standard tablet stamped %53 JJS 1956 579*	579 . 355 1
Reference mark; 另 ft ME. of tablet; in base on E. side of power pole; spike mail	579.36
Ashland, about 0.6 mi SE. of NE. and of Ohio River highway bridge; at SE. and of small roadside park; 34 ft from river edge of U. S. Highway 52; 25 ft hillward from 12-in. walnut tree; in concrete post; USED standard triangulation station disk stamped "GYP" (Raported destroyed, 1968)	582. 4%
U. E., Sheridan, O.4 mi NE. of; in top of end of RR. tie asarest milepost; No. 574; capper mail and washer	562.65
"BM 520" (USED) (Described previously in this line)	549.680
LINE 2.	-
By J. J. Spahr, 1956; Book AV 480	
Burlington, about 1.2 mi W. of; on N. bank of Ohio River; opposite U. S. Light No. 373; on property of John Andrim; 50 ft above upper river corner of residence; 22 ft NE. of spike in triangular blazed 39—in. maple tree; about 350 ft from low river bank; in concrete pedestal; on 2—in. galvanized iron pipe; USED standard copper bolt designated NOR 510 N (Reported disturbed, 1956 — cap broken off pipe)	556,700
Reference mark; 35 ft N. of bolt; on NE. corner of E. end of concrete walk to house; chiseled square	5 59 .08
W. E., Burlington, 1.1 mi W. of, thence 0.6 mi MW.; at top of hill; in root on M. side of 15-in. maple tree, on fonceline of old rd.; copper mail and washer	706.4 8

CEREDO QUADRANGLE	177 KY57 W. VA2 OHIO	38-082-31 6
LINE 3 (Cont'd.)		Feet
R 17 W., about 1.1 mi W. of 20-foot brid two-story white house; 25.5 ft N. of cem 2.5 ft NW. of telephone pole; 17 ft SE.	nway 243 from Methodist Church, in sec. 3, T 1M, dge and side road NW., at junction of drive N. to sterline of rd.; 32 ft E. of centerline of drive; of SE. corner of garage, about 4 ft above level in.; standard tablet stamped MIT 1 RCD 1955 674M	673. 522
	Control of the contro	
By J. J. Spahr, 1956; Book AV 480		
at Buffalo Creek School and junction of W. of junction; 100 ft NW. of NW. end of	vay 52, thence 2.0 mi N. along Buffalo Creek rd.; Little Buffalo Creek Road; 34 ft N. and 58 ft f bridge; 3 ft N. of yard fence corner; 55 ft S. junction of rd. N.; in concrete post; standard	57 4.0 57
Out of the second of the secon	and as W. committee announced balders absorbed	
Square	, and of M. wingwall of concrate bridge; chiseled	566.92
•	n ter lostfar sombolis stockings	
private Y-drive RE.; in base on SW. side	.7 mi SE.; 40 ft ERE. of conterline of junction of e of power pole; spike mail	623.96
™66 JJS 1956 646™ (Bescribed in lime 2)		61 5.994
	LINE 5.	
By J. J. Spahr, 1956; Book AV 480	•	
#TT 4 68G 1955 574# (Described in line 4)		574-057
	LINE 6.	
By J. J. Spahr, 1956; Book 480		
at Sybene; en N. bank of Ohio River; at edge of walk along S. face of building;	ong U. S. Mighway 52; about 0.3 mi S. of post office SE. carner of lockhouse of U. S. Lock No. 28; at N. on top of SE. corner of 16- by 16-in. concrete od \$566.34" (USED) (Tied by NGS, 1958)	565 .832
of Onio River; 7 ft S. of S. face of le	e, aleng U. S. Highway 52; at Lock Me. 28 on M. bank ckhouse; 1 ft S. ef M. edge of walk; 6 ft E. ef center ockhouse; USED standard brass plug designated \$566.31*	56 5.773
building: 55 ft SSE, of centerline of a	shington Avenue; 97 ft NW. of NW. corner of city lley; 30 ft SW. of SW. side of village water tank concrete post; standard tablet stamped *68 JJS 1956 565*	564.916
Reference mark; 44 ft S. of tablet; in rowasher	ot on ME. side of 48—in. maple tree; copper sail and	565.06
OR 510 (USED) (Described in line 2)		556.700

LINE 7.	Feet
By J. J. Spahr, 1956; Book AV 480	
64 JJS 1956 576 (Described in line 2)	576.032
U. E., South Point, 1.3 mi E. of, thence 0.9 mi MW.; 9 ft ME. of conterline of rd.; on MW. corner of concrete walk to green shingled house; chiseled square	575.06
South Point, 2.1 mi N. of N. & W. RR. crossing, along U. S. Highway 52 to junction of I-rd. E., thence 0.3 mi E.; 30 ft NE. of junction of I-rd. S.; 2 ft W. of 6- by 4-ft concrete block pump building: in concrete post; standard tablet stamped M69 JJS 1956 RESET 1958 (Not found, 1968)	574.818
SM 520 (USED) (Bescribed in line 1)	549.680
LINE B.	
By J. J. Spahr, 1956; Book AV 480	
"566.34" (USED) (Tied by MGS, 1958) (Described in line 6)	565.832
Huntington, 2.9 mi W. of corner of Feurth Avenue and Sixth Street, along U. S. Highway 60, thence 0.2 mi NV. on W. 28th Street to river levee; at pump station at mouth of Fourpole Creek; 67 ft NE. of NE. corner of pump building; 14 ft S. of SE. corner of concrete platform; on top of levee; 3 ft NE. of corner post of guardrail; in concrete post; standard tablet stamped NTI 6 GBG 1955 562N	56 2 . 101
Reference mark; 64 ft W. of tablet; on floor level of pump station; on ME. cerner of M. side of E. equipment door; chiseled square	56 5 . 93
U. E., Muntington, 3.4 mi W. of Intersection of Fourth Avenue and Sixth Street; 10 ft W. of NW. corner of curb of Auburn Read and 31st Street W.; chiseled crass designated **OH 549** (USED elevation not held)	5 1 9.02
Ceredo, about 2.2 mi E. ef, along U. S. Highway 60 and Spring Valley rd.; 4.3 mi W. ef cerner of Fourth Avenue and Sixth Street in Huntington along Highway 60 and Spring Valley rd.; at junction of rds. at S. end of viaduct ever C. & O. RR.; about 100 ft SW. of small concrete block shed; 64 ft SE. ef SE. corner of sidewalk at S. end of viaduct; 32 ft S. and 34 ft E. ef junction of I-rd.; 28 ft S. of, and about level with conterline of rd. epposite; 26 ft E. ef rd. sign; 51 ft W. of vertical 3-in. pipe in gas line; in concrete post; standard tablet stamped mIT 7 GBG 1955 578 (Reported met found, 1968)	577.588
Reference mark; 77 ft MW. of tablet; on MW. corner of W. end of SW. wingwall of concrete everpass bridge; chiseled square	576.697
U. E., Corede, 2.2 mi E. of, thence 1.2 mi S.; at top of hill; 72 ft SW. of, and 3 ft higher than conterline of junction of Y-rd. S. to Veteran's Administration Hospital; on top of stone wall; chiseled square	6 55 . 559

LIME 8 (Cont'd.)

Feet

Spring Valley Store, 1.5 mi W. of, along paved rd.; 3.1 mi NE. of junction of paved rd. with State Highway 75; 1.0 mi W. of entrance to V.A. Hospital; at rd. junction on curve in front of residence of Lloyd Ward; 42 ft S. and 36 ft W. of centerline of main rd. and rd. tangent W.; 19 ft S. and 34 ft E. of graveled I—rd. N.; 27 ft W. of, and about 3 ft higher than centerline of main rd. opposite; 10 ft N. of fence corner; 2 ft E. of stone retaining wall; in concrete post; standard tablet stamped TI 8 GB6 1955 568 (Reported destroyed, 1957)

567.872

Reference mark; 9 ft SW. of tablet; on SE. corner of stone retaining wall; chiseled square

568.88

Spring Valley Store, 2.9 mi SW. of; 1.8 mi N. of junction of State Highway 75 and Spring Valley rd.; 2.4 mi S. of entrance to V.A. Hospital; at entrance gate to Camp Mad Anthony Wayne; 2 ft MW. of large rock in row at entrance gate; 46 ft SW. of pole No. 486—46; 37 ft due E. of entrance to camp; in concrete post flush with lawn; standard tablet stamped "II 9 GBG 1955 581"

580.869

Zogs on into Guyandotte quadrangle/

TTT 6 GBG 1955 562" (Described previously in this line)

562.101

Chesapeake; about 3.0 mi W. of post office, along U. S. Highway 52; at U. S. Lock 28; on N. bank of Ohio River; about 300 ft SE. of lock house; 11 ft SE. of slope of riprap; at N. corner of iron plates at NE. corner of locks; in top of end of concrete driveway from top of back to lock; standard gaging station tablet stamped MGAGING REFERENCE MARKING (Tied by NGS, 1958)

513.260

*566.31 (USED) (Tied by MGS, 1958) (Described in line 6)

565.773

LINE 9.

By J. J. Spahr, 1956; Book AV 480

Catlettsburg, 4.7 mi S. of; on left bank about 4.7 mi above mouth of Big Sandy River; about 0.3 mi upstream from Campbell Run; about 770 ft downstream from milepost No. BSJ-4; 18 ft E. of conterline of C. & O. Ry. riverward track; 28 ft W. of 24-in. elm tree; 45 ft N. of telephone pole; on iron pipe in concrete post; standard USED cap designated NB 3 AN (USED elevation not held)

553.340

** 84 1935** (MGS) (Not found, 1972)

553.4%

U. E., Neal; 90 ft S. of junction of T-rd. W.; on conter of E. headwall of concrete culvert; chiseled square

581.55

Kanova, 2.3 mi S. of bridge over Big Sandy River, along Big Sandy River rd.; 1.0 mi N. of Meal; 87 ft NE. of centerline of junction of Miller Creek Road E.; 33 ft E. of centerline of river rd.; 10 ft N. of N. gatepost; at SW. cerner of yard in front of house No. 1902; 2 ft W. of corner fence post; in concrete post; standard tablet stamped N96 JJS 1956 560 (Not found, 1972)

560.436

CEREBO QUADRANGLE	177 KY-57 W. VA-2 0010	74-082-31 9
LIME 9 (Cont'd.)		Fact
Reference mark; 100 ft S. of tabl	et; en corner ef L-shaped culvert; chiseled square	559.39
U. E., Buffalo Creek, 4.4 mi W. a culvert; chiseled square	of RR. bridge; em NW. end of NE. concrete gwardrail of	574.14
of junction of U.S. highway 60 junction of I-rd. SW. to Hill C	ge ever Twelvepole Creek, along State Highway 75; 3.5 mi S. and Highway 75 at Keneva; 35 ft SSW. of centerline of Crest Cemetery; 14 ft SSE. of centerline of graveled rd., 10 of ground end of guy wire; in concrete post; standard tablet deported Destroyed, 1979)	628.70 3
Reference mark; 11 ft MME. of tab	olet; in base on S. side of powerline pole; spike sail	627.97
	of RR. bridge; at outside of sharp curve in hwy.; 20 ft S. outcrop at stone walk to house S.; chiseled square	646. 91
of centerline of Highway 75; 38	ge over Twelvepole Creek, along State Highway 75; 32 ft M. 3 ft ME. of junction of I-rd. M.; 11 ft M. of concrete rd. in concrete post; standard tablet stamped *98 JIS 1956 651*	6 51 . 19 6
W. E., Buffalo Creek; on W. end o	of S. abutment of M. & W. RR. bridge; chiseled circle with	564.42
formed by junction of State Hi	i S. of Camp Mad Anthony Wayne; at center of grassy triangle glaway 75 and Twelvepole Creek rd. to Ceredo; 4 ft ME. of, and rd. signpost; in concrete post; standard tablet stamped	566 .879
Reference mark; 9 ft SW. of tabl	et; on rock estorop; chiseled square	565.22
TTT 9 686 1955 581" (Described	in line 8)	580.869
	LINE 10.	
By J. J. Spahr, 1956; Book AV 48	0	·
W. E., Buffale Crock; chiseled c	ircle with cress in center (Described in line 9)	564.42
U. E., Buffalo Creek, O.7 mi S. with field entrance rd. SW.; a	of high school; 10 ft W. of conterline of junction of Y-rd. n large rock in conterline of field rd.; chiseled square	576.65
Cedar Run on Big Sandy River, junction of Y-rd. (Cedar Run conterline of rd.; 27 ft E. of	a school, along Buffalo Creek Road; 3.2 mi EME. of mouth of along Buffalo Creek Road; 2.0 mi S. of Malcolm Lane; at and Buffalo Creek Roads); 31 ft W. of, and 5 ft lower than Buffalo Creek Church; in top of M. ond of 9th concrete step let stamped *100 JJS 1956 RESET 1965 609*	609.3 71

CEREDO QUADRANGLE	177 KY57 H. VA2 0HIO	38- 082 - 31
LIME 10 (Cont'd.)		10 Feet
Reference mark; about 22 ft S. of table	st; sa St. cerner of first concrete step to church;	
chiseled cross		605.77
U. E., Buffalo Valley Church, 1.0 mi W. of conterline of rd.; in base on SW.	ef; about 200 ft W. of branch crossing W.; 8 ft W. side of 36-in. elm tree; spike mail	625.70
Codar Run rd.; on dividing ridge beta corner of log cabin; 14 ft SSE, of ca	.7 mi NE. of mouth of Codar Rum on Big Sandy River, along ween Big Sandy River and Buffalo Crook; 41 ft MME. of N. enterline of rd.; about 57 ft E. of top of hill; 1 ft N. ndard tablet stamped "101 JJS 1956 790" (Reported	em zla
		790.34 7
Reference mark; 100 ft SW. of tablet;	in base on MW. side of power pole; spike mail	788.25
U. E., Buffalo Valley Church, 3.2 mi W. ever Cedar Run; chiseled square	. ef; on S. end ef E. ceacrate guardrail ef hwy. bridge	552 . 46
19 ft E. of conterline of C & O. Ry. about 310 ft downstream from 24-in. o	n left bank about 7.4 mi above mouth of Big Sandy River; riverward track; about 0.2 mi upstream from Lockwood Creek; culvert under hwy. and RR.; 6 ft upstream from telephone pole; tandard USED cap designated "B 4 B" (USED elevation not held)	559 • 55 1
	LINE 11.	
By J. J. Spahr, 1956; Beck AV 480		
*100 JJS 1956 RESET 1965 609" (Descrit	ped in line 10)	609.371
U. E., Buffale Valley Church, 0.6 mi Si	E. of; conterline of junction of I-drive ME.	597.74
U. E., Buffalo Valley Church, 1.1 mi Si W. headwall of a stone culvert; chise	E. ef; 12 ft from centerline ef rd.; en R. end of eled square	607.25
	1.7 mi ME. of Rice on Whites Creek; 85 ft S. of centerline of centerline of rd.; 4 ft E. of powerline pole; in ed #102 JJS 1956 610#	609. 919
Reference mark; 82 ft NWL of tablet; or square	n SW, and of MW. stone headwall of culvert; chiseled	604.62
U. E., Buffale Valley Church, 2.3 mi Si branch from E.; chiseled square	E. of; on N. end of E. stone headwall of culvert over	649.22
Buffalo and Lynn Greeks; 38 ft S. of centerline of Buffalo Greek rd.; 10	I.l mi MMW. of junction of rds. on ridge at head of conterline of junction of T—rd. SWL; 19 ft SWL of ft SWL of mailbox of B. Word; 3 ft SWL of 12—in. In concrete post; standard tablet stamped	
"103 JJS 1956 682"		682.018
Reference mark; 39 ft W. of tablet; en chiseled square	W. stame wingwall of bridge over Buffalo Crock;	681.62

は一

concrete box culvert; on culvert headwall; chiseled cross

Boltsfork; 500 ft N. of State Highway 3 steel bridge over Bolts Fork; at NW. corner of lawn at residence of Drew Hogan; 71 ft S. of SW. corner of Drew Hogan Store; 50 ft ENE. of chiseled square on rock outcrop across rd.; 38 ft SW. of mail and bottle cap in power pole; 20 ft ENE. of I-rd. W.; in concrete post; standard tablet stamped "IVA II 31 NY 1952" 669.66

38-082-31

38-082-31

Total American

ENDANGERED BENCH MARK NOTIFICATION

BENCH MARK STAMPING 65 NY 1952
STATE KY QUAD CEREDO QUAD NO. 177 KY- 57WKA-2 OH
NOTIFICATION RECEIVED (Date)
AUTHORIZATION AND SUPPLIES SENT FOR RESET (Date)
AGENCY/PERSON DOING RESET:
NAME GEORGE LOVELACE
AGENCY
ADDRESS 801 BELFONT
ASHLAND KENTUCKY 41/01
PHONE: (606) - 325 - 4774
FTS
REMARKS:
$l \cap l$
REPORT PREPARED BY JOHNWANTER
DATE
•

Place original in Quad Folder and a copy (with correspondence) in Suspense File. When reset is accomplished and notes typed and in Control List, discard notification form and copy.

HORIZONTAL CONTROL HORTH AMERICAN DATUM OF 1927

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

38-082-31 CEREDO QUADRANGLE 177 KY.-57 W.VA.-2 OHIO M3815-W8230/15 DIAGRAM NJ 17-4 HUNTINGTON

Boyd, Greenup, and Lawrence Counties, Ky.; Wayne County, W.VA.; and Lawrence County, Ohio

Edition of 1/4/77


PR: CRY/rmm

GRAYSON

(178 KY.)

Plane coordinates are based on Lambert projection, Kentucky, North Zone; West Virginia, South Zone, and Chio, South Zone Only the permanent marks are listed for control classified obsolete and are not shown on sketch

IRONTON
(5. OHIO-191 KY.)



LOUISA (160 KY.-42 W.VA.) GUYANDOTTE (56 W.VA.-1 OHIO)

. DISCLAIMER

We no longer attest to the validity of the positions listed for horizontal control established by transit traverse procedures. This control is now considered OBSOLETE and is included in this list for the purpose of identification only.

INDEX OF PERMANENT MARKS

MARK (USGS)	PAGE NO.
TVA TT 31 NY 1952 TVA TT 32 NY 1952 TVA TT 33 NY 1952 TVA TT 49 NY 1952 TT 4 GBG 1955 574 TT 6 GBG 1955 562 TT 7 GBG 1955 578 TT 8 GBG 1955 568 TT 9 GBG 1955 581	3 3 3 4 4 4
USED 566.31	3 4

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE 0 1 17

The following positions are considered **OBSOLETE**. To be used only to locate permanent marks in the field.

By M. L. Bennett (TVA), 1952; Fieldbooks MS 30208, 30209, 30210

Boltsfork; 500 ft N. of State Highway 3 steel bridge over Bolts Fork; at NW. corner of lawn at residence of Drew Hogan; 71 ft S. of SW. corner of Drew Hogan Store; 50 ft EME. of chiseled square on rock outcrop across rd.; 38 ft SW. of nail and bottle cap in power pole; 20 ft ENE. of I-rd. W.; in concrete post; standard tablet stamped "TVA IT 31 NY 1952"

Ky. N) X = 2.444.692

Y = 282.913

38 15 59.89

82 42 03.96

Alley; 0.5 mi S. of East Fork Methodist Church, along State Bighway 3; 2.1 mi N. of Highway 3 bridge at Boltsfork; on property of Clem Bromfield; between brick siding frame house and white barn; 55 ft WNW. of chiseled square on concrete base once used for gasoline pumps; 52 ft WNW. of nail and bottle cap in 12-in. oak tree; 50 ft SW. of centerline of hwy.; 40 ft SE. of E. corner of barn; 2 ft NE. of nail and bottle cap in power pole; in concrete post; standard tablet stamped "TVA TT 32 NY 1952"

X = 2.442.612 Y = 293.557

38 17 45.45

82 42 27.80

Alley, 1.3 mi W. of junction of U.S. Highway 23, along Garner Road; 0.5 mi NE. of T-rd. S.; 41 ft WNW. of painted cross on large fencepost; 22 ft NW. of centerline of rd.; 8 ft NE. of nail and bottle cap in 14-in. ash tree; 6 ft W. of nail and bottle cap in 12-in. ash tree; 4 ft NW. of pasture fence; in concrete post; standard tablet stamped "TVA TI 33 NY 1952"

X = 2.435.281

Y = 293.746

38 17 48.52

82 43 59.70

By M. L. Bennett (TVA), 1952; Fieldbook MS 30210

Princess, at junction of U.S. Highway 60 and State Highway 5; on U.S. Highway 60 right-of-way; 84.5 ft SE. of and level with centerline of T-rd. NW.; 14.4 ft NE. of 30-in. elm; 64.0 ft NE. of centerline of Y-rd. N.; 50 ft SW. of SE. end of culvert; in concrete post; standard tablet stamped "TVA TT 49 MY 1952"

X = 2.431.073

Y = 326.069

38 23 08.70

82 44 45.87

By G. B. Grunwell, 1955; Book AH 400

Getaway, about 3.9 mi NW. along State Highway 243 from Methodist Church; in sec. 3, T 1N, R 17 W.; about 1.1 mi W. of 20-ft bridge and side road NW.; at junction of drive N. to two-story white house; 25.5 ft N. of centerline of rd.; 32 ft E. of centerline of drive; 2.5 ft NW. of telephone pole; 17 ft SE. of SE. corner of garage; about 4 ft above level of hwy.; in concrete post projecting 2 in.; standard tablet stamped "TT I RCD 1955 674"

X = 2.492.455

Y = 366.797

38 29 40.63

82 31 45.54

STATION DESCRIPTION PLANE COORDINATES, FEET

LATITUDE

LONGITUDE 0 1 #

OBSOLETE MARKS (Cont'd.)

Chesapeake, 2.1 mi W. of, along U.S. Highway 52, thence 2.0 mi N. along Buffalo Creek Road; at Buffalo Creek School and junction of Little Buffalo Creek Road; 34 ft N. and 58 ft W. of junction; 100 ft NW. end of bridge; 3 ft N. of yard fence corner; 55 ft S. of rd. fork W.; about 5 ft above intersection of rd. N.; in concrete post; standard tablet stamped "TT 4 GBG 1955 574"

Ky. N) X = 2.499.863

Y = 349.328

38 26 46.60

82 30 16.53

Chesapeake, about 3.0 mi W. of post office, along U.S. Highway 52; at Lock No. 28 on N. bank of Ohio River; 7 ft S. of S. face of lockhouse; 1 ft S. of M. edge of walk; 6 ft E. of center of front steps; in walk at S. face of lockhouse; USED standard brass plug designated "566.31"

X = 2,500,739 Y = 337,440

38 24 48.94

82 30 08.37

Huntington, 2.9 mi W. of corner of Fourth Avenue and Sixth Street, along U.S. Highway 60, thence 0.2 mi NW. along West 28th Street to river levee; at pump station at mouth of Four Pole Creek; 67 ft ME. of ME. corner of pump building; 14 ft S. of SE. corner of concrete platform; on top of levee; 2 ft ME. of corner post for guardrail; in concrete post; standard tablet stamped "IT 6 GBG 1955 562"

X = 2,500,973 Y = 335,380

38 24 28 53

82 30 05.92

Ceredo, about 2.2 mi E. of, along U.S. Highway 60 and Spring Valley Road; 4.3 mi W. of Huntington (corner of Fourth Avenue and Sixth Street), along Highway 60 and rd. to Spring Valley rd.; at junction of rds. at S. end of viaduct over C. & O. Ry.; about 100 ft SW. of small concrete block shed; 64 ft SE. of SE. corner of sidewalk at S. end of viaduct; 51 ft W. of vertical 3-in. pipe in gashine; 32 ft S. and 34 ft E. of junction of I-rd.; 28 ft S. of, and about level with centerline of rd. opposite; 26 ft E. of rd. sign; in concrete post; standard tablet stamped "TT 7 GBG 1955 578" (Not found, 1968)

X = 2.496.621 Y = 330.930

38 23 45.36

82 31 01.63

Spring Valley Store, 1.5 mi W. of, along paved rd.; 3.1 mi NE. of junction of paved rd. with State Highway 75; 1.0 mi W. of entrance to Veterans Administration Hospital; at rd. junction on curve in front of residence of Lloyd Ward; 42 ft S. and 36 ft W. of centerline of main rd. and rd. tangent W.; 19 ft S. and 34 ft E. of graveled I-rd. N.; 27 ft W. of, and about 3 ft higher than centerline of main rd. opposite; 10 ft N. of fence corner; 2 ft E. of stone retaining wall; in concrete post; standard tablet stamped "TT 8 GBG 1955 568" (Reported destroyed, 1957)

X = 2,492,560 Y = 323,675

38 22 34.41

82 31 54.33

Spring Valley Store, 2.9 mi S. of, along rd.; 2.4 mi S. of entrance to U.S. Veterans Hospital; at entrance gate to Camp Mad Anthony Wayne; 1.8 mi N. of junction of State Highway 75 and Spring Valley Road; 46 ft SW. of pole No. 486 - 46; 37 ft due E. of entrance to camp; 2 ft NW. of large rock in row of rocks at entrance gate; in concrete post flush with lawn; standard tablet stamped "TT 9 GBG 1955 581"

X = 2.498.042

Y = 320.926

38 22 06.22

82 30 46.15

SUPPMENTAL

By W. C. Elder, 1958; Book AH 542

. MGS standard triangulation station disk stamped "LAMGDOM 1934"

Ky. H) X = 2.490,270.30 Y = 361,263.38

38 28 46.344

3 82 32 14.306

LANGDON 1934, 0.3 mi NW. of; W. of hwy.; 28 ft N. of fence; 12 ft W. of clump of trees; reinforcing rod; designated LANGDON + 1

X = 2,488,826

Y = 361,958

38 28 53.47

82 32 32.30

Coalgrove, 0.7 mi ME. of; near S. edge of sec. 31, I. 1 M., R. 18 W.; about 0.2 mi S. of State Highway 243; M. of transmission line and E. of fenceline; designated MEWCASTLE HILL LOT + 1 B

X = 2,462,236

Y = 367,017

38 29 48.22

82 38 05.54

Coalgrove, 0.4 mi ME. of; N. of State Highway 243 at I—rd. N.; at SW. corner of Zoar Baptist Church; on SW. corner of sidewalk; chiseled square designated MEWCASILE HILL LOT + 1 C

X = 2.463.917

Y = 368,715

38 29 59.36

82 37 44.13

cerido qualifotio Z.

Station: FLAGPOLE / Not on and 1

County: Lawrence

State: Ohic

Observer: G. B. Grunwell

Year: 1955 Datum: Prelim. 1927 N.A.D.

Description:

At U. S. Lock and Dam No. 28, at W. edge of office building; flagpole

W.Va. s. X = 1,569,530

Y = 518,210

To Station—	[Latitude 38 24 48.84 To Station— Azimuth			Longitude 82				Distance		
East Base	308	, 50 11	n	° 128	5 0	24	"	Feet Dist Log_Meters 2185	Miles 0.414	
WHTN (Tower)	313	42 58		133 171				10,784 2044	2.042 0.387	
iest Base		21 17								
	,									
÷										
	-									
•										

Station: TANK (V.A. Hospital)

County:

"MAGGET A

State: W. Va.

Observer: 0, B. Orangell

Year:1950 Datum:

N.A.S.

Description: Bank AH AUT 3

(Vacarapied)

Aunbingbon, 5.0 mi by rd. SW. of dominate see, near Spring Valley; at V. S. Veterana Abrinistration Hospital; server of knot finial on red and white disclosed main water tent.

W. Va. S.) X = 1,565,439

Y = 504,875

[Latitude 35 83 36 37						Longitude 80 30 57.45]					
To Station—	Azimuth					Back Az	imuth	Dis	Distance		
	9	<i>y</i>		Ð	0	3	<i>;</i> ;	kozynajkk Peet	Miles		
Oakland (USOSUS)	88	State of Sta	04		262	20	ĸġ.	38,320	7.239		
Langdon (USC&OS)		43	30		350	11 (2) 11 (2) 12 (2)	\$ 5	37,924	7.182		
					-						
<i>*</i>								The state of the s			
	Manager of the second of							Victorial Basis and Audies			
								* 9 manual name name name name name name name name			

United states department of the interior—geological adryby

Cerido - 2- oko

Station: LANGDON (U.S.C. & G.S.)

County: Lawrence

State: ohio

Observer: G. B. Grunwell Year: 1955 Datum: 1927 N.A.D.

Description:

Station is on a high knob near the heads of Rankin Creek and Buffalo Creek, about 5.75 mi E. of center of Ashland, Ky., about 6 mi NNE of Kenova, W.Va., on property of Norris Langdon.
Surface, reference and azimuth marks are standard bronze disks

set in concrete cylinders.

Underground mark is a standard bronze disk set in concrete. Reference mark 1 is N. of station at same elevation.

Reference mark 2 is E. of station, about 10 ft lower, at S. edge

of dim rd. past station.

Azimuth mark is ENE. of station, 10 ft E. of centerline of dirt

rd., about 125 yds N. of Langdon home.

To reach from Huntington, W.Va., take U.S. Highway 52 N. across Ohio River Bridge, go for 0.25 mi, turn right, (N) on gravel T-rd. Follow main road ahead for 1.85 mi and take right fork. Keep main rd. from here for 3.0 mi., turn sharp left at rd. junction. Go up this rd. for 4.4 mi and turn left at rd. junction. Proceed about 100 yds and turn at crossroads up hill. Go 0.35 mi to top of grade opposite station. It is on a small knoll in apple orchard about 250 yds W. of Langdon home, and 81 ft ENE. of dead snag.

A 10-ft stand was required.

W.Va. S. X = 1,559,940

Y = 542,396

[Latitude 38 28 46.344

Longitude82 32 14.306

To Station-Azimuth Back Azimuth Distance Miles Log. Meters 36 47 17.4 Oakland (USC&GS) 216 43 09.6 53,041 10.046 272 33 35.0 315 48 02 316 03 11 92 40 02.4 49,564 Motts (A.M.S.) 9.389 WPLH (Tower)
WSAZ (TV Tower) 135 51 48 41,544 7.868 136 07 19 45,822 8.678 WHTN (Tower) 330 31 36 RADIO 2 (Tower) 337 34 32 TANK (V.A. Hosp.) 350 42 43 WHTN (Tower) 150 33 55 36,153 6.847 157 36 51 170 43 30 46,470 8.801 **3**7,924 7.182

Form 9-107a