



TERMINAL SECT. NO. 2. FOR RECTANGULAR PLATE WASHER REQUIREMENTS AT SPLICE SEE CUR. STD. DWG. **RBR-010**

PLAN VIEW


TERMINAL SECT. NO. 2



SECTION A-A



SECTION C-C



SECTION B-B

1. GENERAL

- a. SEE CUR. STD. DWGS. IN THE **RBB**, **RBI**, **RBR**, AND **RPM-SERIES** FOR OTHER RELATED GUARDRAIL DETAILS AND BRIDGE PLANS FOR BRIDGE WING DETAIL.
- b. SEE CUR. STD. DWG. **RDB-SERIES** FOR CURB BOX INLET TYPE B.
- c. GUARDRAIL CONNECTOR TO BRIDGE END TYPE A-1 IS FOR USE ON THE EXIT END OF A DIVIDED HIGHWAY.

2. MATERIAL REQUIREMENTS

- ALL HARDWARE SHALL BE GALVANIZED. (AASHTO M-232)
- 5/8" STEEL PLATE "A" (AASHTO M-270)
- 7/8" HEX HEAD BOLTS OR STEEL THREADED RODS (LENGTH AS SHOWN)
- 7/8" HEAVY HEX NUTS (7/8" THICK) (AASHTO M-291)
- 7/8" FLAT WASHERS (3/16" THICK) (AASHTO M-293)
- 7/8" BEVELED WASHERS (5/16" MEAN THICKNESS) (AASHTO M-293)
- BOTH THE BOLT AND THREADED ROD SHALL HAVE A MINIMUM OF 50,000 LBS. TENSILE STRENGTH AT THE NARROWEST POINT.

3. CONSTRUCTION METHODS

- a. ELIMINATE EXTRA OFFSET BLOCKS WHEN CURB BOX INLET TYPE B IS NOT REQUIRED.
- b. HOLES TO BE FORMED THROUGH BRIDGE WING WITH 1" I.D. PLASTIC PIPE FOR 7/8" BOLTS. PLASTIC PIPE SHALL REMAIN IN PLACE.

4. METHOD OF MEASUREMENT AND BASIS OF PAYMENT

- a. GUARDRAIL CONNECTOR TO BRIDGE END TYPE A-1 SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE EACH, WHICH INCLUDES TERMINAL SECT. NO. 2, RAIL ELEMENTS, SPACER TUBE, HARDWARE AND ALL OTHER INCIDENTALS NECESSARY TO COMPLETE THE INSTALLATION. STEEL "W" BEAM GUARDRAIL (SINGLE FACE) AND ISLAND HEADER CURB ARE SEPARATE BID ITEMS WHICH ARE ALWAYS REQUIRED. CURB BOX INLET TYPE B IS A SEPARATE BID ITEM THAT WILL BE USED WHEN REQUIRED FOR BRIDGE END DRAINAGE.

BID ITEMS AND UNIT TO BID	
GUARDRAIL CONNECTOR TO BRIDGE END TY A-1	EACH
GUARDRAIL-STEEL "W" BEAM-S FACE	LF
ISLAND HEADER CURB TYPE 1 OR 2	LF
CURB BOX INLET TYPE B (AS REQUIRED)	EACH

- b. THE PLASTIC PIPE AND COST OF FORMING SHALL BE INCLUDED IN THE UNIT PRICE BID FOR BRIDGE SUPERSTRUCTURE CONCRETE.

- ⑤ ISLAND HEADER CURB. TRANSITION FROM ISLAND CURB SHAPE TO SHAPE ON BRIDGE WING WITHIN 7'-3". LENGTH OF CURB VARIABLE (22'-3" WHEN L=5'-0") (17'-3" WHEN L=10'-0") (12'-3" WHEN L=15'-0") (7'-3" WHEN L=20'-0"). ON THE APPROACH END CONSTRUCT 25'-0" OF ISLAND HEADER CURB EVEN WHEN CURB BOX INLET TYPE B IS NOT REQUIRED.

- ⑥ 6'-4" WHEN L=5'-0"
- 11'-4" WHEN L=10'-0" ★
- 16'-4" WHEN L=15'-0"
- 21'-4" WHEN L=20'-0"

7. CURB BOX NOT REQUIRED UNLESS NEEDED FOR DRAINAGE.

- ★ 10'-0" LENGTH IS REQUIRED UNLESS OTHERWISE NOTED.
- L EQUALS THROAT LENGTH OF BOX.

USE WITH CUR. STD. DWGS.
BHS-008 RBC-002 RBC-003 RBR-010

KENTUCKY
DEPARTMENT OF HIGHWAYS
GUARDRAIL CONNECTOR
TO BRIDGE END
TYPE A-1

STANDARD DRAWING NO. RBC-006-01
SUBMITTED *[Signature]* DATE 02-26-20
APPROVED *[Signature]* DATE 02-26-20

~ MAINTENANCE NOTES ~

- 1. NOT FOR NEW CONSTRUCTION. ONLY USE FOR REPAIRING OR RESTORING EXISTING HARDWARE.
- 2. FOR NEW CONSTRUCTION, REFER TO **BHS-013** AND **BHS-014** FOR THRIE-BEAM CONNECTIONS.
- 3. USE 3500 PSI CONCRETE FOR REPAIRS TO EXISTING JERSEY SHAPES.