



~ NOTES ~

- | | | |
|----------------------------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BID ITEMS AND UNIT TO BID | | |
| SINGLE VEHICULAR WOVEN WIRE GATE | EACH | 4. THE CONTRACTOR IS NOT TO ORDER GATES UNTIL THEIR NECESSITY AND LOCATION HAVE BEEN CERTIFIED BY THE ENGINEER. |
| OR | | |
| DOUBLE VEHICULAR WOVEN WIRE GATE | EACH | 5. WOVEN-WIRE FABRIC USED IN THE GATES SHALL EITHER BE ALUMINUM-COATED STEEL NO. 1047-6-9 OR ZINC-COATED STEEL NO. 1047-6-9. |
| OR | | |
| PEDESTRIAN WOVEN WIRE GATE | EACH | 6. NPS = NOMINAL PIPE SIZE - ASTM F1083 AND F1043 (HEAVY INDUSTRIAL FENCE) SHALL GOVERN. |
| CONCRETE-CLASS B | CUYD | 7. GATES SHALL HAVE HEAVY PRESSED STEEL CORNERS SECURELY RIVETED OR SHALL BE MACHINE NOTCHED AND ELECTRICALLY WELDED SO AS TO BE RIGID AND WATER TIGHT. ALL WELDED JOINTS SHALL BE CLEANED AND PAINTED WITH TWO (2) COATS OF ALUMINUM PAINT. |
- ① 6' TO 13' WIDTH FOR SINGLE GATE AND 12' TO 26' WIDTH FOR DOUBLE GATE.
- ② 4' TO 6' WIDTH
3. FABRIC TIE WIRES SHALL BE SPACED 1'-0" ON CENTERS.

KENTUCKY DEPARTMENT OF HIGHWAYS	
WOVEN WIRE GATES	
STANDARD DRAWING NO. RFG-001-07	
SUBMITTED <i>W. S. G. Seal</i>	12-01-15
DESIGNED BY <i>W. S. G. Seal</i>	DATE
APPROVED <i>W. S. G. Seal</i>	12-01-15
STATE HIGHWAY ENGINEER	DATE