



NOTES

1. THE BID ITEM PER SQUARE YARD BETWEEN POINTS (A) AND (B) SHALL BE "MOUNTABLE MEDIAN TYPE 7A".
2. THE VARIABLE LENGTH MOUNTABLE MEDIAN BETWEEN POINTS (A) AND (B) SHALL MEET THE CURRENT REQUIREMENTS OF STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION.
3. LIP INTEGRAL CURB TERMINATES AT POINT (C) (SEE PLANS).
- ④ CROSS SLOPE OF 2% ON TANGENTS AND PARALLEL PAVEMENT CROSS SLOPE ON SUPERELEVATED SECTIONS.
- ⑤ 1/2" PREMOLDED EXPANSION JOINT MATERIAL.
- ⑥ TRANSVERSE JOINTS IN THE MOUNTABLE MEDIAN BETWEEN POINTS (A) AND (B) SHALL BE CONSTRUCTED AND SEALED IN THE SAME MANNER AS THE JOINTS IN THE ADJOINING CONCRETE PAVEMENT.

USE WITH RIGID PAVEMENT

KENTUCKY
DEPARTMENT OF HIGHWAYS

MOUNTABLE MEDIAN
TYPE 7A

STANDARD DRAWING NO. RPM-015-03

SUBMITTED *John B. Sackett* 12-1-99
DIRECTOR DIVISION OF DESIGN DATE

APPROVED *F. M. [Signature]* 12-1-99
STATE HIGHWAY ENGINEER DATE