



CHANNELIZED INTERSECTION ON A TWO DIRECTIONAL TWO LANE FACILITY

LEGEND	
⊗	TYPE V BI-DIRECTIONAL (YELLOW)
□	TYPE V MONO-DIRECTIONAL (WHITE)
	RAISED OR FLUSH MEDIAN
	MARKINGS (YELLOW)
	MARKINGS (WHITE)

GENERAL NOTES

1. MARKERS INSTALLED ALONG DASHED YELLOW CENTERLINES SHALL BE PLACED BETWEEN AND IN LINE WITH THE SKIPS.
- ② MARKERS INSTALLED ALONG EDGE LINES OR CHANNELIZING LINES SHALL BE PLACED SO THAT THE NEAR EDGE OF THE CASTING IS NO MORE THAN 1" FROM THE NEAR EDGE OF THE LINE.
3. MARKERS SHALL NOT BE INSTALLED ON TOP OF THE PAVEMENT JOINT. OFFSET MARKERS A MINIMUM OF 2" FROM THE PAVEMENT JOINT. ENSURE THAT THE FINISHED LINE OF MARKERS IS STRAIGHT WITH MINIMAL LATERAL DEVIATION. MARKERS MAY BE ELIMINATED AT THE DISCRETION OF THE ENGINEER.

DRAWING NOT TO SCALE

KENTUCKY DEPARTMENT OF HIGHWAYS		
PAVEMENT MARKER ARRANGEMENT CHANNELIZED INTERSECTION		
STANDARD DRAWING NO. TPM-145-02		
SUBMITTED	<i>B. Allen Wolf</i> DIRECTOR OF TRAFFIC OPERATIONS	12-2-11 DATE
APPROVED	<i>[Signature]</i> STATE HIGHWAY ENGINEER	12-2-11 DATE