



1. DEVICES SIMILAR TO THOSE DEPICTED SHALL BE PLACED FOR OPPOSITE DIRECTION OF TRAVEL.
2. THE SIZE OF SIGNS 1 THRU 3 SHALL BE 48" X 48" IF THE SPEED LIMIT IS 45 MPH OR GREATER. OTHERWISE, 36" X 36" SIGNS MAY BE USED.
3. THE ADVISORY SPEED LIMIT ON SIGN 3 SHALL BE DETERMINED BY THE ENGINEER.
4. PAVEMENT MARKINGS WHICH ARE NO LONGER APPLICABLE SHALL BE OBLITERATED BY AN APPROVED METHOD.
5. SPACING OF CHANNELIZING DEVICES SHOULD NOT EXCEED 20'.
- ⑥ IF THE TANGENT DISTANCE ALONG THE TEMPORARY DIVERSION IS MORE THAN 600 FEET, A REVERSE CURVE SIGN, LEFT FIRST, SHOULD BE USED INSTEAD OF THE DOUBLE REVERSE CURVE SIGN, AND A SECOND REVERSE CURVE SIGN, RIGHT FIRST, SHOULD BE PLACED IN ADVANCE OF THE SECOND REVERSE CURVE BACK TO THE ORIGINAL ALIGNMENT. WHEN THE TANGENT SECTION OF THE DIVERSION IS MORE THAN 600 FEET, AND THE DIVERSION HAS SHARP CURVES WITH RECOMMENDED SPEEDS OF 30 MPH OR LESS, REVERSE TURN SIGNS SHOULD BE USED.
- ⑦ RAISED PAVEMENT MARKERS ARE REQUIRED ONLY FOR HARD SURFACE ROADWAYS. TYPE IVA MARKERS SHALL BE MAINTAINED THROUGHOUT THE ENTIRE LIMITS OF THE DIVERSION AT A SPACING OF 20'.

- LEGEND**
- TYPE III BARRICADE
 - SIGN
 - CHANNELIZING DEVICES
DRUMS
TYPE II BARRICADES
 - PAVEMENT MARKERS
TYPE IVA
(BI-DIRECTIONAL YELLOW)

DRAWING NOT TO SCALE
USE WITH CURRENT STD. DWG.
TTD-110

SIGNING AND SPACING TABLE			
ROAD TYPE	A	B	C
EXPRESSWAY/ FREEWAY	1000'	1600'	2600'
SP. LT. ≥ 45 MPH*	500'	500'	500'
SP. LT. ≤ 40 MPH*	250'	250'	500'

*NOTE: USE NORMAL POSTED SPEED LIMIT

**KENTUCKY
DEPARTMENT OF HIGHWAYS**

**ROAD CLOSURE
WITH
DIVERSION**

STANDARD DRAWING NO. TTC-150-02

SUBMITTED: *B. Allen Wolf* 12-2-11
DIRECTOR OF TRAFFIC OPERATIONS DATE

APPROVED: *[Signature]* 12-2-11
STATE HIGHWAY ENGINEER DATE