
BEGIN HIGHER FINES ZONE

R2-10


END HIGHER FINES ZONE

R2-11



8" (MIN.) FY

BEGIN HIGHER FINES ZONE



8" (MIN.) FY

WHEN **FLASHING**

S4-4P

APPLICATION

IN ACCORDANCE WITH KRS 189.2327, IN ORDER FOR HIGHER FINES TO BE ESTABLISHED IN A HIGHWAY WORK ZONE, SIGNS INFORMING DRIVERS OF THE WORK ZONE AND THAT FINES ARE HIGHER MUST BE DISPLAYED AND AT LEAST ONE (1) BONA FIDE WORKER MUST BE PRESENT.

THE ENGINEER MAY DETERMINE WHETHER TO ESTABLISH A HIGHER FINES ZONE WITHIN A HIGHWAY WORK ZONE BASED ON ENGINEERING JUDGMENT.

- ~ NOTES ~
- 1. THE BEGIN AND END HIGHER FINES ZONE SIGNS SHALL BE 36" X 48" FOR FREEWAYS AND EXPRESSWAYS AND 24" X 30" FOR OTHER ROADWAYS. "WHEN FLASHING" PLAQUES SHALL BE 36" X 18" FOR FREEWAYS EXPRESSWAYS AND 24" X 12" FOR OTHER ROADWAYS.
- 2. SIGNS SHALL HAVE A WHITE BACKGROUND WITH A BLACK LEGEND AND SHALL BE MOUNTED AT ELEVATIONS AND OFFSETS PRESCRIBED IN THE MUTCD.
- 3. USE ENGINEERING JUDGMENT WHEN DETERMINING THE LIMITS OF HIGHER FINES ZONES. FOR SHORT LENGTH PROJECTS WHERE WORK WILL OCCUR THROUGHOUT THE PROJECT LIMITS, LOCATE "BEGIN HIGHER FINES ZONE" SIGN ASSEMBLY BETWEEN THE LAST ADVANCE WARNING SIGN AND THE BEGINNING OF THE ACTIVITY AREA AND LOCATE THE "END HIGHER FINES ZONE" SIGN 250' IN ADVANCE OF THE "END ROAD WORK" SIGN. FOR LONG LENGTH PROJECTS WHERE WORK WILL NOT OCCUR THROUGHOUT THE PROJECT LIMITS, CONSIDER PLACING SIGNS ONLY IN AREAS WHERE ACTIVITY IS OCCURRING.
- 4. SIGNS SHALL BE DUAL-MOUNTED ON MULTI-LANE HIGHWAYS WHERE MEDIAN IS WIDE ENOUGH TO MAINTAIN LATERAL CLEARANCES AS PRESCRIBED IN THE MUTCD. WHERE CONSTRUCTION ONLY AFFECTS ONE DIRECTION OF A DIVIDED HIGHWAY WITH A BARRIER OR WIDE MEDIAN, SIGNS SHALL NOT BE ERECTED FOR OPPOSING DIRECTION.
- 5. ADDITIONAL SIGNS MAY BE REQUIRED FOR LONG HIGHWAY WORK ZONES OR WHERE RAMPS OR INTERSECTING STREETS JUNCTION WITHIN THE PROJECT LIMITS.
- 6. "BEGIN HIGHER FINES ZONE" SIGN ASSEMBLIES MAY INCLUDE A "WHEN FLASHING" PLAQUE AND FLASHING BEACONS. BEACONS SHALL BE YELLOW, AT LEAST 8" IN DIAMETER, AND MOUNTED HORIZONTALLY NEAR THE TOP OF THE SIGN ASSEMBLY. BEACONS SHALL FLASH ALTERNATELY AND CONFORM TO PART 4S OF THE MUTCD.
- 7. HIGHER FINES ZONES SIGNS SHALL BE COVERED IF A BONA FIDE WORKER WILL NOT BE PRESENT FOR A SIGNIFICANT PERIOD OF TIME. IN SUCH CASES. ASSEMBLIES WITH FLASHING BEACONS SHALL BE TURNED OFF.

BID ITEM TEMPORARY SIGNS UNIT TO BID SQFT

COMMONWEALTH OF KENTUCKY DEPARTMENT OF HIGHWAYS

HIGHER FINES

ZONE SIGNS

SEPIA NUMBER S-TTD-120-03