



~ NOTES ~

THE CONTRACT UNIT PRICE PER LINEAR FOOT FOR "CONC MEDIAN BARRIER TYPE  $\oplus$  TL5 56 IN SHALL BE FULL COMPENSATION FOR ALL MATERIALS, EQUIPMENT, LABOR AND INCIDENTALS NECESSARY TO COMPLETE THE WORK.

$\oplus$  A, B OR C DEPENDING ON PAVEMENT TYPE.

- ① LONGITUDINAL CONSTRUCTION JOINT WITHOUT TIE BARS IS REQUIRED AND SHALL BE PLACED AT THE LOCATION SHOWN OR MAY BE INSTALLED AT THE CORRESPONDING POINT ON THE OPPOSITE SIDE OF THE BARRIER, AT THE OPTION OF THE CONTRACTOR. IT SHALL BE REQUIRED ON THE LOW SIDE OF A SUPERELEVATED SECTION.
2. 3" RACEWAY (TYPICAL). SEE ELSEWHERE IN THE PLANS FOR LOCATION AND PAYMENT FOR RACEWAY WHEN REQUIRED.
- ③ CONSTRUCTION JOINT PERMITTED WHEN FIXED FORMS OR SLIP FORMS ARE USED.
4. SEE TYPE B BARRIER DETAIL FOR WALL DIMENSIONS.
- ⑤ TRANSVERSE EXPANSION JOINTS SHALL BE INSTALLED PER STANDARD SPECIFICATONS FOR ROAD AND BRIDGE CONSTRUCTION.
- ⑥ CONSTRUCT USING CONCRETE CLASS AA WITH A STRENGTH OF 4000 PSI.
7. WHEN MEDIAN BARRIER IS INSTALLED ON A STRUCTURE.

APPROX. QUANTITIES  
PER LINEAR FOOT

TYPE	6" WALL	
	CONC. IN CU. YDS.	STEEL IN POUNDS
A	0.28	11.47
B	0.22	11.47

THICKNESS FOR TYPE A. THE CONTRACTOR IS RESPONSIBLE FOR ADDITIONAL CONCRETE QUANTITIES.

*W. J. Layson*  
DIVISION DIRECTOR  
07-12-2021  
DATE



COMMONWEALTH OF KENTUCKY  
DEPARTMENT OF HIGHWAYS



DRAWING TITLE: SEPIA 019 - CONCRETE MEDIAN BARRIER FIXED-FORM OF SLIP-FORM (PERMANENT) (TL5 56" TALL WALL)

ITEM NO. COUNTY OF

SHEET NO.