



SECTION A-A

SECTION B-B

~ NOTES ~

- BID ITEMS AND UNIT TO BID  
MOUNTABLE MEDIAN TYPE 6A SQYD  
LIP CURB AND GUTTER LF
1. THE BID ITEM PER SQ. YD. BETWEEN POINTS (A) AND (B) SHALL BE "MOUNTABLE MEDIAN TYPE 6A".
  2. THE VARIABLE LENGTH MOUNTABLE MEDIAN BETWEEN POINTS (A) AND (B) SHALL MEET THE CURRENT REQUIREMENTS OF STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.
  3. CURB AND GUTTER TERMINATES AT POINT (C) (SEE PLANS).
  - ④ CROSS SLOPE OF 2% ON TANGENTS AND PARALLEL PAVEMENT CROSS SLOPE ON SUPERELEVATED SECTIONS.

USE WITH CUR. STD. DWG.  
RPM-100

KENTUCKY DEPARTMENT OF HIGHWAYS	
MOUNTABLE MEDIAN TYPE 6A	
STANDARD DRAWING NO. RPM-012-04	
SUBMITTED <i>W. P. Galt</i>	12-01-15
DIRECTOR OF DESIGN	DATE
APPROVED <i>Shelley</i>	12-01-15
STATE HIGHWAY ENGINEER	DATE