

Kentucky Statewide Model

Kentucky Model User's Group

October 3, 2007

Scott Thomson, PE



Overview

- Brief History of Statewide Model
- Two In-House Efforts
 - Springfield
 - Gilliland
- Lessons Learned
 - Successful Usage
 - Limitations

Model Development History

- 2003, Conversion from MINUTP started
- 2005, Version 1.0 completed
 - Truck component
 - Two TAZ levels, regular, and sub-zone
 - But, takes *2-6 hours* to run



Model Development History

- Version 2.0, rolled out in 2006
 - run time improved to 1 hour
 - select link added
 - but, future forecasts didn't seem reasonable



Model Development History

- So why use the statewide model?
- Model contains three levels of SE data
- Runtimes are very reasonable to run complete



Two Modeling Efforts

- ❖ Completion of the Springfield Bypass

- ❖ Washington County ~ Rural

- ❖ Impact study of a new I-64 Interchange

- ❖ Jefferson/Shelby County ~ Fringe Urban




In-house Modeling


- Our First Steps:
 - Established Area of Interest
 - drew a circle around the area
 - Used Allroads.shp
 - Added centerline file as a layer and traced new links
 - Filled in new road attributes
 - from HIS/EXOR database and similar roads



Springfield, KY



Study Area, 9 roads crossed



Ready to run the scenarios?

....Not yet.

- Developed spreadsheet to track results
 - desired bypass split= 50%
- Made initial no-build assignment run
 - Initially, 91% of traffic took the existing bypass
- Compared ADT's at screen line
 - The sum of the 9 routes was within 85%




Ready to run the scenarios?Not yet.

- Adjusted scenario speeds and travel times
 - took 10 iterations to get 67/33 split w/o signals
 - took 7 iterations to get 52/48 split w/ signals
- Adjusted speeds US150, north of town
- Opened the new link with similar bypass speeds



Post processing spreadsheet





Springfield Final Results

- Update network 2 hours
- Initial analysis 4 hours
- Calibration runs 28 hours
- Build scenario 2 hours
- Final Report 6 hours

total 42 hours



Gilliland Interchange Study



Our second project!

- Elements
 - Three general routes
 - Ten alternates
 - Estimate impact along adjacent links



Our second project!

Steps

- Established project limits
- Used Allroads.shp
 - added links for connectivity
- Ran calibration runs for current year
 - adjusted speeds to adjust trip assignments
 - established ‘feel’ for reasonable link speeds



Gilliland Interchange Study

Calibration Results

| BASE RUN COMPARISON TO ACTUAL COUNTS | | | | | | | | | |
|--------------------------------------|----------|-----|------|--------|----------|-------|---------|----------|------|
| | Segments | Sta | Year | Count | 2006 est | | | No Build | |
| US 60 | B | 998 | 2005 | 33300 | 34800 | -0.36 | (12118) | 28095 | 0.81 |
| | C | 16 | 2005 | 15900 | 16500 | -0.19 | (3097) | 14871 | 0.90 |
| | D | 119 | 2006 | 9640 | 9600 | -0.21 | (2035) | 8522 | 0.89 |
| | E | 596 | 2004 | 5920 | 6300 | -0.35 | (2044) | 5178 | 0.82 |
| I-64 | H | 19 | 2006 | 52000 | 52000 | -0.06 | (3054) | 50450 | 0.97 |
| | G | 19 | 2006 | 52032 | 52000 | -0.06 | (3054) | 50450 | 0.97 |
| KY-148 | Q | 996 | 2006 | 17100 | 17100 | -0.13 | (2221) | 15951 | 0.93 |
| | R | 251 | 2005 | 3421 | 3600 | -0.71 | (2442) | 2042 | 0.57 |
| | S | 369 | 2006 | 2010 | 2000 | -0.56 | (1129) | 1320 | 0.66 |
| KY-155 | T | 361 | 2004 | 14752 | 16300 | -0.15 | (2243) | 15137 | 0.93 |
| I-265 | J | O36 | 2006 | 69400 | 69400 | | (34383) | 49297 | 0.71 |
| | K | D01 | 2006 | 62100 | 62100 | -0.70 | (43485) | 34000 | 0.55 |
| | L | D35 | 2006 | 57500 | 57500 | -0.78 | (44635) | 27198 | 0.47 |
| KY-1531 | N | 117 | 2003 | 624 | 700 | -0.45 | (280) | 542 | 0.77 |
| KY-1531 | M | 117 | 2003 | 624 | 800 | -0.69 | (433) | 542 | 0.68 |
| KY-1848 | F | 522 | 2006 | 6524 | 6500 | -0.41 | (2668) | 4991 | 0.77 |
| | | | | 109191 | 218200 | | | 91% | 77% |
| | Wa | | | | | | | 198091 | |

Gilliland Final Results

- Update network 6 hours
- Initial analysis 12 hours
- Calibration runs 70 hours
- Alternative runs 20 hours
- Final Report 18 hours

total 126 hours



Conclusions

- Model is an ADT or “average hr” model
- Reasonable current year trip generation
- Study “screen circle” for reasonableness
- Link speeds need to be adjusted



Conclusions

- Calibrated Model provided good results
 - Signals can create up to 60% time penalty
 - Consider impact of curves and hills
 - Consider time penalty for stop signs



Model Limitations

- ✗ Model does not consider congestion
- ✗ Truck speeds do not equal Auto speeds
- ✗ Statewide Model not suited for future projections
- ✗ Eastern Kentucky area doesn't calibrate well



Model Limitations

- ✓ Model IS sensitive to speeds
- ✗ Model is NOT sensitive to link capacity



Successful Models Simulated

Rural interchanges

New rural routes

Small community bypasses

Ramp closures

Scheduled Interstate lane closures



Questions??
Comments??

Kentucky Statewide Model

October 3, 2007

Scott Thomson, PE

