

Appendix C

Adequacy Ratings

ADEQUACY RATINGS

Section Length	Condition	Safety	Service	Composite	Percentile	IRI	VSF	CRF	Lane Width	Access Control	Median Type	Median Width	Shoulder Type	Shoulder Width_R	Peak Capacity	Speed Limit	Horizontal Align	Vertical Align	Critical Rate Factor	Median Value Calculation	Design Speed	HOR Exceptions	Actual Rate	Average Rate	Critical Rate
0.066	9	23.5	15	47.5	2.77	227	0.1	-1	12	3	4	0	2	3	2163	35	1	1	1.38	3	60	0	-1.00	-1.00	-1.00
10.741	30	21.4	15	66.4	14.73	111	0.11	0.949675	10	3	4	0	4	1	1434	55	3	0	1.1	3	55	0	295.27	210.70	310.92
1.078	30	18.5	15	63.5	11.8	115	0.16	1.644758	11	3	4	0	4	2	1474	55	3	3	1.57	3	55	0	790.10	210.70	480.38
1.048	30	31.8	20	81.8	56.58	101	0.31	1.434387	11	3	4	0	2	2	1920	55	4	2	0.57	3	55	0	543.50	210.70	378.91
7.691	30	5.5	20	55.5	3.53	105	0.3	0.902892	10	3	4	0	2	1	1945	55	3	4	1.13	3	55	2	244.40	210.70	270.68
12.933	30	35.4	15	80.4	51.6	100	0.25	0.644802	10	3	4	0	2	1	655	35	3	0	0.72	3	60	2	192.53	210.70	298.59
17.577	24	7.4	15	46.4	2.59	126	0.28	1.276753	10	3	4	0	2	1	835	35	3	1	1.38	3	50	3	349.66	210.70	273.86
13.683	30	14.5	19	63.5	7.12	114	0.56	0.887454	11	3	4	0	2	1	578	35	3	4	1.16	3	60	2	240.31	210.70	270.79
0.336	22.5	37.5	20	80	49.85	135	0.3	0.778305	11	3	4	0	2	4	1504	35	3	2	0.28	3	60	0	442.67	210.70	568.76

Furnished by KYTC Division of Planning