



LEGEND

- ⊠ SIGN
- ▣ TRUCK MOUNTED ATTENUATOR
- ☐ SWEEPER/BLOWER
- ⚡ FLASHING ARROW PANEL

~ NOTES ~

1. OPERATE FLASHING ARROW PANEL IN CAUTION MODE. THE ARROW PANEL SHALL BE TYPE B (60"X30") OR LARGER.
2. SIGNS 1 THRU 4 SHALL HAVE A BLACK BORDER AND LEGEND ON A BACKGROUND OF FLUORESCENT ORANGE SHEETING.
3. ALL VEHICLES IN THE STRIPING TRAIN SHALL BE EQUIPPED WITH HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS ON THE CAB.
4. THE LAST TRAIL VEHICLE IN THE WORK TRAIN SHALL BE EQUIPPED WITH A TRUCK MOUNTED ATTENUATOR (T.M.A.) IF LANES ARE 10' WIDE OR GREATER.
5. THE LEAD VEHICLE SHALL MAINTAIN VISUAL CONTACT WITH THE STRIPER WHENEVER POSSIBLE TO COORDINATE ON AND OFF THE ROAD MANEUVERS. THE WORK TRAIN SHALL BE REQUIRED TO PULL OFF THE ROADWAY PERIODICALLY TO ALLEVIATE TRAFFIC CONGESTION.
6. TWO-WAY RADIO COMMUNICATION SHALL BE MAINTAINED BETWEEN ALL VEHICLES IN THE WORK TRAIN.
7. THE SPACING BETWEEN VEHICLES IN THE WORK TRAIN SHOULD BE ADJUSTED, AS NEEDED, TO PROVIDE ADEQUATE SIGHT DISTANCE TO APPROACHING VEHICLES AND TO PROTECT THE FRESHLY APPLIED LINE.
8. VEHICLE-MOUNTED SIGNS SHALL BE MOUNTED IN A MANNER SUCH THAT THEY ARE NOT OBSCURED BY EQUIPMENT OR SUPPLIES. SIGN LEGENDS ON VEHICLE-MOUNTED SIGNS SHALL BE COVERED OR TURNED FROM VIEW WHEN WORK IS NOT IN PROGRESS.

BID ITEMS AND UNIT TO BID
 REFER TO SECTION 112 OF STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.

APPLICATION

THIS DRAWING APPLIES TO DURABLE STRIPING OPERATIONS ON TWO-LANE, TWO-WAY ROADWAYS INVOLVING THE PLACEMENT OF EDGE LINES ONLY.

DRAWING NOT TO SCALE

KENTUCKY DEPARTMENT OF HIGHWAYS	
MOBILE OPERATION FOR DURABLE STRIPING CASE III	
STANDARD DRAWING NO. TTS-130-02	
SUBMITTED <i>B. Allen Wolf</i>	12-01-15 DATE
DIRECTOR OF HIGHWAY OPERATIONS	
APPROVED <i>[Signature]</i>	12-01-15 DATE
STATE HIGHWAY ENGINEER	