



NOTES

METHOD OF MEASUREMENT AND BASIS OF PAYMENT

MODULAR GLARE SCREEN \triangle - \square SHALL BE PAID FOR AT THE CONTRACT UNIT PRICE BID PER LINEAR FOOT AND SHALL INCLUDE ALL LABOR, MATERIALS AND OTHER INCIDENTALS NECESSARY TO COMPLETE THE INSTALLATION .

- \triangle 24" , 36" , OR 48" (HEIGHT)
- \square (G) = GREEN

CONSTRUCTION METHODS

INSTALLATION SHALL BE COMPLETED IN ACCORDANCE WITH THE MANUFACTURES RECOMMENDATIONS (A COPY OF WHICH SHALL BE FURNISHED TO THE ENGINEER) .

- ① 3" WIDE STRIP OF REFLECTIVE MATERIAL AROUND BLADE EVERY 10'-0" ON CENTER.
2. MODULAR UNITS ARE FURNISHED IN LENGTHS OF 9'-8" . THE DISTANCE BETWEEN EACH UNIT SHALL BE 4" WHEN INSTALLED.

KENTUCKY DEPARTMENT OF HIGHWAYS		
SYRO STEEL MODULAR GLARE SCREEN (FOR CONC. MEDIAN BARRIERS)		
STANDARD DRAWING NO. RBM-030-03		
SUBMITTED	<i>John B. Sackett</i> DIRECTOR DIVISION OF DESIGN	12-1-99 DATE
APPROVED	<i>J. M. Powell</i> STATE HIGHWAY ENGINEER	12-1-99 DATE