

- (1) SPAN OF BOX CULVERT.
- (2) RISE OF BOX CULVERT.
- 3. FOR DIMENSIONS, QUANTITIES, AND BILL OF REINFORCEMENT SEE CURRENT STANDARD DRAWINGS RDH-1100, RDH-1200 AND RDH-1300 SERIES.
- 4. DIMENSIONS FROM CONCRETE TO STEEL SHALL BE 2" CLEAR DISTANCE.
- 5. ENCIRCLED LETTERS , , INDICATE STEEL BAR LOCATIONS.
- 6. BARS(C),(G),(K),(V),(W) ARE SPACED 1'-0" O.C. ALL OTHER BARS SHALL BE EVENLY SPACED.
- 7. BARS(V)AND W ARE PLACED IN ORDER OF INCREASING LENGTHS, BEGINNING AT THE END OF EACH WING.
- 8. BARS(C)AND K ARE PLACED IN ORDER OF INCREASING LENGTHS, BEGINNING AT THE TOP OF EACH WING.
- 9. HEADWALLS LOCATED AT EDGE OF SHOULDERS SHALL BE PARALLEL TO CENTERLINE OF THE ROAD.
- 10. LIMITS OF APRON.
- 11. PAVING SHALL BE REQUIRED AND SHALL BE SLOPED IN DIRECTION OF FLOW EQUAL TO SLOPE OF BOX. FRONT FACE OF HEADWALL AND ENDS OF WINGS SHALL REMAIN VERTICAL.

## (LAYOUT AND STEEL PATTERN)

## KENTUCKY DEPARTMENT OF HIGHWAYS

PRECAST BOX CULVERT H-WALLS-15°-30°& 45° SK

(BOX RISE LESS THAN 6'-0")

STANDARD DRAWING NO. RDH-1010-02 DIRECTOR DIVISION OF DESIGN

STATE HIGHWAY ENGINEER