



~ NOTES ~

- BID ITEMS AND UNIT TO BID
MOUNTABLE MEDIAN TYPE 7A
LIP INTEGRAL CURB
- SQYD
LF
1. THE BID ITEM PER SQ. YD. BETWEEN POINTS (A) AND (B) SHALL BE "MOUNTABLE MEDIAN TYPE 7A".
 2. THE VARIABLE LENGTH MOUNTABLE MEDIAN BETWEEN POINTS (A) AND (B) SHALL MEET THE CURRENT REQUIREMENTS OF STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.
 3. LIP INTEGRAL CURB TERMINATES AT POINT (C) (SEE PLANS).
 - (4) CROSS SLOPE OF 2% ON TANGENTS AND PARALLEL PAVEMENT CROSS SLOPE ON SUPERELEVATED SECTIONS.

- (5) 1/2" PREMOLDED EXPANSION JOINT MATERIAL.
- (6) TRANSVERSE JOINTS IN THE MOUNTABLE MEDIAN BETWEEN POINTS (A) AND (B) SHALL BE CONSTRUCTED AND SEALED IN THE SAME MANNER AS THE JOINTS IN THE ADJOINING CONCRETE PAVEMENT.

INTENDED USE:
WITH RIGID PAVEMENT

USE WITH CUR. STD. DWG.
RPM-100

KENTUCKY DEPARTMENT OF HIGHWAYS	
MOUNTABLE MEDIAN TYPE 7A	
STANDARD DRAWING NO. RPM-015-04	
SUBMITTED <i>William P. Gullett</i>	12-01-15
<small>DIRECTOR, DIVISION OF DESIGN</small>	
APPROVED <i>[Signature]</i>	12-01-15
<small>STATE HIGHWAY ENGINEER</small>	
	DATE