



~ NOTES ~

1. FLASH ARROW PANELS TO DIRECT TRAFFIC RIGHT OR LEFT AS APPROPRIATE. FLASHING ARROW PANELS SHALL BE TYPE B (60"X30") OR LARGER.
 2. SIGNS 1 THRU 3 SHALL HAVE A BLACK BORDER AND LEGEND ON A BACKGROUND OF FLUORESCENT ORANGE SHEETING. SIGN 4 SHALL HAVE A BLACK BORDER AND LEGEND ON A BACKGROUND OF REFLECTIVE WHITE SHEETING.
 3. ALL VEHICLES IN THE STRIPING TRAIN SHALL BE EQUIPPED WITH HIGH-INTENSITY ROTATING, FLASHING, OSCILLATING, OR STROBE LIGHTS ON THE CAB.
 4. THE LAST TRAIL VEHICLE IN THE WORK TRAIN SHALL BE EQUIPPED WITH A TRUCK MOUNTED ATTENUATOR (T.M.A.) IF LANES ARE 10' WIDE OR GREATER.
 5. WHEN MORE THAN TWO LANES ARE TO BE CLOSED, SIGN 1 SHALL AGREE WITH THE NUMBER OF LANES CLOSED AND ADDITIONAL TRAIL VEHICLES SHALL BE USED.
 6. TWO-WAY RADIO COMMUNICATION SHALL BE MAINTAINED BETWEEN ALL VEHICLES IN THE WORK TRAIN.
 7. THE SPACING BETWEEN VEHICLES IN THE WORK TRAIN SHOULD BE ADJUSTED, AS NEEDED, TO PROVIDE ADEQUATE SIGHT DISTANCE TO APPROACHING VEHICLES AND TO PROTECT THE FRESHLY APPLIED LINE.
 8. VEHICLE-MOUNTED SIGNS SHALL BE MOUNTED IN A MANNER SUCH THAT THEY ARE NOT OBSCURED BY EQUIPMENT OR SUPPLIES. SIGN LEGENDS ON VEHICLE-MOUNTED SIGNS SHALL BE COVERED OR TURNED FROM VIEW WHEN WORK IS NOT IN PROGRESS.
- BID ITEMS AND UNIT TO BID
 REFER TO SECTION 112 OF STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION.

LEGEND

- ⚡ FLASHING ARROW PANEL
- ⊠ SIGN
- ⊠ TRUCK MOUNTED ATTENUATOR

DRAWING NOT TO SCALE

APPLICATION

THIS DRAWING APPLIES TO DURABLE STRIPING OPERATIONS INVOLVING MULTIPLE LANE CLOSURES ON MULTI-LANE ROADWAYS.

KENTUCKY DEPARTMENT OF HIGHWAYS	
MOBILE OPERATION FOR DURABLE STRIPING CASE II	
STANDARD DRAWING NO. TTS-125-02	
SUBMITTED <i>B. Allen Wolf</i>	DATE 12-01-15
<small>DIRECTOR OF SPECIAL TRAFFIC OPERATIONS</small>	
APPROVED <i>[Signature]</i>	DATE 12-01-15
<small>STATE HIGHWAY ENGINEER</small>	